Open Comments

SNo.	Basic Details	Clause/Subclause No.& Attachment	Paragraph No./Figure No./Table No.	Type of Comment	Comments/Suggestions along with Justification for the Proposed Change	Proposed Change/Modified Wordings	Remarks
	Name: Dr. Eapen P Joseph	4.1			Add sentence in the end	para 1 modified	
	Organisation: N/A	N/A					
Mobile	Email: jeapen@npcil.co.in Mobile: 9969512317 Comment ID #: PGD_2024-05-267733					Store bearings in a clean and dry environment to prevent contamination and	
						corrosion. Avoid areas with excessive	
						moisture, dust, or dirt that can damage the	
					As far as possible bearings shall be kept in	bearings. As far as possible bearings shall be	
			1	General	original packing.	kept in original packing.	
		5.2 N/A			Add as 5.2.8		
					Angular contact bearings and Taper Roller	5.2.8 Angular contact bearings and Taper	
					bearigs shall be installed in correct	Roller bearigs shall be installed in correct	
			8	Technical	orientation.	orientation.	
		6.3			Add	modified sentence	
		N/A					
						If the shaft does not have a proper surface	
						finish, it may risk in losing the fit "unless otherwise specified, as a guideline" the	
						surface finish for mounting/fitting may be	
					"unless otherwise specified as a guideline"	taken as follows:	
1			2	General	at the start of second sentence,		