अर्ध/पूर्ण रूप से प्रक्रमित गैर-दिशात्मक विद्युतीय इस्पात एवं पूर्ण रूप से प्रक्रमित दिशात्मक विद्युतीय इस्पात के लिए तप्त-बेल्लित और अतप्त-बेल्लित इस्पात की चद्दर — विशिष्टि

IS 18316: 2023

Hot-Rolled and Cold-Rolled
Steel Strips Intended for Processing
of Semi/Fully Processed Non-Grain
Oriented Electrical Steel or
Fully Processed Grain Oriented
Electrical Steel — Specification

ICS 77.140.50

© BIS 2023



भारतीय मानक ब्यूरो BUREAU OF INDIAN STANDARDS मानक भवन, 9 बहादुर शाह ज़फर मार्ग, नई दिल्ली - 110002 MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI - 110002

www.bis.gov.in www.standardsbis.in

## **FOREWORD**

This Indian Standard was adopted by the Bureau of Indian Standards, after the draft finalized by the Wrought Steel Products Sectional Committee had been approved by the Metallurgical Engineering Division Council.

Electrical steels, which utilizes the ferromagnetic properties of iron, are used in the cores of electromagnetic devices such as motors, generators, and transformers because of the ability of ferromagnetic materials to magnify the magnetic effects of current-carrying coils. Electrical steel is often referred to as silicon steel, as Si is the main alloying element. A need is felt to formulate a standard for units, which utilizes steels, for enhancing their electrical and magnetic properties.

This standard prescribes requirements for steels used for manufacture of electrical steels covered under various Indian Standards such as IS 648, IS 3024, IS 15391.

The composition of the Committee responsible for the formulation of this standard is given in Annex A.

For the purpose of whether a particular requirement of this standard is complied with the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2: 2022 'Rules for rounding off numerical values (*second revision*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

## Indian Standard

## HOT-ROLLED AND COLD-ROLLED STEEL STRIPS INTENDED FOR PROCESSING OF SEMI/FULLY PROCESSED NON-GRAIN ORIENTED ELECTRICAL STEEL OR FULLY PROCESSED GRAIN ORIENTED ELECTRICAL STEEL — **SPECIFICATION**

#### 1 SCOPE

This standard covers the general technical conditions for steel strips intended for further processing to produce non-grain oriented electrical steel in semi/fully processed condition and grain oriented electrical steel in fully processed condition.

#### 2 REFERENCES

The standards given below contain provisions which through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of these standards:

IS No. Title

IS 228 (all parts) Methods for chemical analysis of steels

IS 1730: 1989 Steel plates, sheets, strips and

> flats for structural and general purposes engineering Dimensions (second revision)

IS 1956 (Part 4) Glossary of terms related to iron : 2013 and steel: Part 4 Steel sheet and

strip (second revision)

IS 8910 : 2022/ General technical delivery

ISO 404: 2013 requirements for steel and steel

products (second revision)

IS/ISO 16160: Hot-rolled steel sheet products Dimensional and shape 2012

tolerances (first revision)

## 3 TERMINOLOGY

- **3.1** For the purpose of this standard the definitions given in IS 1956 (Part 4) shall apply.
- 3.2 Electrical Steels Unalloyed steels with particular requirements for magnetic or electrical properties (or) steels for sheets and strips containing only Si and/or Al as alloying element(s) and with

requirements for magnetic losses and for the minimum values for magnetic induction only.

#### 4 SUPPLY OF MATERIAL

- **4.1** General requirements relating to the supply of hot-rolled/cold-rolled carbon steel sheet/strips shall conform to IS 8910.
- 4.2 Hot-rolled and cold-rolled steel strip shall be supplied in coil form either with mill edges or sheared (slit) edges as agreed to between the manufacturer and the purchaser.
- **4.3** The material may be supplied in any one of the following conditions subject to mutual agreement between the supplier and the purchaser:
  - hot-rolled with or without pickling; and
  - b) cold-rolled condition Full hard/partially annealed.
- **4.4** The material shall be supplied as per the chemical composition given in Table 2.

## **5 DESIGNATION**

There shall be four grades of steel as given in Table 1.

Table 1 Designation and Grades of Steel (Clause 5)

Sl No.	Grade and Designation		
	Grade	Designation	
(1)	(2)	(3)	
i)	LS	Low silicon	
ii)	MS	Medium silicon	
iii)	HS	High silicon	
iv)	VHS	Very high silicon	

## 6 MANUFACTURE

Strips shall be made from steel manufactured by any process of steel making at the discretion of the manufacturer or as mutually agreed between the supplier and the purchaser.

## **7 CHEMICAL COMPOSITION**

**7.1** Ladle analysis of the material, when carried out either by the method specified in the relevant parts of IS 228 or any other national/international standard for instrumental/chemical method shall be as given in Table 2.

**7.2** In case of dispute the procedure given in the relevant part of IS 228 shall be the referee method.

## 7.3 Product Analysis

Permissible variation in case of product analysis from the limits specified in Table 2 shall be as given in Table 3.

**Table 2 Chemical Composition** 

(Clauses 4.4, 7.1 and 7.3)

Sl No.	Grade	Designation	Constituent, Percent					
			C Max	Si	S Max	P Max	Mn <i>Max</i>	Al Max
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
i)	LS	Low silicon	0.06	$\geq$ 0.10 to $<$ 0.60	0.020	0.30	1.00	0.50
ii)	MS	Medium silicon	0.05	$\geq$ 0.60 to $\leq$ 2.00	0.020	0.20	1.00	1.00
iii)	HS	High silicon	0.05	$\geq$ 2.00 to $<$ 3.00	0.020	0.20	1.00	2.00
iv)	VHS	Very high silicon	0.05	$\geq$ 3.00 to <6.00	0.020	0.20	1.00	2.00

NOTES

**Table 3 Permissible Variation for Product Analysis** (Clause 7.3)

SI No.	Constituent	Percentage Limit of Constituent	Variation Over the Specified Maximum or Under the Minimum Limits,
			Percent, Max
(1)	(2)	(3)	(4)
i)	Carbon	≤0.050	0.010
ii)	Manganese	≤1.00	0.040
iii)	Sulphur	$\leq 0.020$	0.005
iv)	Phosphorus	≤0.30	0.010
		$\geq$ 0.10 to <0.60	0.030
v)	Silicon	$\geq$ 0.60 to<2.00	0.100
,		$\geq 2.00 \text{ to} \leq 6.00$	0.150
vi)	Aluminium	≤0.50	0.05
,		$>0.50$ to $\leq 6.00$	0.10

<sup>1</sup> In case of material intended for semi processed CRNGO non alloy type, other limits for silicon content may be mutually agreed to between the manufacturer and the purchaser.

<sup>2</sup> The nitrogen content of the steel shall not be more than 0.012 percent.

<sup>3</sup> Restricted chemistry may be mutually agreed between the purchaser and the supplier.

#### **8 FREEDOM FROM DEFECTS**

The steel shall be free from segregation, laminations, surface flaws and other defects, which are detrimental to subsequent processing and ultimate use.

## 9 DIMENSIONS AND TOLERANCES (FOR HOT-ROLLED STEEL)

- **9.1** Unless otherwise agreed to between the supplier and the purchaser, standard dimensions of hot-rolled steel strip shall be as specified in IS 1730.
- **9.2** Unless otherwise agreed the thickness tolerances shall be as per IS/ISO 16160.

## 9.3 Crown

Crown is the difference in strip thickness from centre to edge.

Crown = 
$$t_c - (t_1 + t_2)/2$$

where

 $t_{\rm c}$  = thickness at centre of the strip width;

 $t_1$  and  $t_2$  = thicknesses measured at 40 mm inside of the two edges.

The crown of the hot-rolled mill edge steel strip meant for cold rolling shall be as follows:

For width up to and including 100 µm, Max 1 200 mm:

For width above 1 200 mm: 150 µm, Max

- **9.3.1** Any special tolerances to suit specific requirements shall be mutually agreed to between the manufacturer and the customer.
- **9.3.2** The difference in thickness across width at the two edges of slit strip shall not exceed the limits given below:

Sl No.	Nomina	l Thickness	Tolerance on Thickness Over Two Edges
	From	mm Up to and Including	mm
(1)	(2)	(3)	(4)
i)	_	3	0.06
ii)	3	4	0.08

## 9.4 Permissible Width Variations

The permissible tolerance on the nominal width of hot-rolled strip shall conform to the requirements specified in IS/ISO 16160.

## 9.5 Edge Camber

The edge camber tolerance shall be as indicated below:

Sl No.	Nominal Width		Measured Length	Can	ıber
	mm		mm	m	m
	From	Up to and Including		Mill Edge	Slit Edge
(1)	(2)	(3)	(4)	(5)	(6)
i)	_	600	2 500	_	10
ii)	600	1 500	2 500	25	15

# 10 DIMENSIONS AND TOLERANCES (FOR COLD-ROLLED STEEL)

## **10.1 Thickness Tolerances**

10.1.1 The allowable tolerance on the nominal thickness within the same acceptable unit shall be  $\pm$  8 percent of the nominal value for thickness less than or equal to 0.5 mm and  $\pm$  6 percent of the nominal value for thickness greater than 0.50 mm. The additional thickness due to welds, with respect to the measured thickness of the steel strip shall not

exceed 0.050 mm.

10.1.2 The difference in the thickness in a direction perpendicular to the direction of rolling shall not exceed 0.02 mm for thickness less than or equal to 0.5 mm and 0.03 mm for thickness 0.65 mm and 1.00 mm. The measurement shall be made using a micrometer with an accuracy of 0.001 mm. These tolerances apply only to the materials with a width greater than 150 mm.

10.1.3 The height of the weld if any and edge burr

shall not exceed 50 microns.

#### 10.2 Width Tolerances

**10.2.1** For material supplied with trimmed edges, the tolerances of mentioned below shall apply:

Sl No.	Nominal Width mm	Tolerance mm
(1)	(2)	(3)
i)	600 to ≤1000	+2.0/-0.0
ii)	>1000 to ≤1500	+3.0/-0.0

**10.2.2** For materials supplied with as rolled edges, the tolerances on nominal width should be  $\pm 20/-0$  mm.

10.3 Material required to tolerances other than those specified in 10.1 and 10.2 shall be subject to agreement between the purchaser and the manufacturer.

#### 11 DELIVERY

The material in the form of strips shall be supplied

in coils. The mass of the coil shall be as agreed to between the contracting parties.

#### 12 PACKING

Material with suitable packing shall be provided by the manufacturer/supplier to prevent damages and deterioration in quality during storage, handling and transport. The exact method of packing and weight of each packet shall be mutually agreed to between the purchaser and the supplier.

## 13 MARKING

13.1 Each strip/coil shall carry a metal tag or adhesive label/sticker bearing the cast number or identification mark or lot number traceable to the cast number and the manufacturer's name or trade mark or shall be legibly marked at top.

## 13.2 BIS Certification Marking

The product(s) conforming to the requirements of this standard may be certified as per the conformity assessment schemes under the provisions of the *Bureau of Indian Standards Act*, 2016 and the Rules and Regulations framed thereunder, and the product(s) may be marked with the Standard Mark.

Representative(s)

### ANNEX A

(Foreword)

#### COMMITTEE COMPOSITION

Wrought Steel Products Sectional Committee, MTD 04

CAII	Passarch & Davidonment Center for Iron &	SUDI MIDVIV PANEDIEE (Chairnarean

SAIL, Research & Development Center for Iron & Shri Nirvik Banerjee (*Chairperson*)
Steel, Ranchi

All India Induction Furnace Association, New Delhi
SHRI A. K. SHARMA
SHRI PRABHAKAR MISHRA (Alternate)

AM/NS Steel Hazira, Surat

SHRI DEEPAK GUPTA

SHRI KALPESH DAVE (Alternate)

Bharat Heavy Electrical Ltd, Bhopal Shri S. K. Mahajan Shri Arun Khare (*Alternate*)

Central Boilers Board, New Delhi Shri S. K. Jain

Organization

Cold Rolled Steel Manufacturers Association of Shri Rajiv Chaturvedi Shri N. K. Sood (*Alternate*)

DMRL, Ministry of Defence, Hyderabad SHRI R. V. S. NAGESH

Indian Machine Tools Manufacturers Association, Shri Y. Balaramaiah Bengaluru

Institute of Steel Development and Growth, Kolkata

SHRI P. L. RAO

SHRI SAJAL KUMAR GHORAI (Alternate)

Jindal Steel & Power Ltd (JSPL), Raigarh

SHRI MORESHWAR BORKAR

SHRI JOY DUTTA (Alternate)

JSW Ltd, Bellary

SHRI DEVASISH MISHRA

SHRI G. V. RAMANA (Alternate)

JSW Steel Ltd, Dolvi/Salem

SHRI SUBHASIS CHAKRABORTY

SHRI B. M. HASAN (Alternate)

Ministry of Defence (DGOFB), Kolkata Shri R.D. Barma

Ministry of Defence (DGQA), Ichapur,

SHRI K. YADAV

SHRI G. SUBBA RAO (Alternate)

Ministry of Shipping, New Delhi
SHRI ANIL PRUTHI
SHRI RAMJI SINGH (Alternate)

Ministry of Steel (Government of India), New Delhi
SHRI BHAGIRATHI PRADHAN (Alternate)

Power Grid Corporation, Gurgaon
SHRI MANOJ KUMAR GUPTA
SHRI DEEPAK KUMAR SAHOO (Alternate)

Organization

Representative(s)

Rashtriya Ispat Nigam Limited, Vishakapatnam

SHRIMATI RUCHIRA GUPTA
SHRI SHANKAR JEE (Alternate)

Research Designs and Standards Organization (RDSO), Lucknow

SHRI MANOJ KUMAR GUPTA
SHRI SALISH ORAON (Alternate)

SAIL, Bhilai Steel Plant, Bhilai

SHRI SHRIRANG KHANKHOJE SHRI K.V. SHANKAR (*Alternate*)

SAIL, Bokaro Steel Plant, Bokaro

SHRIMATI BISWASI SUNITA MINZ

SHRIMATI ROSELIN DODRAE (Alternate)

SAIL, Research & Development Center for Iron & Steel, Ranchi

SHRI P. PATHAK

SAIL, Rourkela Steel Plant, Rourkela

SHRI S. SRIKANTH (Alternate)

Society of Indian Automobile Manufacturers (SIAM), New Delhi SHRI RAMAKRISHNAN P. (Alternate)

Steel Authority of India Limited, IISCO Steel Plant, Barddhaman SHRI KARTIKE KARWAL SHRI KANISHKA CHANA (*Alternate*)

Tata Blue Scope Steel Ltd, Pune

SHRI SAIKAT DE (Alternate)

SHRI A. DASGUPTA

SHRI KUNTAL PATWARI

1

Shri Rajesh Maheshwari

Tata Motors Ltd, Pune

SHRI PRADEEP KULKARNI SHRI LOKESH PALIWAL (Alternate)

Tata Steel Ltd, Jamshedpur

SHRI AVTAR SINGH SAINI

The Tin Plate Company of India Ltd, Jamshedpur

SHRI SUDIPTO SARKAR (Alternate)

SHRI SUBRATA SADHU (Alternate)

In Personal Capacity (New Delhi)

SHRI A. C. R. DAS

SHRI S. J. DEY

BIS Directorate General

SHRI SANJIV MAINI, SCIENTIST 'F'/SENIOR DIRECTOR AND HEAD (METALLURGICAL ENGINEERING) [REPRESENTING DIRECTOR GENERAL (Ex-officio)]

Member Secretary
SHRI ARUN PUCCHAKAYALA
SCIENTIST 'D'/JOINT DIRECTOR
(METALLURGICAL ENGINEERING), BIS

This Pade has been Intentionally left blank

### **Bureau of Indian Standards**

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 2016 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

## Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Head (Publication & Sales), BIS.

#### **Review of Indian Standards**

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the website-www.bis.gov.in or www.standardsbis.in

This Indian Standard has been developed from Doc No.: MTD 04 (21506).

## **Amendments Issued Since Publication**

Amend No.	Date of Issue	Text Affected	

## **BUREAU OF INDIAN STANDARDS**

## **Headquarters:**

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002

Telephones: 2323 0131, 2323 3375, 2323 9402 Website: www.bis.gov.in

Regional Offices:	Telephones
Central : 601/A, Konnectus Tower -1, 6 <sup>th</sup> Floor, DMRC Building, Bhavbhuti Marg, New Delhi 110002	Telephones { 2323 7617
Eastern : 8 <sup>th</sup> Floor, Plot No 7/7 & 7/8, CP Block, Sector V, Salt Lake, Kolkata, West Bengal 700091	2367 0012 2320 9474
Northern: Plot No. 4-A, Sector 27-B, Madhya Marg, Chandigarh 160019	265 9930
Southern: C.I.T. Campus, IV Cross Road, Taramani, Chennai 600113	2254 1442 2254 1216
Western: Plot No. E-9, Road No8, MIDC, Andheri (East), Mumbai 400093	{ 2821 8093

Branches: AHMEDABAD. BENGALURU. BHOPAL. BHUBANESHWAR. CHANDIGARH. CHENNAI. COIMBATORE. DEHRADUN. DELHI. FARIDABAD. GHAZIABAD. GUWAHATI. HIMACHAL PRADESH. HUBLI. HYDERABAD. JAIPUR. JAMMU & KASHMIR. JAMSHEDPUR. KOCHI. KOLKATA. LUCKNOW. MADURAI. MUMBAI. NAGPUR. NOIDA. PANIPAT. PATNA. PUNE. RAIPUR. RAJKOT. SURAT. VISAKHAPATNAM.