भारतीय मानक Indian Standard

सड़क वाहन — संपीड़ित प्राकृतिक गैस (सीएनजी)/जैव-संपीड़ित प्राकृतिक गैस (जैव-सीएनजी) — ईंधन प्रणाली के घटक — सीएनजी/जैव-सीएनजी/एलपीजी नाली (वेंटिलेशन नली/पाइप)

(पहला पुनरीक्षण)

Road Vehicles — Compressed Natural Gas (CNG)/Bio-compressed Natural Gas (Bio-CNG) — Fuel System Components — Automatic Valve (Solenoid Valve)

(First Revision)

ICS 43.060.40

© BIS 2024



भारतीय मानक ब्यूरो BUREAU OF INDIAN STANDARDS मानक भवन, 9 बहादुर शाह ज़फर मार्ग, नई दिल्ली - 110002 MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI - 110002 www.bis.gov.in www.standardsbis.in

November 2024

Price Group 5

Automotive Vehicles Running on Non-Conventional Energy Sources Sectional Committee, TED 26

FOREWORD

This Indian Standard (First Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Automotive Vehicles Running on Non-Conventional Energy Sources Sectional Committee had been approved by the Transport Engineering Division Council.

This standard was first published in 2008 to specify definitions, test methods and requirements of conduit (ventilation hose/pipe), of CNG onboard fuel system components, intended for use on motor vehicles defined in IS 14272. In this revision, bio-CNG is added to the scope of this standard keeping in view the technological advancements that have taken place since its last Publication. The new scope also covers liquefied petroleum gas (LPG) to incorporate the Amendment No. 1 to earlier Standard.

In the formulation of this standard considerable assistance has been derived from the following AIS Standards issued by the Automotive Research Association of India:

AIS 024 (Rev. 1) (Part A) — Safety and procedural requirements for type approval of gaseous fuelled vehicles — Part A (Automotive application)

AIS 024 (Rev. 1) (Part B) — Safety and procedural requirements for type approval of gaseous fuel agricultural Tractors — Part B (Agricultural tractors application)

AIS 024 (Rev. 1) (Part C) — Safety and procedural requirements for type approval of gaseous fuel vehicles— Part C (CEV's application)

AIS 028 (Rev. 1) (Part A) — Code of practice for use of gaseous fuels in internal combustion engine vehicles — Part A (Automotive application)

AIS 028 (Rev. 1) (Part B) — Code of practice for use of gaseous fuels in internal combustion engine agricultural tractors — Part B (Agricultural tractors application)

AIS 028 (Rev. 1) (Part C) — Code of practice for use of gaseous fuels in internal combustion engine construction equipment vehicles (CEV's) — Part C (CEV's application)

AIS-025 (Version 3) — Safety and procedural requirements for type approval of LPG operated vehicles

AIS 026 (Version 3) — Code of practice for use of LPG fuel in internal combustion engine to power 4 wheeled vehicles

AIS 027 (Version 3) — Code of practice for use of LPG fuel in internal combustion engine to power 2 & 3 wheeled vehicles.

This standard is one of the series of Indian Standards published on CNG/Bio-CNG/LPG onboard fuel system components. Other standards in the series are:

IS No.

Title

- 15711: 2024 Road vehicles Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components Performance and general test methods
- 15712:2024 Road vehicles Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components Automatic valve
- 15713 : 2024 Road vehicles Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components Pressure regulator

Indian Standard

ROAD VEHICLES — COMPRESSED NATURAL GAS (CNG)/ BIO-COMPRESSED NATURAL GAS (BIO-CNG)/LIQUEFIED PETROLEUM GAS (LPG) — FUEL SYSTEM COMPONENTS — CNG/BIO-CNG/LPG CONDUIT (VENTILATION HOSE/PIPE)

(First Revision)

1 SCOPE

1.1 This standard specifies definitions, test methods and requirements of conduit (ventilation hose /pipe), of CNG/bio-CNG/LPG onboard fuel system components, intended for use on motor vehicles defined in IS 14272.

1.2 This standard is applicable to CNG/ bio-CNG/LPG fuel system components intended to be used on vehicles using compressed natural gas/bio-compressed natural gas/liquefied petroleum gas in accordance with IS 15320 (Part 1) (mono-fuel or bi-fuel or dual fuel applications as applicable).

1.3 This standard is not applicable to the following:

- a) Liquefied natural gas (LNG) fuel system components located upstream of, and including, the vaporizer;
- b) Fuel containers;
- c) Stationary gas engines; and
- d) CNG/bio-CNG/LPG fuel systems components for the propulsion of marine craft.
- e) Hydrogen natural gas blend (HCNG) fuel system components

1.4 This standard is based upon a service pressure for compressed natural gas/bio-compressed natural gas as a fuel at 20 MPa (200 bar) and liquefied petroleum gas as a fuel at 2 MPa (20 bar) settled at 15 °C.

2 REFERENCES

The standards given below contain provisions which, through reference in this text, constitute provisions of this standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreement based on this standard are encouraged to investigate the possibility of applying the most recent edition of these standards:

IS No.	Title	
IS 14272 : 2011	Automotive vehicles — Types — Terminology (first revision)	
IS 15061 : 2002	Automotive vehicles — Flammability requirements	
IS 15320 (Part 1) : 2012/ISO 15403-1 : 2006	Natural gas — Natural gas for use as a compressed fuel for vehicles: Part 1 Designation of the quality (<i>first revision</i>)	
IS 15710 : 2024	Road vehicles — Compressed natural gas (CNG) fuel system components — General Requirements and definitions	

3 DEFINITIONS

For the purpose of this standard definitions given in IS 15710 shall apply.

3.1 Self-Extinguishing/No Bum Rate (SFJNBR) — The material stops burning before it has burnt for 60 s from the start of timing and has not burnt more than 50.8 mm (2 inch) from the point where the timing was started.

4 TYPE TESTS (TYPE APPROVAL)

The material of the conduit used for ducting shall be sufficiently strong to resist mechanical damage, preserve venting integrity, protect the piping or hose within it, shall not support combustion and shall meet the following minimum criteria.

4.1 Pressure Test

4.1.1 The conduit shall withstand an internal pressure of 30 kPa.

To access Indian Standards click on the link below:

https://www.services.bis.gov.in/php/BIS 2.0/bisconnect/knowyourstandards/Indian standards/isdetails/

IS 15715 : 2024

4.1.2 The conduit shall not suffer sufficient damage to permit leakage when tested by applying a 60 kgf static force applied through 20 mm diameter, in the following manner:

- a) Applied to a free length of conduit (minimum length of 500 mm); and
- b) With the conduit connection clamped up in position, the force then applied 5 mm from the end of this coupling so as to place the connection in tension.

4.2 Flammability Test

When tested for horizontal burning rate as per Annex A of IS 15061, the material shall be self-extinguishing/no burn rate (SE/NBR).

4.3 Resistance to Ultraviolet Degradation

When tested as per <u>Annex A</u> of this standard, presence of stabilizer for ultraviolet degradation shall be confirmed.

5 MARKING

5.1 In case conduit (ventilation hose/pipe) is not permanently marked, then the package of conduit shall have tag/sticker with the following details:

- a) Manufacturer's name, trade-mark or symbol;
- b) Part No. or unique identification mark;
- c) Size; and
- d) Batch number.

5.2 BIS Certification Marking

The product(s) conforming to the requirements of this standard may be certified as per the conformity assessment schemes under the provisions of the *Bureau of Indian Standards Act*, 2016 and the Rules

and Regulations framed thereunder, and the product(s) may be marked with the Standard Mark.

6 TECHNICAL INFORMATION TO BE SUBMITTED BY THE COMPONENT MANUFACTURER

Technical information to be submitted by the component manufacturer for component type approval/type test shall contain at least following information:

- a) Name of the manufacturer;
- b) Manufacturing plant address;
- c) Part number;
- d) Inner diameter (ID);
- e) Outer diameter (OD); and
- f) Drawings with relevant dimensions and materials.

7 NUMBER OF SAMPLES FOR TESTING

Minimum 6 number of 500 mm length conduits (ventilation hose/pipe) along with end plugs and hose/pipe clips shall be submitted to the test agency for testing. One end plug shall have provision to connect pneumatic pipe of 8 mm inner diameter.

8 CHANGES IN TECHNICAL SPECIFICATIONS OF A TYPE APPROVED COMPONENT AND EXTENSION OF APPROVAL

Any modification in technical specification of already type approved component shall require re-type test/extension of approval at the discretion of test agency, based on the justification provided by the component manufacturer and reviewed by the test agency, which has granted type approval.

ANNEX A

(*Clause* <u>4.3</u>)

TEST METHOD TO DETERMINE THE PRESENCE OF ULTRAVIOLET DEGRADATION AGENT (UV STABILIZER)

A-1 SCOPE

This test method is intended to provide a general technique to determine the presence of ultraviolet degradation agent (UV stabilizer) present in the samples. This method is useful in performing a qualitative analysis.

A-2 SUMMARY OF THE TEST PROCEDURE

This test method consists of a method in which the acetone extract of the sample under test is prepared in the form of thin film or capillary film and its spectrum is collected over IR range of 4 000 cm⁻¹ to 400 cm⁻¹. The spectrum is then compared with any internationally available library, such as atlas of hummel polymer library spectra or with the enhanced polymer.

Additives library such as saddler, FDM, nicolet, RAPRA or any other library spectra.

A-3 APPARATUS

Fourier transform infrared spectrometer with wave number range of 7 800 cm⁻¹ to 350 cm⁻¹.

A-4 REAGENT

A-4.1 Acetone

A-5 PROCEDURE

The representative test quantity of sample is extracted with acetone solvent for 16 h. The extract is dried and then subjected to FTIR spectrometer test.

The sample prepared from the above techniques is mounted to a suitable sample holder and kept inside sample compartment of optical bench of IR spectrometer and its infrared spectrum is collected keeping the following instrumental parameters according to the nature of the sample:

- a) The environmental conditions for equipment are maintained. They are as follows:
 - 1) Room temperature: 0 °C to 35 °C; and
 - 2) Relative humidity: 20 percent to 80 percent.
- b) The optical bench is switched on and is allowed to initialize;
- c) The resolution is set to 4.0 cm⁻¹, No. of scans to 40, apodization to Happ-Ganzel and wave number range from 4 000 cm⁻¹ to 400 cm⁻¹;
- d) Background spectrum is collected without the sample in the compartment;
- e) The sample spectrum is collected with the prepared sample in the compartment after collecting background spectrum; and
- f) The sample spectrum collected is baseline corrected and normalized to compare with the standard spectrum from the library using search commands.

A-6 REPORT

The obtained FTIR spectrum is searched in any internationally available library, such as atlas of hummel polymer library spectra or with the enhanced polymer additives library such as saddtler, FDM, nicolet, RAPRA or any other library spectra for best matching spectrum of ultraviolet stabilizer.

ANNEX B

(Foreword)

COMMITTEE COMPOSITION

Automotive Vehicles Running on Non-Conventional Energy Sources Sectional Committee, TED 26

Automotive Research Association of India (ARAI), Pune

Organization

A B Process Technologies, Pune

Ashok Leyland Ltd, Chennai

Automotive Component Manufactures Association of India, New Delhi

Bajaj Auto Ltd, Pune

Bosch Limited, Bengaluru

Central Institute of Road Transport, Pune

Central Pollution Control Board, New Delhi

CLH Gaseous Fuel Applications Ltd, Gurugram

Delhi Transport Corporation, New Delhi

GAIL (India) Limited, New Delhi

Indian Auto LPG Coalition, Faridabad

Indian Institute of Petroleum, Dehradun

Indian Institute of Science, Bengaluru

Indian Institute of Technology Ropar, Rupnagar

Indian Oil Corporation Ltd, (R & D Centre), Faridabad

Indian Rubber Mfrs Research Association, Thane, Mumbai

International Centre for Automotive Technology (ICAT), Manesar

Representative(s)

DR S. S. THIPSE (*Chairperson*) SHRI A. D. DEKATE

SHRI KUNAL CHOPDE

SHRIMATI SUCHISMITA C. SHRI MUTHUKUMAR N. (Alternate)

SHRI SANJAY TANK Shrimati Seema Babal (*Alternate*)

SHRI MILIND J. PAGARE SHRI ARVIND V. KUMBHAR (Alternate)

SHRI BHARADWAJ M. KRISHNAMURTHY SHRI VIKRAM K. (*Alternate*)

SHRI SAMIR SATTIGERI SHRI V. V. JOSHI (Alternate)

SHRI A. SUDHAKAR SHRI SUNEEL DAVE (*Alternate* I) SHRI KEDARNATH DASH (*Alternate* II)

SHRI SHISHIR AGRAWAL SHRI GAGAN AGRAWAL (*Alternate*)

SHRI VIKAS BATRA

SHRI ASHISH KUMAR MITTAL SHRI LOKESH MEHTA (*Alternate*)

SHRI SHISHIR AGRAWAL SHRI SUYASH GUPTA (*Alternate*)

SHRI WITTISON KAMEI SHRI ROBINDRO LAIRENLAKPAM (Alternate)

PROF R. V. RAVIKRISHNA

SHRI DHIRAJ KUMAR MAHAJAN DR DEBAPRASAD MANDAL (Alternate)

DR M. SITHANANTHAN

DR K. RAJ KUMAR DR BHARAT KAPGATE (*Alternate*)

SHRI VAIBHAV PRASHANT YADAV SHRI VIJAYANTA AHUJA (*Alternate*)

Organization

Mahindra & Mahindra Ltd, Mumbai

Mahindra & Mahindra Ltd (Truck and Bus Division), Pune

Maruti Suzuki India Limited, Gurugram

Minda Emer Technologies Limited, Gurugram

Ministry of New and Renewable Energy, New Delhi

Petroleum and Explosive Safety Organization, Nagpur

Petronet LNG Ltd, New Delhi

Prodair Air Products India Private Ltd, Pune

Renault India Private Limited, Mumbai

Rohan BRC Gas Equipment Pvt Ltd, Ahmedabad

Society of Indian Automobile Manufacturers, New Delhi

Swagelok – Bombay Fluid System components Pvt Ltd, Mumbai

Tata Motors Ltd, Pune

TVS Motor Company Ltd, Hosur

Vanaz Engineers Ltd, Pune

Volkswagen India Pvt Ltd, Mumbai

BIS Directorate General

Representative(s)

SHRI RAJAMANI PARTHIBAN Shri Shailesh Kulkarni (Alternate)

SHRI V. G. KULKARNI

SHRI GURURAJ RAVI SHRI ARUN KUMAR (Alternate)

SHRI VIVEK JAIN SHRI BIBHUTI KUMAR (*Alternate*)

SHRI DIPESH PHERWANI

SHRI D. K. GUPTA SHRI VIVEK KUMAR (*Alternate*)

SHRI PANKAJ WADHWA (Alternate)

SHRI RAVI SUBRAMANIAN SHRI ARUN KURUVANGATTIL (Alternate)

SHRI RAJENDRA KHILE SHRI VIJAY DINAKARAN (*Alternate*)

SHRI STEFANO DE CAROLIS SHRI PARTHIV SHUKLA (*Alternate*)

SHRI P K BANERJEE DR SANDEEP GARG (Alternate)

SHRI SACHIN KOULGI SHRI HARISH TAKKE (*Alternate*)

SHRI P. S. GOWRISHANKAR SHRI SHAILENDRA DEWANGAN (Alternate)

SHRI V. PATTABIRAMAN SHRI K. M. SRIKANTH (*Alternate*)

SHRI S. J. VISPUTE SHRI J. S. DHUMAL (*Alternate*)

SHRI JOREG BOUZEK SHRI PANKAJ GUPTA (*Alternate*)

SHRI DEEPAK AGARWAL, SCIENTIST 'F'/ SENIOR DIRECTOR AND HEAD (TRANSPORT ENGINEERING) [REPRESENTING DIRECTOR GENERAL (*Ex-officio*)]

Member Secretary Shri Gaurav Jayaswal Scientist 'C'/Deputy Director (Transport Engineering), BIS this Page has been intertionally left blank

IS No.

Title

- 15714 : 2024 Road vehicles Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components Gas air mixer
- 15715: 2024 Road vehicles Compressed natural gas (CNG) /bio-compressed natural gas (bio-CNG)/ liquefied petroleum gas (LPG) Fuel system components — CNG/bio-CNG/LPG conduit (ventilation hose/pipe)
- 15716: 2024 Road vehicles Compressed natural gas (CNG) /bio-compressed natural gas (bio-CNG) fuel system components CNG/bio-CNG high pressure fuel line (rigid) with end connections (having pressure exceeding 2.15 MPa)
- 15717: 2024 Road vehicles Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG)/ liquefied petroleum gas (LPG) Fuel system components — Petrol valve (automatic/manual)
- 15718: 2024 Road vehicles Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components CNG/bio-CNG high Pressure fuel line (flexible hose) with end connections (having pressure exceeding 2.15 MPa)
- 15719: 2024 Road vehicles Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG)/ liquefied petroleum gas (LPG) fuel system components Electrical Wiring kit
- 15720: 2024 Road vehicles Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG)/ liquefied petroleum gas (LPG) fuel system component — Compartments sub-compartments
- 15721: 2024 Road vehicles Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG)/ liquefied petroleum gas (LPG) fuel system components — Fire retardant material for seat, upholstery, roof and side lining
- 15722: 2024 Road vehicles Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components CNG/bio-CNG flexible fuel line with or without end connections (having pressure not exceeding 2.15 MPa)
- 15723: 2024 Road vehicles Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG)/ liquefied petroleum gas (LPG) fuel system components — Current Limiting devices

The composition of the Committee responsible for the formulation of this standard is given in Annex B.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 2022 'Rules for rounding off numerical values (*second revision*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 2016 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

Headquarters:

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Head (Publication & Sales), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the website-www.bis.gov.in or www.standardsbis.in.

This Indian Standard has been developed from Doc No.: TED 26 (15013).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Manak Bhavan, 9 Bahadur Shah Zafar <i>Telephones</i> : 2323 0131, 2323 3375, 23	0	Website: www.bis.gov.in	
Regional Offices:			Telephones
Central : 601/A, Konnectus Tower DMRC Building, Bhavbhu Delhi 110002			2323 7617
Eastern : 8 th Floor, Plot No 7/7 & 7/ Salt Lake, Kolkata, West I			<pre>{ 2367 0012 2320 9474 { 265 9930</pre>
Northern : Plot No. 4-A, Sector 27-B, Chandigarh 160019	Madhya Marg,		265 9930
Southern : C.I.T. Campus, IV Cross F	Road, Taramani, Chennai 600113		<pre>{ 2254 1442 2254 1216</pre>
Western: 5 th Floor/MTNL CETTM, 7 Mumbai 400076	Fechnology Street, Hiranandani (Gardens, Powai	{ 25700030 25702715

Branches : AHMEDABAD, BENGALURU, BHOPAL, BHUBANESHWAR, CHANDIGARH, CHENNAI, COIMBATORE, DEHRADUN, DELHI, FARIDABAD, GHAZIABAD, GUWAHATI, HARYANA (CHANDIGARH), HUBLI, HYDERABAD, JAIPUR, JAMMU, JAMSHEDPUR, KOCHI, KOLKATA, LUCKNOW, MADURAI, MUMBAI, NAGPUR, NOIDA, PARWANOO, PATNA, PUNE, RAIPUR, RAJKOT, SURAT, VIJAYAWADA.