

---

---

पोत एवं समुद्री प्रौद्योगिकी — पोत विशेष  
पर रहने की सम्भावना के बारे में कंपन के  
मापन, मुल्यांकन एवं रिपोर्टिंग के  
दिशानिर्देश

**Ships and Marine Technology –  
Guidelines for Measurement,  
Evaluation and Reporting of  
Vibration with Regard to Habitability  
on Specific Ships**

ICS 17.160; 47.020.01

© BIS 2024  
© ISO 2018



भारतीय मानक ब्यूरो  
BUREAU OF INDIAN STANDARDS  
मानक भवन, 9 बहादुर शाह ज़फर मार्ग, नई दिल्ली - 110002  
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG  
NEW DELHI - 110002

[www.bis.gov.in](http://www.bis.gov.in) [www.standardsbis.in](http://www.standardsbis.in)

## NATIONAL FOREWORD

This Indian Standard which is identical to ISO 21984 : 2018 'Ships and marine technology — Guidelines for measurement, evaluation and reporting of vibration with regard to habitability on specific ships' issued by International Organization for Standardization (ISO), was adopted by the Bureau of Indian Standards on the recommendations of the Shipbuilding Sectional Committee and approval of the Transport Engineering Division Council.

The text of ISO standard may be proposed for publication as an Indian Standard without deviations. Certain conventions are, however, not identical to those used in Indian Standards. Attention is particularly drawn to the following:

- a) Wherever the words 'International Standard' appear referring to this standard, they should be read as 'Indian Standard'; and
- b) Comma (,) has been used as a decimal marker while in Indian Standards, the current practice is to use a point (.) as the decimal marker.

In this adopted standard, reference appears to certain International Standards for which Indian Standards also exist. The corresponding Indian Standards, which are to be substituted in their respective places, are listed below along with their degree of equivalence for the edition indicated:

<i>International Standard</i>	<i>Corresponding Indian Standard</i>	<i>Degree of Equivalence</i>
ISO 2041 Mechanical vibration, shock and condition monitoring — Vocabulary	IS/ISO 2041 : 2018 Mechanical vibration, shock and condition monitoring — Vocabulary ( <i>first revision</i> )	Identical
ISO 2631-1 Mechanical vibration and shock — Evaluation of human exposure to whole-body vibration — Part 1: General requirements	IS 13276 (Part 1) : 2000/ ISO 2631-1 : 1997 Mechanical vibration and shock — Evaluation of human exposure to whole body vibration: Part 1 General requirements ( <i>first revision</i> )	Identical
ISO 2631-2 Mechanical vibration and shock — Evaluation of human exposure to whole-body vibration — Part 2: Vibration in buildings (1 Hz to 80 Hz)	IS/ISO 2631-2 : 2003 Mechanical vibration and shock — Evaluation of human exposure to whole body vibration: Part 2 Vibration in buildings (1 Hz to 80 Hz)	Identical
ISO 8041 Human response to vibration — Measuring instrumentation	IS/ISO 8041-1 : 2017 Human response to vibration measuring instrumentation: Part 1 General purpose vibration meters ( <i>first revision</i> )	Identical

Attention is drawn to the possibility that some of the elements of this standard may be the subject of patent rights. The Bureau of Indian Standards shall not be held responsible for identifying any or all such patent rights.

Annex A, B & C are for informative only.

In reporting the result of a test or analysis made in accordance with this standard, if the final value, observed or calculated, is to be rounded off it shall be done in accordance with IS 2 : 2022 'Rules for rounding off numerical values (*second revision*)'.

# Contents

Page

<b>Introduction</b> .....	<b>iv</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>2</b>
<b>4 Instrumentation</b> .....	<b>2</b>
4.1 General requirements.....	2
4.2 Functional test.....	3
<b>5 Measurement locations and directions</b> .....	<b>3</b>
5.1 Measurement locations.....	3
5.2 Measurement directions.....	3
<b>6 Measurement conditions</b> .....	<b>3</b>
<b>7 Measurement procedure</b> .....	<b>4</b>
<b>8 Evaluation</b> .....	<b>4</b>
8.1 Guidance values of acceptable vibration.....	4
8.2 Beating.....	5
<b>9 Test report</b> .....	<b>5</b>
<b>Annex A (informative) Example of length of a deck house (L) and its height (H) for slenderness ratio</b> .....	<b>6</b>
<b>Annex B (informative) Frequency weighting, <math>W_m</math></b> .....	<b>7</b>
<b>Annex C (informative) Example of report for evaluation of habitability on board ships in accordance with this document</b> .....	<b>9</b>
<b>Bibliography</b> .....	<b>10</b>

## **Introduction**

Shipboard vibration that interferes with duties or reduces comfort is objectionable and often results in adverse comments from crew and passengers. To quantify this vibration, this document gives guidelines for the measurement, evaluation and reporting of habitability for all persons on board specific ships including crew.

Vibration data acquired in accordance with this document are also useful for

- comparison with ship specifications,
- comparison with other ships, and
- further development and improvement of vibration regulations.

*Indian Standard*

# SHIPS AND MARINE TECHNOLOGY – GUIDELINES FOR MEASUREMENT, EVALUATION AND REPORTING OF VIBRATION WITH REGARD TO HABITABILITY ON SPECIFIC SHIPS

## 1 Scope

This document gives guidelines for the measurement, evaluation and reporting of vibration with regard to habitability for all persons on board ships satisfying one or both of the following conditions:

- a) 2-stroke cycle, long-stroke, low-speed diesel engine directly coupled to the fixed-pitch propulsion propeller is installed.
- b) length of deck house (L) is limited as compared with its height (H) (i.e. deck house of around 1,0 and above in slenderness ratio of H to L). An example of length of deck house (L) and its height (H) for slenderness ratio is shown in [Annex A](#).

Overall frequency-weighted r.m.s. vibration values in the frequency range 1 Hz to 80 Hz are given as guidance values for different spaces on ships.

This document is applicable to specific ships with intended voyages of 24 h or more.

This document specifies requirements for the instrumentation and the procedure of measurement in normally occupied spaces. It also contains analysis specifications and guidelines for the evaluation of ship vibration with respect to habitability.

This document is not applicable to machinery spaces, other than engine control rooms, where persons do not stay for prolonged periods of time.

ISO 20283-5 is generally applicable to all ships. Requirements for measurement, evaluation and reporting of vibration with regard to habitability for all persons on board passenger and merchant ships, including specific ships to which this document may also be applicable can be found in ISO 20283-5. This document is neither complementary nor additional but supplementary to ISO 20283-5. The shipbuilder can select either this document or ISO 20283-5 to apply to any specific ship upon due consideration to individual design conditions of the ship and, if any, experience in building sister or similar ships, and that particular selection is intended to be agreed on by the shipowner.

The evaluation of low-frequency ship motion which can result in motion sickness is covered by ISO 2631-1. For the evaluation of the global structural vibration of a ship, however, see ISO 20283-2.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2041, *Mechanical vibration, shock and condition monitoring — Vocabulary*

ISO 2631-1, *Mechanical vibration and shock — Evaluation of human exposure to whole-body vibration — Part 1: General requirements*

ISO 2631-2, *Mechanical vibration and shock — Evaluation of human exposure to whole-body vibration — Part 2: Vibration in buildings (1 Hz to 80 Hz)*

ISO 8041, *Human response to vibration — Measuring instrumentation*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 2041 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

#### 3.1 accommodation space

space intended for recreational and administration use, namely cabins including day and sleeping rooms, hospitals, mess rooms, recreation rooms

Note 1 to entry: Examples of recreation rooms are lounges, smoke rooms, cinemas, gymnasiums, libraries, hobby rooms and game rooms.

#### 3.2 office

space or room for carrying out a ship's business

EXAMPLE Deck office, ship office, meeting rooms.

#### 3.3 work space

space allocated predominantly for manual work, namely workshops, laundries, galleys and laboratories, but not *machinery space* (3.4)

#### 3.4 machinery space

space which contains steam or internal-combustion machinery, pumps, air compressors, boilers, oil fuel units, major electrical machinery, oil filling stations, thrusters, refrigerating, stabilizing, steering gear, ventilation and air conditioning machinery, etc., and trunks to such spaces

#### 3.5 duty station

*work space* (3.3) where crew members typically stay over prolonged periods of time (typically for a watch of 4 h) to monitor navigation or machinery

Note 1 to entry: Main duty stations are the engine control room and the wheel house excluding bridge wing areas.

#### 3.6 open-deck recreation space

designated space on the open deck to be used for the purpose of recreation

#### 3.7 free route

condition achieved when the ship is proceeding at a constant speed and course with helm adjustment of  $\pm 2^\circ$  or less and no throttle adjustment

### 4 Instrumentation

#### 4.1 General requirements

Measurements in accordance with this document may be carried out using different types of measuring and recording equipment, e.g. instruments of digital, spectral or time-based type. The measuring instrumentation shall meet the relevant requirements of ISO 8041.

It is acceptable to use instruments manufactured in accordance with ISO 8041 that have frequency indications above 80 Hz provided that the filter characteristics comply with ISO 2631-2 (for frequency

weighting,  $W_m$ , see [Annex B](#)). The compliance of the instruments with the specifications of ISO 8041 requires a calibration of at least every two years. The date of the last calibration shall be reported.

If further data analysis is required following the measurement analysis as described in this document, the measurement data should be recorded with an electronic system which produces permanent records.

## 4.2 Functional test

Each channel of the instruments shall be checked on board the ship prior to and after each measurement series to ensure proper functioning. The check may be made by comparing the vibration value measured at any location by the instruments with that measured at the same location by other instruments, or with that provided by a portable exciter.

## 5 Measurement locations and directions

### 5.1 Measurement locations

Measurement locations shall be selected on all decks of normally occupied spaces in sufficient quantity in order to characterize satisfactorily the vibration behaviour of the ship with respect to habitability.

In work spaces, measurement transducers shall be especially placed at main duty stations of the crew. In accommodation spaces, transducer shall be positioned in the centre of spaces or where a person stays for prolonged periods of time. In general, measurements should be made at least 1 m from a steel wall as far as practical.

Vibration transducers shall be located and attached properly to the floor surface such that the vibration at the interface between the person and the source of vibration is adequately captured. If the floor is covered with a non-rigid or resilient material, the transducer shall be suitably mounted such that the pressure distribution on the surface of the floor covering is not altered. A transducer mounted on an appropriate three-spike plate may be used. The details about the transducer installation on rigid and soft material shall be clearly stated in the measurement report.

### 5.2 Measurement directions

The transducer directions shall correspond to the three translational axes of the ship: longitudinal, transverse and vertical.

## 6 Measurement conditions

Measurement data shall be obtained, in the first instance, during the acceptance or performance trial of the ship. The collection of consistent and accurate vibration data requires the following uniform and favourable measurement conditions:

- a) free-route test on a straight course;
- b) constant propulsion power according to contractual normal seagoing condition;
- c) propulsion rotational speed is set constant during measurements;
- d) full immersion of the propeller;
- e) all systems to be in normal operation mode [heating, ventilation and air conditioning (HVAC), auxiliary engines, stabilizers, etc.]; and
- f) for acceptable water depth needing no shallow water correction, Beaufort scale for wind and significant wave height, refer to ISO 15016.

Any deviation from the above measurement conditions shall be mutually agreed between the interested parties and shall be stated in the test report.

## 7 Measurement procedure

On each deck, measurements are required in all three directions (see 5.2), i.e. covering the in-plane vibration in horizontal directions (transverse and longitudinal) in addition to out-of-plane vibration in vertical direction, at least at two meaningful locations. The results should be evaluated separately. At other locations on the same deck, measurements are required in at least vertical direction.

The frequency weighting,  $W_m$ , in accordance with ISO 2631-2 shall be applied to all measurements irrespective of their direction.

NOTE One-third-octave band values of the frequency weighting,  $W_m$ , and a graphical presentation are given in Annex B. The frequency weighting,  $W_m$ , for narrow-band analysis is given in ISO 8041.

The frequency range to be evaluated is 1 Hz to 80 Hz. The measurement duration shall be at least 1 min. If significant frequency components below 2 Hz are obvious or suspected, measurement duration of at least 2 min is recommended.

The result of each measurement shall be the overall frequency-weighted r.m.s. value as defined in ISO 2631-1. The highest value in any direction shall be used for the evaluation of habitability.

## 8 Evaluation

### 8.1 Guidance values of acceptable vibration

Vibration guidance values are given in Table 1 in terms of the overall frequency-weighted r.m.s. velocity (mm/s) and acceleration (mm/s<sup>2</sup>) in the frequency range 1 Hz to 80 Hz.

NOTE Overall frequency-weighted r.m.s. velocity,  $v_w$ , and acceleration,  $a_w$ , are related to each other through:

$$a_w = \frac{1}{0,028} v_w \quad (1)$$

The guidance values stated in Table 1 are to be regarded as maximum values.

**Table 1 — Guidance values of acceptable vibration**

Type of occupied space	Guidance value
Accommodation space	5,0 mm/s
	179 mm/s <sup>2</sup>
Open-deck recreation space	4,5 mm/s
	161 mm/s <sup>2</sup>
Office	4,5 mm/s
	161 mm/s <sup>2</sup>
Engine control room	5,0 mm/s
	179 mm/s <sup>2</sup>
Wheel house excluding bridge wings	6,0 mm/s
	214 mm/s <sup>2</sup>
Other work spaces	6,0 mm/s
	214 mm/s <sup>2</sup>



## 8.2 Beating

Beating is an interference between two sinusoidal vibrations of slightly different frequencies. It is perceived as periodic variation in vibration magnitude with a frequency that is the difference between the two vibration frequencies. Beating can readily be recognized. If beating is recognized, occurrence should be reported together with at least one noticeable location.

## 9 Test report

The test report shall, at least, contain the following information and data:


- a) a reference to this document, i.e. ISO 21984;
- b) place and date of the test;
- c) identification of persons and organizations performing the test;
- d) principal ship characteristics;
- e) actual conditions of ship and environment experienced during the test, including, e.g. beating;
- f) locations and orientations of the transducers;
- g) recording equipment, date of last calibration and statement of functional testing; and
- h) results of the measurements.

An example of a test report is shown in [Annex C](#).

## Annex A (informative)

### Example of length of a deck house (L) and its height (H) for slenderness ratio

Typical shapes of a deck house of specific ships are sketched in [Figure A.1](#). Equivalent length (L) of a deck house shall be measured based on [Figure A.1](#) considering the effectiveness of bending and shear stiffness as a cantilever. Height (H) of a deck house above the upper deck shall be measured at the centre line of the hull section.



**Key**

- T.BHD    transverse bulkhead
- P.BHD    partial bulkhead or transverse frame
- Bkt.     bracket to connect engine casing and deck house

**Figure A.1 — Typical shapes of a deck house of specific ships**

## Annex B (informative)

### Frequency weighting, $W_m$

The frequency weighting used,  $W_m$ , is defined in ISO 2631-2. It is given in [Table B.1](#) and shown schematically in [Figure B.1](#) for information.

**Table B.1 — Frequency weighting,  $W_m$ , defined from 1 Hz to 80 Hz, in one-third-octave bands (calculated using the true mid-frequencies, band limitation included)**


Frequency band number <sup>a</sup> $x$	Frequency Hz		Acceleration as input quantity		Velocity as input quantity	
	Nominal	True	Factor $W_a$	dB	Factor $W_v$	dB
-7	0,2	0,199 5	0,062 9	-24,02	0,002 21	-53,12
-6	0,25	0,251 2	0,099 4	-20,05	0,004 39	-47,14
-5	0,315	0,316 2	0,156	-16,12	0,008 70	-41,21
-4	0,4	0,398 1	0,243	-12,29	0,017 0	-35,38
-3	0,5	0,501 2	0,368	-8,67	0,032 5	-29,77
-2	0,63	0,631 0	0,530	-5,51	0,058 9	-24,60
-1	0,8	0,794 3	0,700	-3,09	0,097 9	-20,19
0	1	1,000	0,833	-1,59	0,147	-16,68
1	1,25	1,259	0,907	-0,85	0,201	-13,94
2	1,6	1,585	0,934	-0,59	0,260	-11,68
3	2	1,995	0,932	-0,61	0,327	-9,71
4	2,5	2,512	0,910	-0,82	0,402	-7,91
5	3,15	3,162	0,872	-1,19	0,485	-6,28
6	4	3,981	0,818	-1,74	0,573	-4,83
7	5	5,012	0,750	-2,50	0,661	-3,59
8	6,3	6,310	0,669	-3,49	0,743	-2,58
9	8	7,943	0,582	-4,70	0,813	-1,80
10	10	10,00	0,494	-6,12	0,869	-1,22
11	12,5	12,59	0,411	-7,71	0,911	-0,81
12	16	15,85	0,337	-9,44	0,941	-0,53
13	20	19,95	0,274	-11,25	0,961	-0,35
14	25	25,12	0,220	-13,14	0,973	-0,23
15	31,5	31,62	0,176	-15,09	0,979	-0,18
16	40	39,81	0,140	-17,10	0,978	-0,20
17	50	50,12	0,109	-19,23	0,964	-0,32
18	63	63,10	0,0834	-21,58	0,925	-0,67
19	80	79,43	0,060 4	-24,38	0,844	-1,48
20	100	100,0	0,040 1	-27,93	0,706	-3,02
21	125	125,9	0,024 1	-32,37	0,533	-5,46
22	160	158,5	0,013 3	-37,55	0,370	-8,64

<sup>a</sup> Index  $x$  is the frequency band number according to IEC 61260-1.

Table B.1 (continued)

Frequency band number <sup>a</sup> <i>x</i>	Frequency Hz		Acceleration as input quantity		Velocity as input quantity	
	Nominal	True	Factor $W_a$	dB	Factor $W_v$	dB
23	200	199,5	0,006 94	-43,18	0,244	-12,27
24	250	251,5	0,003 54	-49,02	0,156	-16,11
25	315	316,2	0,001 79	-54,95	0,099 5	-20,04
26	400	398,1	0,000 899	-60,92	0,063 0	-24,02

<sup>a</sup> Index *x* is the frequency band number according to IEC 61260-1.



**Key**

- 1 based on acceleration as input quantity
- 2 based on velocity as input quantity
- X frequency, Hz
- Y frequency weighting, dB

Figure B.1 — Frequency weighting curve,  $W_m$ , band limitation included (schematic)

The frequency weighting based on acceleration as input quantity,  $W_a$ , and the frequency weighting based on velocity as input quantity,  $W_v$ , are related one to each other as shown in [Formula \(B.1\)](#):

$$W_a(f) = \frac{1}{0,028} \frac{1}{2\pi f} W_v(f) \tag{B.1}$$

where  $f$  is the frequency.

## Annex C (informative)

### Example of report for evaluation of habitability on board ships in accordance with this document

Place of test:		Date:
Name of organization responsible for the test:		
Name of person performing the test:		
Name of ship:	Yard (shipbuilder) and yard number:	
Type of ship:	Date built:	

Hull particulars		Main engine particulars	
Length between perpendiculars, m:		Type:	Number of cylinders:
Breadth moulded, m:	Draught, m:	Number:	Power, kW:
Remarks:		Speed, r/min:	

Propulsion particulars		Measurement conditions	
Number and type:	Number of blades:	Sea state:	Beaufort scale for wind:
		Significant wave height, m:	Wind speed, m/s:
		Depth of water, m:	Wind direction:
Speed, r/min:		Draught forward, m:	Draught aft, m:
Remarks:		Remarks:	

Type and characteristics of measuring instrumentation
Measuring equipment particulars:
Functional test:

Measurement results			
Transducer location	Direction	Overall frequency-weighted r.m.s. values	
		Accelera- tion mm/s <sup>2</sup>	Velocity mm/s
1.			
2.			
3.			
....			

## Bibliography

- [1] ISO 15016, *Ships and marine technology — Guidelines for the assessment of speed and power performance by analysis of speed trial data*
- [2] ISO 20283-2, *Mechanical vibration — Measurement of vibration on ships — Part 2: Measurement of structural vibration*
- [3] ISO 20283-5, *Mechanical vibration — Measurement of vibration on ships — Part 5: Guidelines for measurement, evaluation and reporting of vibration with regard to habitability on passenger and merchant ships*
- [3] IEC 61260-1, *Electroacoustics — Octave-band and fractional-octave-band filters — Part 1: Specifications*



## Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 2016* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

### Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Head (Publication & Sales), BIS.

### Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the website-[www.bis.gov.in](http://www.bis.gov.in) or [www.standardsbis.in](http://www.standardsbis.in).

This Indian Standard has been developed from Doc No.: TED 17 (24281).

### Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

## BUREAU OF INDIAN STANDARDS

### Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002

Telephones: 2323 0131, 2323 3375, 2323 9402

Website: [www.bis.gov.in](http://www.bis.gov.in)

### Regional Offices:

	Telephones
Central : 601/A, Konnectus Tower -1, 6 <sup>th</sup> Floor, DMRC Building, Bhavbhuti Marg, New Delhi 110002	{ 2323 7617
Eastern : 8 <sup>th</sup> Floor, Plot No 7/7 & 7/8, CP Block, Sector V, Salt Lake, Kolkata, West Bengal 700091	{ 2367 0012 2320 9474
Northern : Plot No. 4-A, Sector 27-B, Madhya Marg, Chandigarh 160019	{ 265 9930
Southern : C.I.T. Campus, IV Cross Road, Taramani, Chennai 600113	{ 2254 1442 2254 1216
Western : 5 <sup>th</sup> Floor/MTNL CETTM, Technology Street, Hiranandani Gardens, Powai Mumbai 400076	{ 25700030 25702715

**Branches :** AHMEDABAD, BENGALURU, BHOPAL, BHUBANESHWAR, CHANDIGARH, CHENNAI, COIMBATORE, DEHRADUN, DELHI, FARIDABAD, GHAZIABAD, GUWAHATI, HARYANA (CHANDIGARH), HUBLI, HYDERABAD, JAIPUR, JAMMU, JAMSHEDPUR, KOCHI, KOLKATA, LUCKNOW, MADURAI, MUMBAI, NAGPUR, NOIDA, PARWANOO, PATNA, PUNE, RAIPUR, RAJKOT, SURAT, VIJAYAWADA.