

भारतीय मानक

Indian Standards

IS/IEC TR 63463:2024

एचवीडीसी कनवर्टर स्टेशनों के लिए जीवन
विस्तार दिशानिर्देश

Life extension guidelines for HVDC
converter stations

ICS 29.020; 29.240.10

© BIS 2024

© IEC 2024



भारतीय मानक ब्यूरो

BUREAU OF INDIAN STANDARDS

मानक भवन, 9 बहादुर शाह जफर मार्ग, नई दिल्ली — 110002

MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG

NEW DELHI — 110002

www.bis.gov.in

www.standardsbis.in

August 2024

Price Group

NATIONAL FOREWORD

This Indian Standard which is identical with IEC TR 63463:2024 'Life extension guidelines for HVDC converter stations' Issued by the International Electrotechnical Commission (IEC) was adopted by the Bureau of Indian Standards on the recommendation of the HVDC Power Systems Sectional Committee and approval of the Electrotechnical Division Council.

This IEC standard was developed in WG 12 of IEC TC 115 which was convened by national mirror committee of India ETD 40 chairperson. This standard was an Indian new work item proposal (NWIP) at IEC level.

The text of the IEC Standard has been approved as suitable for publication as an Indian Standard without deviations. Certain conventions are, however, not identical to those used in Indian Standards. Attention is particularly drawn to the following:

- a) Wherever the words 'International Standard' appears referring to this standard, they should be read as 'Indian Standard'.
- b) Comma (,) has been used as a decimal marker, while in Indian Standards the current practice is to use a point (.) as the decimal marker.

Only English language text has been retained while adopting it in this Indian Standard, and as such the page numbers given here are not the same as in the International Standard.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated expressing the result of a test, shall be rounded off in accordance with IS 2: 2022 'Rules for rounding off numerical values (*second revision*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.