भारतीय मानक

IS XXXX : 2024 ISO 22605 : 2020

Indian Standard

## रीफ्रैक्टरीज— इम्पल्स एक्ससिटेशन ऑफ़ वाइब्रेशन के द्वारा उत्थित ताप में डायनामिक यंग स मॉडुलुस (म ओ इ) निर्धारित करना

## Refractories — Determination of dynamic Young's modulus (MOE) at elevated temperatures by impulse excitation of vibration

ICS 81.080

© BIS 2024 © ISO 2005

भारतीय मानक ब्यूरो BUREAU OF INDIAN STANDARDS मानक भवन, 9बहादुर शाह ज़फर मार्ग, नई दिल्ली110002 -MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG, NEW DELHI - 110002 www.bis.gov.in www.standardsbis.in

xxxxxx 2024

**Price Group X** 

## Refractories Sectional Committee, MTD 15

## NATIONAL FOREWORD

This Indian Standard which is identical to ISO 22605:2020 "Refractories — Determination of dynamic Young's modulus (MOE) at elevated temperatures by impulse excitation of vibration" issued by the International Organization for Standardization (ISO), was adopted by the Bureau of Indian Standards on the recommendation of the Refractories Sectional Committee and approval of the Metallurgical Engineering Division Council.

The text of ISO standard has been approved as suitable for publication as in Indian Standard without deviations. Certain terminologies and conventions are, however, not identical with those used in Indian Standard. Attention is especially drawn to the following:

- a) Wherever the words `International Standard' appear referring to this standard, it should be read as `Indian Standard'.
- b) Comma (,) has been used as a decimal marker while in Indian Standards the current practice is to use a point (.) as the decimal marker.

In this adopted standard, reference appears to certain International Standards for which Indian Standards also exists. The corresponding Indian Standards which are to be substituted in their place are listed below along with their degree of equivalence for the edition indicated:

International Standard	Corresponding Indian Standard	Degree of Equivalence
ISO 5022 Shaped refractory products — Sampling and acceptance testing.	IS 1528 (Part 7) : 2010 Methods of sampling and physical tests for refractory materials: Part 7 methods of sampling and criteria for conformity ( <i>Second Revision</i> ).	Not Equivalent
ISO 8656-1 Refractory products — Sampling of raw materials and unshaped products — Part 1: Sampling scheme.	IS 1528 (Part 7) : 2010 Methods of sampling and physical tests for refractory materials: Part 7 methods of sampling and criteria for conformity ( <i>Second Revision</i> ).	Not Equivalent
ISO 12680-1 Methods of test for refractory products — Part 1: Determination of dynamic Young's modulus (MOE) by impulse excitation of vibration	MTD 15 (23810) Methods of test for refractory products: Part 1 Determination of dynamic Young's modulus (MOE) by impulse excitation of vibration.	Identical
ISO 16835 Refractory products — Determination of thermal expansion	IS 1528 (Part 19) : 2020 / ISO 16835 : 2014 Methods of Sampling and Physical Tests for Refractory Materials: Part 19 Determination of Thermal Expansion ( <i>First Revision</i> )	Identical

IEC 60584-1 Thermocouples —	IS 16923 (Part 1) : 2018 / IEC 60584-1 :	Identical
Part 1: EMF specifications and	2013 Thermocouples Part 1 EMF	
tolerances	Specifications and Tolerances (First	
	Revision)	
IEC 60584-2 Thermocouples <sup>1)</sup>	IS 16923 (Part 1): 2018 / IEC 60584-1:	Identical
— Part 2: Tolerances	2013 Thermocouples Part 1 EMF	
	Specifications and Tolerances (First	
	Revision)	

The International Standard IEC 60584-2 : 1982 "Thermocouples — Part 2: Tolerances" has been replaced by IEC 60584-1: 2013 "Thermocouples — Part 1: EMF specifications and tolerances" which is adopted as a Indian Standard IS 16923 (Part 1) : 2018 "Thermocouples Part 1 EMF Specifications and Tolerances (*First Revision*)" under dual numbering system.

In reporting the result of a test or analysis made in accordance with this standard, is to be rounded off, it shall be done in accordance with IS 2: 2022 'Rules for rounding off numerical- values (*second revision*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.