

कृषि एवं वानिकी के लिए ट्रैक्टर — ध्वनि
मापन — परीक्षण पद्धति
भाग 1 प्रचालक स्तर पर ध्वनि — सर्वेक्षण विधि
(दूसरा पुनरीक्षण)

Tractors for Agriculture and
Forestry — Noise Measurement —
Method of Test

Part 1 Noise at the Operator's Position —
Survey Method

(Second Revision)

ICS 17.140.20; 65.060.01

© BIS 2024

© ISO 2015



भारतीय मानक ब्यूरो
BUREAU OF INDIAN STANDARDS
मानक भवन, 9 बहादुर शाह ज़फर मार्ग, नई दिल्ली - 110002
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI - 110002

www.bis.gov.in www.standardsbis.in

NATIONAL FOREWORD

This Indian Standard (Part 1) (Second Revision) which is identical to ISO 5131 : 2015 'Tractors for agriculture and forestry — Measurement of noise at the operator's position — Survey method' issued by the International Organization for Standardization (ISO) was adopted by the Bureau of Indian Standards on the recommendation of the Agricultural Machinery and Equipment Sectional Committee and approval of the Food and Agriculture Division Council.

The Indian Standard (IS 12180) was originally published in 1987 with the title 'Method for noise measurement of agricultural tractors' and was based on ISO 5131 : 1982 and ISO/DIS 7216. In the first revision in 2000, the standard was split into two parts with the general title 'Tractors and machinery for agriculture and forestry — Noise measurement — Method of test'. Part 1 was an identical adoption of ISO 5131 : 1996 covering method for the measurement of noise at the position of the operator(s) of a tractor or machine used in agriculture and forestry and Part 2 was an identical adoption of ISO 7216 : 1992 covering method for the measurement of noise emitted by wheeled tractors or self-propelled machine used in agriculture and forestry while in motion.

The second revision of the standard (Part 1) has been undertaken to align with the latest version of ISO 5131 published in 2015.

The text of ISO standard has been approved as suitable for publication as an Indian Standard without deviations. Certain conventions are, however, not identical to those used in Indian Standards. Attention is particularly drawn to the following:

- a) Wherever the words 'International Standard' appear referring to this standard, they should be read as 'Indian Standard'; and
- b) Comma (,) has been used as a decimal marker while in Indian Standards, the current practice is to use a point (.) as the decimal marker.

In this adopted standard, reference appears to the following International Standards for which Indian Standards also exist. The corresponding Indian Standards, which is to be substituted in their respective place, is listed below along with its degree of equivalence for the edition indicated:

<i>International Standard</i>	<i>Corresponding Indian Standard</i>	<i>Degree of Equivalence</i>
ISO 5353 Earth-moving machinery, and tractors and machinery for agriculture and forestry — Seat index point	IS 11113 : 1999/ISO 5353 : 1995 Earth-moving machinery, and tractors and machinery for agriculture and forestry — Seat index point (<i>second revision</i>)	Identical
ISO 6395 Earth-moving machinery — Determination of sound power level — Dynamic test conditions	IS/ISO 6395 : 2008 Earth-moving machinery — Determination of sound power level — Dynamic test conditions	Identical
IEC 60942 Electroacoustics — Sound calibrators	IS 15059 : 2023/IEC 60942 : 2017 Electroacoustics — Sound calibrators (<i>second revision</i>)	Identical
IEC 61672-1 Electroacoustics — Sound level meters: Part 1 Specifications	IS 15575 (Part 1) : 2016/IEC 61672-1 : 2013 Electroacoustics — Sound level meters: Part 1 specifications (<i>first revision</i>)	Identical

(Continued on third cover)

Contents		Page
Introduction		iv
1 Scope		1
2 Normative references		1
3 Terms and definitions		1
4 Measurements units and tolerances		2
5 Instrumentation		2
6 Circumstances for testing		3
6.1 Acoustical environment.....		3
6.2 Ambient conditions.....		3
6.3 Operator.....		3
7 Condition of tractor		3
7.1 Selection.....		3
7.2 Running-in and preliminary adjustment.....		3
8 Microphone location		4
9 Common noise measurement practice		4
10 Test report		4
Annex A (normative) Agricultural tractors		5
Annex B (informative) Specimen report form		8
Annex C (informative) Designation of Maintenance Agency		12
Bibliography		13

Introduction

Technical harmonization with OECD is ensured by the Maintenance Agency operating as specified in [Annex C](#).

TRACTORS FOR AGRICULTURE AND FORESTRY — MEASUREMENT OF NOISE AT THE OPERATOR'S POSITION — SURVEY METHOD

PART 1 NOISE AT THE OPERATOR'S POSITION — SURVEY METHOD

(*Second Revision*)

1 Scope

This International Standard specifies a method for the measuring and reporting of the noise at the operator(s) position of a tractor used in agriculture and forestry. The measured noise relates only to the basic machine and applies to tractors with machine-carried operators. The results provide information to the operator(s) in order to avoid exposing themselves to noise levels that could put their hearing at risk.

The conditions specified for the operation of the machines during the measurements are defined to provide a realistic and repeatable assessment of the maximum noise an operator should be subjected to when operating a machine. The test procedures specified in this International Standard are survey methods as defined in ISO 12001.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5353:1995, *Earth-moving machinery, and tractors and machinery for agriculture and forestry — Seat index point*

ISO 6395:2008, *Earth-moving machinery — Determination of sound power level — Dynamic test conditions*

ISO 12001, *Acoustics — Noise emitted by machinery and equipment — Rules for the drafting and presentation of a noise test code*

IEC 60942, *Electroacoustics — Sound calibrators*

IEC 61672-1, *Electroacoustics — Sound level meters*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

agricultural tractor

self-propelled agricultural vehicle having at least two axles and wheels, or endless tracks, particularly designed to pull agricultural trailers and pull, push, carry, and operate implements used for agricultural work (including forestry work), which may be provided with a detachable loading platform

Note 1 to entry: The agricultural vehicle has a maximum design speed of not less than 6 km/h and may be equipped with one or more seats.

[SOURCE: ISO 12934:2013, 3.1]

3.2

power take-off power

power measured at the dynamometer coupled to any shaft (with the tractor stationary) designed by the tractor manufacturer to be used as a power take-off

[SOURCE: ISO 789-1:1990, 3.2]

3.3 roll-over protective structure ROPS

framework (safety cab or frame) protecting drivers of tractors for agricultural and forestry that avoids or limits risk to the driver resulting from accidental overturning during normal operation

Note 1 to entry: The ROPS is characterized by the provision of space for a clearance zone either inside the envelope of the structure or within a space bounded by a series of straight lines from the outer edges of the structure to any part of the tractor that might come into contact with flat ground and that is capable of supporting the tractor in that position if the tractor overturns.

[SOURCE: ISO 5700:2013, 3.1]

3.4 unballasted tractor mass

mass of the tractor in working order with tanks and radiators full, roll-over protective structure with cladding, and any track equipment or additional front-wheel drive components required for normal use

Note 1 to entry: Not included are the operator, optional ballast weights, additional wheel equipment, special equipment and loads.

[SOURCE: ISO 5700:2013, 3.2]

4 Measurements units and tolerances

The following units and tolerances apply to the maximum value measured:

—	rotational frequency (r/min)	± 0,5 % ;
—	time (s)	± 0,2 s ;
—	distance (m or mm)	± 0,5 % ;
—	force (N)	± 1,0 % ;
—	mass (kg)	± 0,5 % ;
—	atmospheric pressure (kPa)	± 0,2 kPa ;
—	tyre pressure (Pa)	± 5 % .

5 Instrumentation

5.1 A precision quality sound level meter shall be used meeting or exceeding the requirements of IEC 61672-1 for a class 1 instrument. If alternative measuring equipment is used, the tolerances shall not exceed those given in the relevant clauses of IEC 61672-1 for a class 1 instrument. Measurement shall be carried out with a frequency weighting network in conformity with curve A and set to give slow response as described in IEC 61672-1.

5.2 The calibration of the equipment at the time of measurement shall be in accordance in all respects with the specifications of IEC 61672-1 for a class 1 instrument. Checking of the calibration shall be carried out at appropriate intervals and at least before and after each measurement session, using an acoustical calibrator in accordance with the specifications of IEC 60942 for a class 1 instrument. The calibrator shall be checked annually to verify its output and its calibration shall be traceable to a national standards laboratory.

5.3 An adequate technical description of the measuring equipment shall be given in the test report.

6 Circumstances for testing

6.1 Acoustical environment

6.1.1 Measurements shall be made in a sufficiently silent, flat, and open zone. The last 20 m next to the test zone shall be essentially level and there shall be no obstacle in this area likely to reflect significant sound, such as a building, solid fence, tree or other machine.

6.1.2 The surface of the test zone shall be of a kind where pneumatic tyres or endless rubber tracks do not cause excessive noise. It shall be made of concrete, asphalt or a similar material unless otherwise specified. The surface shall be as clean and dry as possible (e.g. free of gravel, leaves, snow, etc.).

6.1.3 For endless metal tracks, the surface of the test zone shall be of a kind where they do not cause excessive noise. In this case, it shall be a layer of humid sand as specified by ISO 6395:2008, 5.3.2.

6.2 Ambient conditions

6.2.1 Measurements shall be made in fine weather with little or no wind. The level of background noise and the level of wind noise at the microphone location shall be at least 10 dB(A) below the noise level measured during the test. Any extraneous noise that occurs while obtaining data, which is not connected to general sound level measurement, shall not be taken into consideration.

6.2.2 No corrections shall be made to the test results for the atmospheric conditions or other factors. Atmospheric pressure shall not be less than 96,6 kPa. If this is not possible because of conditions of altitude, a modified injection pump setting may have to be used, details of which will be included in the report.

6.3 Operator

6.3.1 No person other than the operator of the tractor shall be in the cab during measurements. However, when the noise is being measured at additional operator positions on the machine, the usual number of operators shall be present. No person other than the operator(s) shall be in a position to influence the noise measurements.

6.3.2 The operator shall not wear abnormally thick clothing or any additional attire, such as a hat or scarf, which could influence the sound measurement.

7 Condition of tractor

7.1 Selection

7.1.1 In the case of a third party performing the assessment, the manufacturer and the third party shall work together to select a tractor to be submitted for testing. The tractor shall comply with the manufacturer's product specification, and shall be operated in accordance with the manufacturer's instructions.

7.1.2 [Annex A](#) specifies conditions for agricultural tractors covered by this International Standard.

7.2 Running-in and preliminary adjustment

7.2.1 The tractor shall be new and run in prior to the test in accordance with the manufacturer's usual instructions. If a third party is responsible for the testing, the third party itself may run in the tractor

provided the authority of the manufacturer or their representative, who will remain responsible for the running-in, is obtained.

7.2.2 The adjustment of the carburetor or the injection pump as well as the setting of the governor shall conform to the specifications provided by the manufacturer. The manufacturer may make adjustments in conformity with these specifications prior to testing, but adjustments shall not be made during the test.

8 Microphone location

8.1 For seated operators, the microphone shall be located $250\text{ mm} \pm 20\text{ mm}$ to the side of the centre plane of the seat, the side being that on which the higher sound pressure level is encountered. The axis of the microphone shall be horizontal and the diaphragm shall face forward. The centre of the microphone shall be $700\text{ mm} \pm 20\text{ mm}$ above the seat index point (SIP) and $100\text{ mm} \pm 20\text{ mm}$ forward of that point.

8.2 The SIP shall be determined in accordance with ISO 5353.

8.3 For the seat location and adjustment of the seat, any suspension of the seat shall be depressed until the seat reaches the midpoint of its dynamic range. Where the position of the seat is adjustable only lengthwise and vertically, the longitudinal axis passing through the seat index point shall be parallel with the vertical longitudinal plane of the tractor passing through the centre of the steering wheel and not more than 100 mm from that plane.

9 Common noise measurement practice

9.1 During the entire test, the throttle lever shall be set fully open unless otherwise specified.

9.2 Once the test has started, the tractor shall never be operated in a way that is not in accordance with the manufacturer's published instructions in the operator's manual.

9.3 A 10 s period of stabilized running shall occur before any measurements are recorded.

9.4 All sound level measurements shall be recorded in dB(A) to three significant figures.

9.5 Make at least three measurements at each microphone position, as defined in [Clause 8](#), and for each operating condition. If the range of the sound level results obtained under each measuring condition exceeds 3 dB, further measurements shall be made until the readings of three successive measurements fall within 3 dB. The maximum value of these three readings will be used as the test result.

9.6 When the characteristics of the machine cause the sound pressure levels to fluctuate widely and the 3 dB requirement for successive readings cannot be met, the number of separate measurements shall be greater than the fluctuation range in decibels. The maximum value of these readings will be used as the test result.

9.7 In all cases, any measurement clearly out of range with the general sound pressure levels being read shall be disregarded.

9.8 Tests shall not be made in gears in which the forward speed will then exceed the safety limits of the testing equipment.

10 Test report

A specimen report form for the reporting of results is given in [Annex B](#).

Annex A (normative)

Agricultural tractors

A.1 General requirements

A.1.1 The tractor shall be unballasted. Wheeled tractors shall be fitted with normal agricultural pneumatic tyres, not more than 50 % worn.

A.1.2 For all tests, auxiliary components such as the hydraulic lift pump or air compressor may be disconnected only if it is practicable for the operator to do so as normal practice in work. Disconnection of any auxiliary shall be done in accordance with the operator's manual without using tools, unless otherwise specified for a particular test. If not, they should remain connected and operate at minimum load.

A.1.3 Before the noise measurement, it shall be established by a power take-off power test or other means that the power of the tractor is within 5 % of the manufacturer's rated value.

A.1.4 The optional test with the drawbar loaded should, preferably, be carried out using a draught load provided by a dynamometer vehicle positioned to eliminate interference with the sound field caused by the tractor.

NOTE This is not applicable for agricultural tractors with endless metal tracks.

A.1.5 Wheel slip during the optional test with the drawbar loaded shall not exceed 15 % and track slip shall not exceed 7 %.

NOTE This is not applicable for agricultural tractors with endless metal tracks.

A.2 Tractor options

A.2.1 If the tractor is fitted with a cab, all openings such as doors and windows shall be closed. The test may be repeated with them open provided they have been designed to operate in the open position and they do not cause a hazard during normal use of the machine. The windscreen shall remain in place, closed.

NOTE Measurements with doors, windows and hatches open are made for information purposes only to ensure that the user is made aware of any operating conditions where sound pressure levels could be harmful and exceed those measured in a closed cab.

A.2.2 When the measurements are being made, parts which normally operate at the same time as the engine (e.g. engine cooling fan) shall be functioning, but extra equipment powered by the engine or self-powered (e.g. windscreen wipers, ventilating fans heating and, power take-off) shall not be functioning.

A.2.3 If the tractor is equipped with a reverse driving position, the noise test may be repeated in the reverse position, in accordance with [A.3](#), subject to the manufacturer's instructions for driving in the reverse position as stated in the operator's manual. The windscreen of the tractor shall remain in place, closed.

A.2.4 For tractors that could be fitted with optional seats, the microphone shall be set relative to a seat index point chosen from the range available for fitting to a tractor. The results will also apply to any of the available seats that give a microphone position within a 50 mm radius sphere of this reference point. If any seat gives a microphone position outside this sphere, it shall be dealt with separately.

A.2.5 In the case of measurements on a tractor capable of operating as both a two-wheel drive and four-wheel drive tractor, the sound level shall be measured separately with the front axle engaged and disengaged.

A.2.6 Additional noise measurements may optionally be made with the engine running at maximum speed and all auxiliary air-conditioning equipment working. The heating or ventilating fans shall run at the maximum setting.

A.2.7 Additional noise measurements may optionally be made with the engine stopped and auxiliaries such as ventilating fans, defrosters and other electrical facilities working at maximum settings.

A.3 Required test procedures

A.3.1 Preliminary method

A.3.1.1 A preliminary test shall be made to determine the side of the operator encountering the highest sound pressure level (as mentioned in [8.1](#) and [8.2](#)) by operating the tractor without load in the gear or condition giving a forward speed as near as possible to 7,5 km/h.

NOTE For endless metal tracks, the gear or condition giving a forward speed as near as possible to 5 km/h.

A.3.2 No-load method

A.3.2.1 The noise shall be measured and reported while driving forward with no load in the gear or condition giving a speed as near as possible to 7,5 km/h.

NOTE For endless metal tracks, the gear or condition giving a forward speed as near as possible to 5 km/h.

A.3.2.2 The noise shall be measured and reported while driving forward with no load at the maximum design speed of the tractor.

A.4 Optional test procedures

A.4.1 Drawbar-load method

NOTE This is not applicable for agricultural tractors with endless metal tracks.

A.4.1.1 Measure

A.4.1.1.1 Geared transmissions

For geared transmissions, the noise shall be measured when the drawbar pull gives the maximum sound level in every forward gear. Starting with no load, the load shall be increased until the maximum sound pressure level is found. After each increase of load, time shall be allowed for the level of noise to stabilize before making the measurements. The corresponding engine speeds shall be recorded for each gear.

A.4.1.1.2 Continuously variable transmissions

For continuously variable transmissions, noise measurements shall be made for at least 7 equally spaced speeds over the range of 2,5 km/h to 17,5 km/h. Starting with no load, the load shall be increased until the maximum sound pressure level is found. After each increase of load, time shall be allowed for the level of noise to stabilize before making the measurements. The corresponding engine speeds shall be recorded for each.

A.4.1.2 Report

The noise shall be reported in the forward gear or condition giving the nearest nominal speed to 7,5 km/h at which the drawbar pull gives the maximum sound level. Noise shall also be reported in any gear or condition giving a sound level of at least 1 dB(A) greater.

A.5 Test report

The test report shall contain the results of measurements made according to [Clauses 9](#) and [A.3. Annex B](#) provides an acceptable test report format.

Annex B
 (informative)

Specimen report form

Noise test in accordance with ISO 5131		
GENERAL INFORMATION		
Report number:		Date:
Location of test:		
Submitted for test by:		
Selected for text by:		
Name and address of manufacturer:		
Name and address of manufacturer of protective structure:		
TEST CONDITIONS		
Description of surface on which the tractor or machine was tested:		
Atmospheric pressure (kPa):		
Make/ type/ serial no. of sound meter used:		
SPECIFICATIONS OF TEST TRACTOR OR MACHINE		
Make:		
Model (trade name):		
Model denomination(s) for other countries:		
1st Serial no. or prototype no.:		
Rated PTO power and corresponding speed:		
Max. no-load engine speed:		
Transmission type or gears x ranges:		
Type (2 WD or 4WD; <i>rubber or steel tracks (if applicable); articulated 4WD or articulated 4WD with twin (dual) wheels (if applicable);</i>		
Reversible driver's position:	Y	N

SPECIFICATIONS OF PROTECTIVE STRUCTURE	
Make of the protective structure:	
Model of the protective structure:	
Brief description:	
Interior padding (<i>material and sizes</i>):	Roof:
	Doors:
	Floor:
	Front panel:
	Rear panel:
	Side panels:
	Instrument panel and steering column:
Draught proofing (<i>material and sizes</i>):	
Glass (<i>material and sizes</i>):	
Heaters and ventilators (<i>make and type</i>):	
Windscreen wipers (<i>make and type</i>):	
Direction indicators (<i>make and type</i>):	

TEST RESULTS				
No-load procedure				
A) Measure noise while driving forward with no load in the gear or condition giving a speed as close as possible to 7,5 km/h				
<i>All openings closed</i>				
Gear number	Engine speed (rev/min)	Measured travelling speed (km/h)	Number of driving wheels (2 or 4)	Sound level dB(A)
<i>All openings open (optional)</i>				
Gear number	Engine speed (rev/min)	Measured travelling speed (km/h)	Number of driving wheels (2 or 4)	Sound level dB(A)
B) Measure noise while driving forward with no load at the maximum design speed of the tractor.				
<i>All openings closed</i>				
Gear number	Engine speed (rev/min)	Measured travelling speed (km/h)	Number of driving wheels (2 or 4)	Sound level dB(A)
<i>All openings open (optional)</i>				
Gear number	Engine speed (rev/min)	Measured travelling speed (km/h)	Number of driving wheels (2 or 4)	Sound level dB(A)

TEST RESULTS					
Drawbar-load procedure					
Measure noise in each forward gear at which the drawbar pull gives the maximum sound level. [Report at the speed as close as possible to 7,5 km/h and also in any gear with a sound level at least 1 dB(A) greater]					
<i>All openings closed</i>					
Gear number	Drawbar pull (kN)	Engine speed (rev/min)	Measured travelling speed (km/h)	Number of driving wheels (2 or 4)	Sound level dB(A)
<i>All openings open (optional)</i>					
Gear number	Drawbar pull (kN)	Engine speed (rev/min)	Measured travelling speed (km/h)	Number of driving wheels (2 or 4)	Sound level dB(A)

TRACTORS OR MACHINES TO WHICH TEST RESULTS ARE APPLICABLE								
Tractor or Machine					ROPS			Differences with model tested
Make	Model	Type	WD	Other	Make	Model	Type	

Annex C (informative)

Designation of Maintenance Agency

A Maintenance Agency has been established by the ISO Technical Management Board (TMB) to ensure that technical harmonization can be maintained between ISO/TC 23/SC 2 Standards and OECD Tractor Test Codes. It operates through guidelines approved by the TMB, accessible at <http://standards.iso.org/iso/5131/> that entrust it to the following functions:

- a) to receive the requests for changes from recognized ISO/TC 23/SC 2 P-members;
- b) to evaluate and resolve the requests for changes;
- c) to publish the approved changes.

Changes to this International Standard will be announced by the MA Secretariat to ISO/TC 23/SC 2 and will be made publicly available at <http://standards.iso.org/iso/5131>. They constitute authoritative amendments to [Clauses 1](#) to [10](#) and to the annexes of this International Standard.

Bibliography

- [1] ISO 789-1:1990, *Agricultural tractors — Test procedures — Part 1: Power tests for power take-off*
- [2] ISO 5700:2013, *Tractors for agriculture and forestry — Roll-over protective structures — Static test method and acceptance conditions*
- [3] ISO 12934:2013, *Tractors and machinery for agriculture and forestry — Basic types — Vocabulary*
- [4] OECD Code 5: July 2014, *OECD Standard Code for the official measurement of noise at the driving position(s) on agricultural and forestry tractors*

(Continued from second cover)

The Committee has reviewed the provisions of the following International Standard referred in this adopted standard and has decided that it is acceptable for use in conjunction with this standard:

<i>International Standard</i>	<i>Title</i>
ISO 12001	Acoustics — Noise emitted by machinery and equipment — Rules for the drafting and presentation of a noise test code

In reporting the result of a test made in accordance with this standard, if the final value, observed or calculated, is to be rounded off, it shall be done in accordance with IS 2 : 2022 'Rules for rounding off numerical values (*second revision*)'.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 2016* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Head (Publication & Sales), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the website-www.bis.gov.in or www.standardsbis.in.

This Indian Standard has been developed from Doc No.: FAD 11 (23226).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002

Telephones: 2323 0131, 2323 3375, 2323 9402

Website: www.bis.gov.in

Regional Offices:

	Telephones
Central : 601/A, Konnectus Tower -1, 6 th Floor, DMRC Building, Bhavbhuti Marg, New Delhi 110002	{ 2323 7617
Eastern : 8 th Floor, Plot No 7/7 & 7/8, CP Block, Sector V, Salt Lake, Kolkata, West Bengal 700091	{ 2367 0012 2320 9474
Northern : Plot No. 4-A, Sector 27-B, Madhya Marg, Chandigarh 160019	{ 265 9930
Southern : C.I.T. Campus, IV Cross Road, Taramani, Chennai 600113	{ 2254 1442 2254 1216
Western : Plot No. E-9, Road No.-8, MIDC, Andheri (East), Mumbai 400093	{ 2821 8093

Branches : AHMEDABAD. BENGALURU. BHOPAL. BHUBANESHWAR. CHANDIGARH. CHENNAI. COIMBATORE. DEHRADUN. DELHI. FARIDABAD. GHAZIABAD. GUWAHATI. HIMACHAL PRADESH. HUBLI. HYDERABAD. JAIPUR. JAMMU & KASHMIR. JAMSHEDPUR. KOCHI. KOLKATA. LUCKNOW. MADURAI. MUMBAI. NAGPUR. NOIDA. PANIPAT. PATNA. PUNE. RAIPUR. RAJKOT. SURAT. VISAKHAPATNAM.