भारतीय मानक Indian Standard

IS 18989 : 2024 ISO 20607 : 2019

मशीनरी की सुरक्षा — निर्देश पुस्तिका — सामान्य प्रारूपण सिद्धांत

Safety of Machinery — Instruction Handbook — General Drafting Principles

ICS 13.110

© BIS 2024 © ISO 2019



भारतीय मानक ब्यूरो BUREAU OF INDIAN STANDARDS मानक भवन, 9 बहादुर शाह ज़फर मार्ग, नई दिल्ली - 110002 MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI - 110002 www.bis.gov.in www.standardsbis.in

October 2024

Price Group 11

NATIONAL FOREWORD

This Indian Standard which is identical to ISO 20607 : 2019 'Safety of machinery — Instruction handbook — General drafting principles' issued by the International Organization for Standardization (ISO) was adopted by the Bureau of Indian Standards on recommendation of the Safety of Machinery Sectional Committee and approval of the Mechanical Engineering Divisional Council.

The text of ISO standard has been approved as suitable for publication as an Indian Standard without deviations. Certain conventions are, however, not identical to those used in Indian Standards. Attention is particularly drawn to the following:

- a) Wherever the words 'International Standard' appears referring to this standard, they should be read as 'Indian Standard'; and
- b) Comma (,) has been used as a decimal marker while in Indian Standards, the current practice is to use a point (.) as the decimal marker.

In this adopted standard, reference appears to certain International Standards for which Indian Standards also exist. The corresponding Indian Standards, which are to be substituted in their respective places, are listed below along with their degree of equivalence for the editions indicated:

International Standard	Corresponding Indian Standard	Degree of Equivalence
ISO 12100 : 2010 Safety of machinery — General principles for design — Risk assessment and risk reduction	IS 16819 : 2018/ISO 12100 : 2010 Safety of machinery — General principles for design — Risk assessment and risk reduction	Identical

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 2022 'Rules for rounding off numerical values (*second revision*)'. The number of significant places retained in the rounded-off value should be the same as that of the specified value in this standard.

Contents

Page

Intro	ductio	1	iv				
1	Scope	9					
2	Norm	ative references	1				
3	Terms and definitions						
4	Princ	inles and general information	2				
•	4.1	General	2				
	4.2	Target group for the instruction handbook	2				
	4.3	Information needs					
	4.4	Comprehensible terminology and wording	3				
	4.5	Presentation of the instruction handbook	3				
	4.6	Information from component or subsystem suppliers	4				
	4.7	Legibility	4				
	4.8	Warnings, hazard and safety symbols used in the instruction handbook					
	4.9	Structuring					
	4.10	Kesiduai Fisks					
		4.10.1 General and warning devices provided with the machine	4 Д				
	4.11	IT security vulnerabilities					
F	Cont	and structure of the instruction handhook	F				
3	5 1	General	ס כ				
	5.2	Instruction handbook content					
	0.2	5.2.1 Basic parts of an introduction handbook					
	5.2.2 5.2.3	5.2.2 Safety					
		5.2.3 Machine overview					
		5.2.4 Transportation, handling and storage	9				
		5.2.5 Assembly, installation and commissioning	9				
		5.2.6 Original equipment manufacturer settings					
		5.2.7 Operation					
		5.2.8 Product or capacity changeover					
		5.2.9 Inspection, testing and maintenance	11 12				
		5.2.10 Cleaning and sanitizing	12 12				
		5.2.11 Fault Illuling/ I oubleshooting and repair	13 12				
		5.2.12 Distinationing, disabiling and scrapping	13				
		5.2.14 Index					
		5.2.15 Glossary					
		5.2.16 Annexes	14				
6	Lang	uage and formulation/style guide	14				
U	6.1	General					
	6.2	Language version(s)					
	6.3	Formulation guidance for instructions	14				
	6.4	Simple wording for instructions	15				
	6.5	Warnings	15				
7	Form	s of publication					
Anne	x A (inf	ormative) Correspondence between ISO 12100:2010, 6.4, and this document					
Anne	x B (inf	ormative) Presentation and formatting					
Anne	x C (inf	ormative) Recommendations for writing instructions	21				
Biblic	ograph	y	24				

Introduction

This document is a type-B standard as stated in ISO 12100.

This document is of relevance, in particular, for the following stakeholder groups representing the market players with regard to machinery safety:

- machine manufacturers (small, medium and large enterprises);
- health and safety bodies (regulators, accident prevention organisations, market surveillance etc.).

Others can be affected by the level of machinery safety achieved with the means of the document by the above-mentioned stakeholder groups:

- machine users/employers (small, medium and large enterprises);
- machine users/employees (e.g. trade unions, organizations for people with special needs);
- service providers, e. g. for maintenance (small, medium and large enterprises);
- consumers (in case of machinery intended for use by consumers).

The above-mentioned stakeholder groups have been given the possibility to participate at the drafting process of this document.

In addition, this document is intended for standardization bodies elaborating type-C standards.

The requirements of this document can be supplemented or modified by a type-C standard.

For machines which are covered by the scope of a type-C standard and which have been designed and built according to the requirements of that standard, the requirements of that type-C standard take precedence.

The structure of safety standards in the field of machinery is as follows.

- a) **Type-A standards** (basic safety standards) give basic concepts, principles for design and general aspects that can be applied to machinery;
- b) **Type-B standards** (generic safety standards) dealing with one or more safety aspect(s), or one or more type(s) of safeguards that can be used across a wide range of machinery:
 - type-B1 standards on particular safety aspects (for example, safety distances, surface temperature, noise);
 - type-B2 standards on safeguards (for example, two-hand control devices, interlocking devices, pressure-sensitive devices, guards);
- c) **Type-C standards** (machine safety standards) dealing with detailed safety requirements for a particular machine or group of machines.

This type-B standard is written to provide guidance to machine manufacturers on how to provide an instruction handbook. According to ISO 12100:2010, 6.4.1.1, drafting information for use is an integral part of the design of a machine. Information for use consists of communication links, such as texts, words, signs, signals, symbols or diagrams, used separately or in combination to convey information to the user. Information for use is intended for professional and/or non-professional users. Instructions are a key part of the information for use of a machine. This document provides safety specifications for machinery that is more specific than IEC/IEEE 82079-1.

The instruction handbook drafted in accordance with this document is intended to inform the user in such a manner that after reading it, he/she is aware of how the machine can be used safely according to its intended use during its life cycle, considering also aspects of reasonably foreseeable misuse.

The objective fulfilled by this document is to improve the safety specifications and readability/ease of use of the instruction handbook of the machine.

this Page has been intertionally left blank

Indian Standard

SAFETY OF MACHINERY — INSTRUCTION HANDBOOK — GENERAL DRAFTING PRINCIPLES

1 Scope

This document specifies requirements for the machine manufacturer for preparation of the safety-relevant parts of an instruction handbook for machinery.

This document:

- provides further specifications to the general requirements on information for use given in ISO 12100:2010, 6.4.5; and
- deals with the safety-related content, the corresponding structure and presentation of the instruction handbook, taking into account all phases of the life cycle of the machine.

NOTE 1 The strategy for risk reduction at the machine is given in ISO 12100:2010, Clause 6, and includes inherently safe design measures, safeguarding and complementary risk reduction measures as well as information for use.

NOTE 2 <u>Annex A</u> contains a correspondence table between ISO 12100:2010, 6.4, and this document.

NOTE 3 Information for conception and preparation of instructions in general is available in IEC/IEEE 82079-1.

This document establishes the principles which are indispensable to provide information on residual risks.

This document does not address requirements for declaration of noise and vibration emissions.

This document is not applicable to machinery manufactured before the date of its publication.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 12100:2010, Safety of machinery — General principles for design — Risk assessment and risk reduction

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12100 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <u>https://www.iso.org/obp</u>
- IEC Electropedia: available at http://www.electropedia.org/

3.1

instruction handbook

part of the information for use provided by a machine manufacturer to the machine user that contains instructions and advice concerning the use of the machinery during all phases of its life cycle

Note 1 to entry: Instruction handbook is a subset of information for use. For more information, see ISO 12100:2010, 6.4.

3.2

integrator

entity who designs, provides, manufactures or assembles an integrated manufacturing system and is in charge of the safety strategy, including the protective measures, control interfaces and interconnections of the control system

Note 1 to entry: The integrator may be a manufacturer, assembler, engineering company or the user.

[SOURCE: ISO 11161:2007, 3.10]

3.3

risk reduction measure

action or means to eliminate hazards or reduce risks

Note 1 to entry: The term "risk reduction measure" used in this document corresponds to the term "protective measure" used in ISO 12100.

EXAMPLE Inherently safe design; protective devices; personal protective equipment; information for use and installation; organization of work; training; application of equipment; supervision.

[SOURCE: ISO/IEC Guide 51:2014, 3.13, modified — The synonymous term has been deleted and Note 1 to entry has been added.]

3.4

vulnerable user

user at greater risk of harm from products or systems, due to age, level of literacy, physical or mental condition or limitations, or inability to access product safety information

[SOURCE: ISO/IEC Guide 51:2014, 3.16, modified — The term "consumer" has been replaced by "user" in the term and in the definition.]

4 Principles and general information

4.1 General

The purpose of the instruction handbook is to provide the user with such information that the machinery concerned can be effectively and safely used during the life cycle of the machine, also considering reasonably foreseeable misuse. When the instruction handbook is being prepared, the communication process "read – think – use" should be followed in order to achieve the maximum effect for the reader.

NOTE For general principles of design of instruction handbooks see also IEC/IEEE 82079-1:2019, 6.3.

The instruction handbook shall follow sequential operations, as applicable.

The instruction handbook shall provide the target group(s) with information on:

- intended use;
- the machine itself and, as appropriate, its parts and components;
- relevant phases of the life cycle of the machine according to ISO 12100;
- hazards that have been identified and risk reduction measures that have been applied in conjunction with activities the user is expected to perform (human machine interaction); and
- residual risks, as these can require risk reduction by the user of the machine.

4.2 Target group for the instruction handbook

Target groups consisting of persons who interact directly with the machine and the task(s) they perform shall be identified.

Target groups that can interact with the machine shall be described in the instruction handbook and typically include, but are not limited to:

- a) installers (for example, system integrators);
- b) operators;
- c) maintenance personnel or technicians;
- d) cleaning personnel;
- e) dismantling personnel.

4.3 Information needs

The instruction handbook shall take into account the specific needs, foreseeable knowledge and technical vocabulary of the target group intended to use the machine.

4.4 Comprehensible terminology and wording

The instruction handbook shall be:

- a) comprehensible by using preferably standardized terms, well recognized technical terms or explaining special technical terms and expressions, if used;
- b) as simple and as brief as possible by using, for example
 - language-independent instructions to support the text (pictograms, pictures, drawings etc.);
 - short and simple sentences;
 - where synonyms are available, use only one term;
 - tables and listings;
 - chronological, logical and sequential writing;
 - repetition, where necessary;
 - diagrams, charts;
- c) expressed in consistent terms and units (for example, SI quantities);
- d) drafted using the active voice;
- e) easily translatable.

NOTE For guidance and examples on formulation, see <u>Annex C</u>.

4.5 Presentation of the instruction handbook

The instruction handbook may be presented as a single document or as a set of separate documents, for example, for the following reasons:

- instructions intended for different target groups (see <u>4.2</u>);
- a single document is too large or complex;
- document is addressing different life phases of the machine.

When providing information for different target groups in a single document the information shall be clearly separated so that a user does not accidently refer to information which does not apply.

4.6 Information from component or subsystem suppliers

Where information from component or subsystem suppliers is necessary for the instruction handbook, it shall either:

- be incorporated directly in the instruction handbook; or
- provide the relevant parts of the original instruction handbook of components/subsystems from suppliers and making appropriate references therein.

4.7 Legibility

Text and graphical symbols shall be legible for the target group(s).

NOTE For examples of recommended text font sizes and graphical symbol heights, see <u>Annex B</u>.

4.8 Warnings, hazard and safety symbols used in the instruction handbook

Warnings, hazard and safety symbols shall be distinguishable from other content of the instruction handbook.

When signs (pictograms) and/or written warnings are used to indicate important messages their meaning shall be clearly explained.

NOTE 1 <u>Annex C</u> provides guidance on wording.

NOTE 2 Terms often used in instruction handbooks are "DANGER", "WARNING", "CAUTION" without or in combination with pictograms. For the definitions of these terms and more information about colours for coding, see ISO 3864-2.

NOTE 3 For safety signs and symbols, see ISO 7000 and ISO 7010.

4.9 Structuring

The instruction handbook should be structured in a such a way that the information can be quickly located, for example, by using sections, chapters, sub-clauses, headings, numbers, highlighting, colors.

NOTE See <u>Clause 5</u> for a recommended structure.

Instruction handbooks shall be presented in a such a way that the reader can determine if they are complete (for example, using a table of contents and the numbering of pages).

4.10 Residual risks

4.10.1 General

Based on the risk assessment and the risk reduction measures the manufacturer of the machine shall inform and warn the target group, if relevant, for each residual risk. General statements about residual risks shall be avoided.

NOTE The information on residual risks form the basis for further risk reduction measures to be introduced by the user of the machine.

Explanations on the risks and appropriate warnings shall be given.

4.10.2 Signals and warning devices provided with the machine

The instruction handbook shall describe signals and warning devices provided with the machine and explain their meaning.

4.11 IT security vulnerabilities

Where applicable, the instruction handbook shall provide information concerning IT security vulnerabilities. See ISO/TR 22100-4:2018, 10.4.

5 Content and structure of the instruction handbook

5.1 General

The essential information, relevant for the user, shall be structured in an instruction handbook (see <u>Table 1</u> for an example). <u>Table 1</u> does not take into account all different target groups, but is a template for information that can be placed in an instruction handbook for the machine concerned. From this, a writer can create a specific instruction handbook for a particular target group. An instruction handbook for a user/operator need not contain all the sections of <u>Table 1</u>.

Section	Content
Basic parts of an instruction	Title page
handbook	Table of contents
(see <u>5.2.1</u>)	Introduction to/purpose of this instruction handbook
Safety (see <u>5.2.2</u>)	General safety information and general safety instructions
Machine overview	Machine description
(see <u>5.2.3</u>)	Intended use
	Key machine specifications
	Controls and displays descriptions
	Floor plan/layout
Transportation, handling and storage (see <u>5.2.4</u>)	Transporting, handling and storing the machine and/or the components
Assembly, installation and	Assembly/integration of the machine
commissioning	Positioning of the machine
(see <u>5.2.5</u>)	Mechanical, pneumatic, hydraulic and electrical installation
	Check and test of safety systems
	Installation check
	Commissioning
Original equipment manu-	Mechanical settings and synchronization
facturer settings	Safety-related (setting) parameters
(see <u>5.2.6</u>)	Pneumatic, hydraulic, electrical and vacuum settings
	Other settings
Operation	Operating modes
(see <u>5.2.7</u>)	Machine start-up and shut-down
	Sequence or chronology of operations
	Other operating instructions, if applicable
Product or capacity changeo-	General product or capacity changeover information
ver (see <u>5.2.8</u>)	Product-specific set-up information
Inspection, testing and maintenance	Maintenance instructions
(see <u>5.2.9</u>)	

Table 1 — Instruction handbook content example

Table 1 (continued)

Section	Content
Cleaning and sanitizing (see 5.2.10)	Cleaning and/or sanitizing of the machine
Fault finding/ troubleshooting and repair (see <u>5.2.11</u>)	General fault finding/troubleshooting and repair information Troubleshooting chart (electrical engineering) Troubleshooting of electrical sensors, vacuum systems, pneumatic systems and hydraulic systems
Dismantling, disabling and scrapping (see <u>5.2.12</u>)	Dismantling, disabling and scrapping instructions
Documents and drawings (see <u>5.2.13</u>)	Documents, drawings and parts list
Index, glossary, annexes	See <u>5.2.14</u> to <u>5.2.16</u>

5.2 Instruction handbook content

5.2.1 Basic parts of an introduction handbook

5.2.1.1 General

The following information shall be included in the instruction handbook, as applicable:

- a) title page;
 - date of issue, version of publication of the instruction handbook;
 - machine designation (model and/or type);
 - sufficient information to identify the machine(s) to which the handbook applies (e.g. identification number, serial number(s), period of application);
- b) table of contents;
- c) introduction to/purpose of this instruction handbook;
- d) how to read and apply the instruction handbook;
- e) name of the manufacturer and contact details (postal address, phone numbers, email address, website);
- f) type of instruction handbook (for example, operation, maintenance, control software, user guide);
- g) date of manufacture;
- h) markings in order to indicate compliance with mandatory/legal requirements;
- i) list of used abbreviations;
- j) symbols and signs for text markings.

If an instruction handbook consists of more than one part, each part is given its own title page as defined above. Identification of this information shall be in a prominent place.

If an instruction handbook consists of more than one part, each part shall be identified in relation to the other parts (for example, part 2 of 5 parts). The following subjects shall be included, as applicable:

- addressed target groups;
- abilities/skills required by the target group(s);

— reader's guide/marking conventions/structure of the instruction handbook.

5.2.1.2 Table of contents

The table of contents shall show the structure of the instruction handbook and serves as a navigation aid within the document.

The instruction handbook shall have a table of contents, if it exceeds 12 pages unless the size or form (for example, instruction card) makes this unnecessary.

Instruction handbooks shall have numbered pages or electronic equivalent (e.g. links).

The table of contents shall also indicate unnumbered text elements such as preface, abbreviated instructions, reader instructions, register/index and appendices, as applicable.

The table of contents can be created in various ways, for example:

- a) a full table of contents of the instruction handbook with:
 - 1) the chapters and sections of the first three levels of the subdivision; and
 - 2) the page number or electronic equivalent where each chapter and section begins;
- b) a simplified table of contents with a full table of contents for each part;
- c) the table of contents should reflect each target group and lifecycle phase.

In a simplified table of contents, there should at least the first level of subdivision with the corresponding page numbers/electronic equivalents.

5.2.2 Safety

5.2.2.1 General

General safety requirements, not restricted to specific tasks, shall be provided together in a specific part of the instruction handbook, preferably in the "Safety" clause. For specific tasks described in the instruction handbook, safety information shall be included where the task is described.

5.2.2.2 General rules for preparation of the "Safety" clause

- a) warnings about potentially hazardous situations that can occur during intended use of the machine;
- b) warnings regarding potentially hazardous situations arising from reasonably foreseeable misuse;
- c) residual risks to be described;
- d) general warnings and precautions to be included.

The following topics shall be added, if relevant:

- substances and emissions that can create risk for the persons that can be involved in the machine operations;
- warnings, where the use of the machine can negatively influence electrically controlled medical devices, such as pacemakers;
- content related to the safety of the user groups. Attention should be given to protect vulnerable user groups (e.g. children, elderly people);
- personal protective equipment to be used for specific tasks;

- safety symbols, safety signs and/or pictograms used in and on the machine, including an image
 of them;
- location of safety symbols, safety signs and/or pictograms on the machine;
- instructions for renewing of safety symbols, safety signs and/or pictograms on the machine, if necessary.

Standardized symbols (see, for example, ISO 7010, IEC 61310) shall be used to indicate important messages such as cautions, warnings and safety instructions.

5.2.2.3 Emergency situations

Where applicable, the instruction handbook shall include information to address specific emergency situations, such as:

- a) the operating method to be followed in the event of accident or breakdown;
- b) the type of fire-fighting equipment to be used; and
- c) a warning of possible emission or leakage of hazardous substance(s) and, if applicable, an indication of means for fighting their effects.

5.2.3 Machine overview

The instruction handbook shall include a general description of the machine. The following information shall be included, where applicable:

- a) machine description;
- b) graphical description (for example, floor plan, drawings, images);
- c) intended use including the type of material/products that can be processed by the machine;
- d) specific applications that are prohibited;
- e) key machine specifications, such as:
 - length, width and height;
 - mass;
 - operating speed;
 - characteristics of the power supply;
 - limits for intended operating conditions, such as temperature, relative humidity and air pressure;
 - intended life limit of the machine;
 - lifetime (mission time) of components, where relevant for safety aspects;
- f) control and display descriptions;
- g) requirements regarding (work)place or environment in which the machine is foreseen to be used (for example, indoors, outdoors, clean room, potentially explosive atmosphere).

5.2.4 Transportation, handling and storage

The following information shall be included in the instruction handbook for transportation, handling and storage of the machine and/or the components, if relevant:

- physical characteristics such as dimensions during transportation, mass and centre of gravity of the machine, gripping/lifting points to be used;
- recommended transportation and handling method including required skills and equipment;
- environmental conditions for storage, such as limits for temperature, relative humidity and avoidance of direct sunlight.

5.2.5 Assembly, installation and commissioning

5.2.5.1 Assembly of the machine

Machines that are not assembled or installed by the manufacturer or under the manufacturer's responsibility shall contain the following instructions, if relevant:

- requirements and procedures for assembly and mounting (for example, temporary support or safeguarding, appropriate climatic conditions);
- requirements for testing, where necessary;
- use of special tools and equipment;
- information on safe disposal of packaging materials and preservation measures.

5.2.5.2 Positioning of the machine

Machines that are not positioned by the manufacturer or under the manufacturer's responsibility shall contain the following instructions, if relevant:

- minimum requirements for placing (for example, floor characteristics, point load, dynamic load, levelling, alignment);
- minimum requirements for fixing and anchoring the machine;
- requirements for accessibility around the machine (for example, for maintenance, cleaning, sanitizing, work spaces).

5.2.5.3 Installation

The instruction handbook shall include information for mechanical, pneumatic, hydraulic and electrical installations, and in particular the required characteristics of the energy supply (for example, mechanical, pneumatic, hydraulic, electrical).

Other information to include in the instruction handbook, if relevant, are:

- characteristics of necessary fluids including hazardous substances;
- necessity for an additional exhaust extraction system and its characteristics.

5.2.5.4 Checking and testing of safety systems

The instruction handbook shall include procedures for checking and testing safety systems.

Machines where the installation check is not performed by the manufacturer or under the manufacturer's responsibility shall include procedures for checking the correct installation, if relevant.

Each safety relevant check shall be described with the following content:

- what to be checked;
- how to check;
- criteria for acceptance/non-acceptance;
- action required in case of non-acceptance.

5.2.5.5 Commissioning

If the machine is not commissioned by the manufacturer or under the manufacturer's responsibility, the instruction handbook shall include procedures for commissioning and first use of the machine, such as:

- specific risks and hazards, and precautions to be taken;
- information about special procedures for commissioning, if required;
- securing and packaging materials that shall be removed (also consider protective films, strips, etc.);
- necessary tools and equipment;
- procedures, such as adjustments, testing, measuring and reporting; and
- inspections.

5.2.6 Original equipment manufacturer settings

The instruction handbook shall include instructions regarding original equipment manufacturer settings where accessible for the machine user, such as:

- mechanical settings and synchronization;
- safety-related (setting) parameters;
- pneumatic, hydraulic, electrical and vacuum settings; and
- other settings.

5.2.7 Operation

The instruction handbook shall include instructions regarding operating safety considerations, such as:

- intended use;
- residual risks;
- information regarding safety relevant emissions [see ISO 12100:2010, 6.4.5.1 c) 4)];
- actuation of controls;
- setting and adjustment;
- operating modes;
- location of the intended operator positions;
- error messages from the control system and location of the error;
- personal protective equipment needed to be used;
- an indication of training requirements;

- checking of hazard area for the absence of persons;
- procedures for starting, control during operation, stopping, emergency situation, reset and restarting (including relevant safety-related parts);
- conversions or tool changes;
- procedures for clearing jams or blockages without creating hazards;
- information regarding the operational environment;
- information about vibration emission of hand-held machines and hand-guided machinery;
- illustrations that clarify and/or provide insight into key functions and risk reduction measures;
- recommendations for removal of waste;
- machine start-up and shut-down;
- sequence or chronology of operations; and
- other operating instructions, if applicable.

Operations that must be carried out by more than one person shall be prescribed. Appropriate warning shall be provided about the consequences if the recommended sequence of operations is not followed.

The operator shall be informed of possible error messages and indications of warning components such as perceptible indication of normal and abnormal operation and recognition of signals.

Signals or displays intended to indicate imminent risk of hazardous situations shall be stated in a comprehensible and unambiguous manner.

5.2.8 Product or capacity changeover

The instruction handbook shall include instructions and safety requirements on foreseeable product or capacity changeover, if applicable:

- product or workpiece size changes;
- tool changes;
- material changes;
- energy changes;
- equipment changes;
- data changes;
- process changeover; and
- procedures to restore operation.

The instruction handbook shall include product-specific set-up information.

5.2.9 Inspection, testing and maintenance

The instruction handbook shall include general maintenance instructions and safety-relevant information, such as:

- intended lifetime for the machine and its components;
- nature, frequency and criteria for inspections;

- specification of the spare parts, in particular those affecting the safety of the machine;
- characteristics of the substances to be used;
- instructions on how to safely perform maintenance operations:
 - instructions relating to maintenance operations which require technical knowledge or particular skills and, hence, need to be carried out exclusively by skilled persons (for example, maintenance staff, specialists);
 - instructions relating to maintenance actions (replacement of parts, etc.) which do not require specific skills and hence may be carried out by other persons (for example, operators);
- drawings and diagrams enabling maintenance personnel to carry out their task rationally (especially fault-finding tasks);
- an overview of necessary tools, replaceable resources, and cleaning equipment needed for maintenance;
- energy control procedures [for example, isolation, dissipation and/or restraint (containment), marking and span-of-control];
- procedures to restore operation;
- replacement parts identification;
- a timetable for necessary maintenance with references on the appropriate procedures, where applicable;
- any restrictions on maintenance that may be performed by the manufacturer because of safety reasons only.

Specific risks and hazards during maintenance shall be taken into account.

Information on the recommended spare parts to ensure a safe operation of the machine shall be given or referenced.

All safety relevant inspection, testing and maintenance for the whole machine and its accessories shall be described in one single section, with relevant information on:

- a) what to be inspected/tested/maintained;
- b) frequency of the inspections/tests/maintenance;
- c) how to inspect/test/maintain;
- d) criteria for acceptance or non-acceptance;
- e) action required in case of non-acceptance.

5.2.10 Cleaning and sanitizing

The instruction handbook shall include instructions and information to clean and/or sanitize a machine to an appropriate level for the application, such as:

- tools, equipment and/or characteristics of cleaning agents required;
- personal protective equipment required;
- specific mode of operation;
- required energy isolation or control;
- cleaning and sanitizing procedures; and

procedures to restore operation.

5.2.11 Fault finding/troubleshooting and repair

The instruction handbook shall include instructions and information for general fault finding/ troubleshooting and repair, such as:

- fault identification and location for repair;
- troubleshooting; and
- procedures to repair the machine and restore operation.

The fault list should be based on certain logic. For example, first faults that are easy to resolve, or the most common faults first, see <u>Table 2</u>.

Fault message	Fault	Possible cause or procedure for detecting the fault	Solution	Performed by (unskilled/skilled/ certified)

Where necessary, add special notes about faults, precautionary measures and safety instructions.

The instruction handbook shall include instructions for reporting specific or unexpected faults or failures to the manufacturer.

5.2.12 Dismantling, disabling and scrapping

The instruction handbook shall include instructions for dismantling, disabling and scrapping of a machine, if applicable:

- preventive measures (technical and organizational);
- energy control procedures [for example, isolation, dissipation and/or restraint (containment)];
- special tools and equipment;
- special risk reduction measures;
- required personal protective equipment;
- sequence or chronology for decommissioning.

Scrapping instructions shall describe the actions the user has to perform at the end of the life cycle of a machine or part, with instructions for dismantling, disposal, recycling and/or destruction, with safety instructions and precautions against risks and hazards to health and the environment.

5.2.13 Documents and drawings

The instruction handbook shall include, or reference, necessary documents and drawings, such as:

- electrical, hydraulic, pneumatic schematics, as appropriate;
- parts lists;
- components supplier instruction handbooks; and
- safety-relevant documents, drawings, data sheets and declarations.

5.2.14 Index

An instruction handbook should include an index, where applicable. Reference to this index should be included in the table of contents.

5.2.15 Glossary

If necessary, an instruction handbook should include a glossary of technical terms used, including synonyms and the meaning of the acronyms.

5.2.16 Annexes

An instruction handbook may include annexes, such as for:

- auxiliary/associated equipment;
- description of tools to be used;
- detailed technical specifications;
- list of spare parts;
- instruction handbooks for supplied components;
- assembly drawings and diagrams;
- pneumatic, electrical, hydraulic or other relevant diagrams;
- tuning or adjustments lists;
- statutory declarations.

6 Language and formulation/style guide

6.1 General

This clause provides instructions for writing clear texts in instruction handbooks. Using the proper writing style and right vocabulary ensures that the reader can easily use the information.

NOTE 1 <u>Annex C</u> contains a number of examples.

NOTE 2 IEC/IEEE 82079-1 contains more detailed guidance.

6.2 Language version(s)

The instruction handbook shall be provided in the language(s) as agreed with the customer. When providing the instruction handbook, the manufacturer shall be aware of applicable legal requirements of the country in which the machine is placed on the market and/or put into service the first time.

6.3 Formulation guidance for instructions

Instructions shall begin with a goal, for example, "Mounting the wheel", "Changing the oil". The goal shall be formatted as a headline and presented in the table of content, if applicable.

The writing style and vocabulary shall be tailored to the target group (see <u>4.3</u>). The text of instruction handbooks shall be formulated so that the user can easily understand it thanks to consistent, accurate, unambiguous, complete, logical, concise and simple writing (see <u>Annexes B</u> and <u>C</u>).

6.4 Simple wording for instructions

Instructions shall be described in one of the following ways:

- writing instructions in a sequential order, preferably one below the other;
- writing one instruction per sentence. Only two instructions per sentence may be given if they are to be performed simultaneously.

Each instruction can consist of four parts:

- a) the number of the instruction or other typographic means to indicate the order of the instructions (start with number 1, not 0);
- b) the wording of the instruction;
- c) the explanation, i.e. the purpose or reason for the instruction; and
- d) the effect of the instruction in order to check the operation of the requested function:
 - 1) describing the result of an instruction, where necessary;
 - 2) describing the status of the machine or process following the completion of an instruction, where necessary;
 - 3) with several results, explaining the situations each instruction brings about;
 - 4) describing the end of an instruction and also how an abnormal termination can be detected.

The following specific instruction requirements shall be fulfilled:

- use the imperative;
- avoiding words that can change the chronology such as "after", "before";
- avoiding words that weaken the instruction;
- avoiding negative words;
- keeping descriptive sentences as short as possible;
- addressing only one subject per paragraph;
- splitting information into subtopics in separate paragraphs, if one paragraph is insufficient;
- always using the same word for a particular part or action;
- making instructions as specific as possible;
- using the same spelling everywhere.

6.5 Warnings

If applicable, a warning shall identify:

- a) the signal word;
- b) the nature or type of hazard;
- c) any possible injury or damage;
- d) how such injury or damage can be avoided.
- NOTE 1 Appropriate signal words are DANGER, WARNING and CAUTION. See ISO 3864-2.

NOTE 2 See also ISO 7000 and ISO 7010.

7 Forms of publication

The instruction handbook shall be provided in the form(s) as agreed with the customer. When providing the instruction handbook, the manufacturer shall be aware of applicable legal requirements of the country in which the machine is placed on the market and/or put into service the first time.

In principle, the instruction handbook can be provided in one or more of the following forms:

- a) as a paper publication;
- b) via an electronic storage medium made available with the machine;
- c) by accessing an external server, website or storage location with information who to access available with the machine;
- d) by accessing an internal server or storage location;
- e) by means of visual and/or auditory forms (human-machine interface, video, internet-based, or audio recording).

Annex A (informative)

Correspondence between ISO 12100:2010, 6.4, and this document

For the correspondence between ISO 12100:2010, 6.4, and this document, see <u>Table A.1</u>.

ISO 12100:2010	This document	ISO 12100:2010	This document
6.4.1.1	4.2	6.4.5.1 d)	<u>5.2.3, 5.2.7</u>
6.4.1.2	<u>4.1</u>	6.4.5.1 e)	<u>5.2.9</u>
6.4.1.3	4.1	6.4.5.1 f)	5.2.12
6.4.2 a)	Out of scope	6.4.5.1 g)	5.2.2.3
6.4.2 b)	Whole document	6.4.5.1 h)	5.2.9
6.4.2 c)	Out of scope	6.4.5.2 a)	4.7
6.4.2 d)	Out of scope	6.4.5.2 b)	6.2
6.4.3 a)	Out of scope	6.4.5.2 c)	<u>4.4</u> b)
6.4.3 b)	Out of scope	6.4.5.2 d)	4.4 b)
6.4.3 c)	Out of scope	6.4.5.2 e)	<u>4.10, B.2, B.4</u>
6.4.3 d)	Out of scope	6.4.5.2 f)	<u>5.2.1.1</u> b)
6.4.3, second paragraph	<u>5.2.9</u>	6.4.5.2 g)	Out of scope
6.4.4 a)	Out of scope	6.4.5.3 a)	<u>5.2.1.1</u> a)
6.4.4 b)	Out of scope	6.4.5.3 b)	4.1
6.4.4 c)	Out of scope	6.4.5.3 c)	<u>4.4</u> b), <u>6.3</u>
6.4.5.1 a)	5.2.4	6.4.5.3 d)	Reference to IEC/ IEEE 82079-1 in <u>Clause 1</u> , Note 3
6.4.5.1 b)	<u>5.2.5.1, 5.2.5.2, 5.2.5.5</u>	6.4.5.3 e)	<u>Clause 7</u>
6.4.5.1 c)	<u>5.2.3</u>		

Table A.1 — Correspondence

Annex B

(informative)

Presentation and formatting

B.1 Font and font size

The font and font size of printed information should be sufficiently clear and large to ensure legibility. For continuous text in printed instruction handbooks, 8-point font to 14-point font should be used. The x-height of a font should be at least 1,5 mm. Precautions, warnings and safety instructions should stand out compared to the normal font. One or more functions such as bold, italic, font size, should be used. Text in capital letters should be avoided as much as possible. Text should not be underlined as this can make words less legible. See Table B.1.

Table B.1 — Minimum recommended text font sizes and heights of safety signs and graphical symbols according to IEC/IEEE 82079-1:2019, Table 4

Product/ information	Location and role of	High con- trast dark	Low contrast	Complex character	Other remarks	Safety signs a sym	nd graphical ools	
document size	instruction	text on light background	colours or white on	sets (e.g. Kanji)		Symbols gen- erally	Safety signs	
Instructions viewed from up to 1 m distance on floor-standing products	critical on product markings	14 pt bold BE68.3 1,0QGO aeocld	16 pt bold BE68.3 1,0QGO aeocld	_	Consider using large print fonts specially developed to help people with visual impairments to	Consider using large print fonts specially developed to help people with visual impairments toAs appl Otherwise a viewing distan attention needs ed or the symb recogn		icable. ccording to ce from which s to be attract- ol needs to be nized.
	text	14 pt	16 pt	_	read signs and labels at 30 cm to 100 cm	Less than 15 unlikely to be critical on-proc	mm height sufficient for luct markings.	
Instructions on desk-top products, information in printed manuals or single-fold	critical on product markings	14 pt bold BE68.3 1,0QGO aeocld	16 pt bold BE68.3 1,0QGO aeocld					
leaflets and documents intended for printing by user	headings	12 pt BE68.3 1,0QGO aeocld	14 pt BE68.3 1,0QGO aeocld	_	Serif fonts may be used (but sans-serif preferred)	5 mm mini- mum height (or 14 pt) e.g. ())	10 mm mini- mum height e.g.	
	continuous text	10 pt BE68.3 1,0QGO aeocld	12 pt BE68.3 1,0QGO aeocld	_		Do not use sa graphical syr than 14 pt cor	fety signs or nbols in less tinuous text.	
a Except for t and 3 mm m NOTE The term	he general warni iinimum in headir "point" (abbrevia	ng sign (ISO 7010 1gs to text. 🛕 ted here to "pt") is)-W001) accomp s a unit of measu	panying a text v	warning, which may sizes and spacing.	7 be: 5 mm minin	um as marking	

Product/ information	Location and role of	High con- trast dark	Low contrast	Complex character	Other remarks	Safety signs a sym	nd graphical bols
document size	instruction	text on light background	colours or white on	sets (e.g. Kanji)		Symbols gen- erally	Safety signs
Hand-held products and	critical on product	12 pt	12 pt	9 pt with 150 % line	Serif fonts may be used	5 mm mini- mum height	10 mm mini- mum height
multi-fold	markings	BE68.3	BE68.3 1,00G0	spacing	(but sans-serif		
sheets		aeocld	aeocld	電気 規格	preferred)		
	headings, decimals	10 pt	12 pt		Use only sans-serif fonts	minimum 5 mm pre-	10 mm min- imum heighta
	accimuis	BE68.3	BE68.3		at this level and	ferred	initiani neight
		aeocld	1,0QGO aeocld		Delow	4 mm/12 pt if very simple	
	continuous	9 pt	Not advised		Electron-	Do not use sa	fety signs or
	text	BE68.3 1,0QGO aeocld	smaller than 12 pt		LARGE-PRINT media should be available on demand	than 14 pt con	itinuous text.
Very small products and	markings, headings, warning	8 pt BE68.3		8 pt with 150 % line	(e.g. from web- site or point of	minimum 5 mm pre- ferred or	10 mm min- imum height ^a
with printable surface less	messages, decimals	1,0QGO aeocld		電気 規格	Salej	3 mm, if very simple	
	continuous text	6 pt BE68.3 1,00C0 aeocld				Do not use an less than 10 p tex	y symbols in t continuous ct.
^a Except for t	^a Except for the general warning sign (ISO 7010-W001) accompanying a text warning, which may be: 5 mm minimum as marking						
NOTE The term "point" (abbreviated here to "pt") is a unit of measurement of type sizes and spacing.							

Table B.1 (continued)

B.2 Emphasizing information

In every instruction handbook, a way should be employed to indicate information of special interest, in particular, precautions, warnings and safety instructions. Attention should be focused on emphasized information in instruction handbooks in a sufficiently prominent manner. A method that stands out should be considered (for example, right at the beginning and/or under a headline that attracts attention), which distinguishes the emphasized information and is used commonly or consistently in practice.

A conventional method is the use of bold and italic letters, the use of lines and frames, or the use of colours. The marking methodology should be described in the preface so that users are able to understand text or images.

Avoid too much emphasizing. Too much highlighting or too many emphasized elements disctract the reader from reading the information.

B.3 Headings

Headings should be used to organize an instruction handbook. Short and clear headings help the user to find desired information.

Headings should be numbered hierarchically.

B.4 Use of colours

The use of colour should be considered for names, especially on controls and components that the user needs to identify clearly and quickly. Colour-blind users should be taken into account. The use of colour should be functional, systematic and consistent. The prescribed safety colours and signs according to the ISO 3864 series should be followed. The contrast should always be at least 70 %.

Consider the percentage of light the background reflects, and the percentage of light the printed matter reflects.

Annex C (informative)

Recommendations for writing instructions

This annex provides recommendations and examples for:

- instructions (see <u>Table C.1</u>);
- sentences (see <u>Table C.2</u>);
- words (see <u>Table C.3</u>);
- verbs (see <u>Table C.4</u>); and
- writing (see <u>Table C.5</u>).

Recommendation	Not preferred	Preferred
Use the active voice.	Make sure that the machine is clean.	Clean the machine.
Use positive wording.	Do not remove tabs.	Leave the tabs.
Use action words instead of a noun style.	Usage, avoidance	Use, avoid
Speak directly to the user.	The user must pull the black lever toward himself.	Pull the black lever towards you.
Keep sentences as short as possible.	Make sure the ON button is pressed.	Press the ON button.
Each instruction contains only one operation. Only give two instructions per sentence if they are to be performed simultaneously.	Drain the cooling system, flush with water, fill it with CRYO, finally let the engine warm up 10 min with CRYO without load.	 Drain the cooling system. Flush the cooling system with water. Fill the cooling system with CRYO. Allow the engine to warm up 10 min without load.
Avoid words such as "after", "be- fore", "for", "prior to"	Unplug the cable after the power is switched off.	Switch off the power.Unplug the cable.
Avoid words that weaken the in- struction.	You can turn off the device.	Switch the device off.

Table C.1 — Instructions

Recommendation	Not preferred	Preferred		
One topic per sentence.	The assembly consists of two side panels and two connecting plates which are attached with a binge	The assembly consists of two side panels and two connecting plates.		
	to each other and are bolted to the main panel.	These panels are attached to each other with a hinge. The connecting plates are attached to the main panel with four screws.		
Use nouns instead of pronouns.	It may protrude maximum 15 cm.	The load may protrude maximum 15 cm.		
Omit no verbs.	Thermostat to 90 °C.	Set the thermostat to 90 °C.		
Use bullets when the order is unimportant.	The control panel contains an on/ off switch, a start button and a	The control panel contains the fol- lowing buttons:		
	stop button.	 an on/off switch a start button a stop button 		
Use a list with letters or numbers when the order is important.	Remove the label as the carriage is retracted and open the isolation valves, then push the carriage slow- ly out (taking care that the other parts are not touched!), and then	a) Pull the carriage in.b) Remove the label.c) Open the isolation valves.		
	close the valves.	d) Push the carriage slowly and ensure it does not touch other parts.e) Close the isolation values.		

Table C.2 — Sentences

Table C.3 — Words

Recommendation	Not preferred	Preferred
Do not use a verb as a noun.	Pressing the button occurs.	Press the button.
Always use the same word for a particular item or action.	Close valve 6.	Close valve 6.
	Open flap 7.	Open valve 7.
Make instructions as specific as possible.	Check the temperature.	Ensure that the temperature remains in the range from 30 °C to 37 °C.

Table C.4 — Verbs

Recommendation	Not preferred	Preferred	
Avoid complex combinations.	For the cleaning of the machine press the button.	Press the button to clean the machine.	
Use the active form.	The machine is adjusted by the user.	The user adjusts the machine.	
Use a clear and functional verb to describe an operation.	Ensure the machine is adjusted.	Carry out adjustment of the machine.	

Recommendation	Not preferred	Preferred	
Be specific and unambiguous.	Try to keep the distance as small as possible.	The distance should not exceed 4 mm.	
Avoid non-quantifiable adjectives or adverbs.	Turn a few times on the handle.	Turn the handle twice clockwise.	
Use no double negatives.	Do not turn off the machine without exiting the program.	a) Exit the program.b) Turn the machine off.	
Provide clear references.	The machine has six motors. They are started with the white button.	The machine has six motors, num- bered 1 to 6. These six motors can be started by pressing the white buttons (1 to 6) on control panel F.	
Write notes as additional informa- tion, not as instructions (proce- dure steps).	NOTE Wait about 15 s until the gyro is stabilized.	NOTE The gyroscope is stabilized after about 15 s.	

Table C.5 — Writing

Bibliography

- [1] ISO 3864 (all parts), Graphical symbols Safety colours and safety signs
- [2] ISO 7000, Graphical symbols for use on equipment Registered symbols
- [3] ISO 7010, Graphical symbols Safety colours and safety signs Registered safety signs
- [4] ISO 11161:2007, Safety of machinery Integrated manufacturing systems Basic requirements
- [5] ISO/TR 22100-4:2018, Safety of machinery Relationship with ISO 12100 Part 4: Guidance to machinery manufacturers for consideration of related IT-security (cyber security) aspects
- [6] ISO/IEC Guide 51:2014, Safety aspects Guidelines for their inclusion in standards
- [7] IEC 61310, Safety of machinery Indication, marking and actuation
- [8] IEC/IEEE 82079-1:2019, Preparation of information for use (instructions for use) of products Part 1: Principles and general requirements

this Page has been intertionally left blank

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 2016 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

Headquarters:

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Head (Publication & Sales), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the website-www.bis.gov.in or www.standardsbis.in.

This Indian Standard has been developed from Doc No.: MED 40 (24381).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Manak Bl <i>Telephon</i>	havan, 9 Bahadur Shah Zafar Marg, New Delhi 110002 es: 2323 0131, 2323 3375, 2323 9402	Website: www.bis.gov.in	
Regional	Offices:		Telephones
Central	: 601/A, Konnectus Tower -1, 6 th Floor, DMRC Building, Bhavbhuti Marg, New Delhi 110002	{	2323 7617
Eastern	: 8 th Floor, Plot No 7/7 & 7/8, CP Block, Sector V, Salt Lake, Kolkata, West Bengal 700091	{	2367 0012 2320 9474
Northern	: Plot No. 4-A, Sector 27-B, Madhya Marg, Chandigarh 160019	{	265 9930
Southern	: C.I.T. Campus, IV Cross Road, Taramani, Chennai 600113	;	2254 1442 2254 1216
Western	: 5 th Floor/MTNL CETTM, Technology Street, Hiranandani (Mumbai 400076	Gardens, Powai	25700030 25702715

Branches : AHMEDABAD, BENGALURU, BHOPAL, BHUBANESHWAR, CHANDIGARH, CHENNAI, COIMBATORE, DEHRADUN, DELHI, FARIDABAD, GHAZIABAD, GUWAHATI, HARYANA (CHANDIGARH), HUBLI, HYDERABAD, JAIPUR, JAMMU, JAMSHEDPUR, KOCHI, KOLKATA, LUCKNOW, MADURAI, MUMBAI, NAGPUR, NOIDA, PARWANOO, PATNA, PUNE, RAIPUR, RAJKOT, SURAT, VIJAYAWADA.