

---

---

उर्वरक प्रयोजनों के लिए केस्टरसीड केक —  
विशिष्टि  
(पहला पुनरीक्षण)

**Castorseed Cake for Fertilizer  
Purposes — Specification**  
( *First Revision* )

ICS 65.080

© BIS 2024



भारतीय मानक ब्यूरो  
BUREAU OF INDIAN STANDARDS  
मानक भवन, 9 बहादुर शाह ज़फर मार्ग, नई दिल्ली - 110002  
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG  
NEW DELHI - 110002  
[www.bis.gov.in](http://www.bis.gov.in) [www.standardsbis.in](http://www.standardsbis.in)

## FOREWORD

This Indian Standard (First Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Soil Quality and Fertilizers Sectional Committee had been approved by the Food and Agriculture Division Council.

This standard was first published in 1964 to provide guidance on production of a quality castorseed oilcake. In the preparation of this standard, assistance was derived from the data furnished by the manufacturers of oilcake in the country and other technical institutions. Reference was also made to Bulletin No. 174 (1933) 'Composition of important manures' issued by the Department of Agriculture, Bombay.

In this revision, the standard has been brought out in the latest style and format of the Indian Standards as well as references to Indian Standards wherever applicable have been updated. It also incorporates two amendments issued to previous version of this standard.

The composition of the Committee responsible for revision of the standard is given in [Annex F](#).

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 2022 'Rules for rounding off numerical values (*second revision*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

*Indian Standard***CASTORSEED CAKE FOR FERTILIZER PURPOSES —  
SPECIFICATION***( First Revision )***1 SCOPE**

This standard prescribes the requirements and methods of test for castorseed cake for use as fertilizer. The oilcake obtained by all the processes, including solvent extraction, is covered in this standard.

**2 REFERENCES**

The standards given below contain provisions which through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent edition of these standards:

<i>IS No.</i>	<i>Title</i>
IS 265 : 2021	Hydrochloric acid — Specification ( <i>fifth revision</i> )
IS 266 : 2024	Sulphuric acid — Specification ( <i>fourth revision</i> )
IS 323 : 2009	Rectified spirit for industrial use — Specification ( <i>second revision</i> )
IS 460 (Part 1) : 2020	Test sieves — Specification: Part 1 Wire cloth test sieves ( <i>fourth revision</i> )
IS 1070 : 2023	Reagent grade water — Specification ( <i>fourth revision</i> )

**3 TERMINOLOGY**

**3.1** For the purpose of this standard, the following definitions shall apply:

**3.1.1** *Decorticated Castorseed Cake* — The material obtained by pressing or extracting castorseed after it has been well hulled or shelled.

**3.1.2** *Undecorticated Castorseed Cake* — The material obtained by pressing or extracting oil from clean castorseed without removing the outer covering.

**4 TYPES**

The material shall be of two types, namely:

- a) *Type 1* — Decorticated; and
- b) *Type 2* — Undecorticated.

**5 REQUIREMENTS****5.1 Description**

The material shall be uniform in texture, clean and free from adulterants, such as sand, dust and metallic pieces.

**5.2** The material shall pass wholly through 2.36 mm IS sieve of which not less than 70 percent shall pass through 850 micron IS sieve [*see IS 460 (Part 1)*]

**5.3** The material shall also comply with the requirements given in [Table 1](#).

**6 PACKING**

The material shall be packed in clean and sound jute bags. The mouth of each bag shall be either machine-stitched or hand-stitched with strong jute twine with at least 14 stitches in each row.

**7 MARKING**

**7.1** Each bag shall be suitably marked indicating clearly that the material is ‘for use as fertilizer’ and shall also be marked with the following information:

- a) Name and type of the material;
- b) Name of the manufacturer;
- c) Batch number;
- d) Net quantity in kg;
- e) Date of packing; and
- f) Any other information required under the *Legal Metrology (Packaged Commodities) Rules, 2011*.

**7.2 BIS Certification Marking**

The product(s) conforming to the requirements of

To access Indian Standards click on the link below:

[https://www.services.bis.gov.in/php/BIS\\_2.0/bisconnect/knownyourstandards/Indian\\_standards/isdetails/](https://www.services.bis.gov.in/php/BIS_2.0/bisconnect/knownyourstandards/Indian_standards/isdetails/)

## IS 3029 : 2024

this standard may be certified as per the conformity assessment schemes under the provisions of the *Bureau of Indian Standards Act, 2016* and the Rules and Regulations framed thereunder, and the products may be marked with the Standard Mark.

### 8 SAMPLING

Representative test samples of the material shall be drawn as prescribed in [Annex E](#).

### 9 TEST METHODS

Tests shall be carried out by the appropriate methods

referred to in col (4) of [Table 1](#).

### 10 QUALITY OF REAGENTS

Unless specified otherwise, pure chemicals and distilled water (*see* IS 1070) shall be used in tests.

NOTE — Pure chemicals shall mean chemicals that do not contain impurities which affect the results of analysis.

**Table 1 Requirements for Castorseed Cake for Fertilizer Purposes**

([Clauses 5.3 and 9](#))

SI No.	Characteristic	Requirement		Method of Test, Ref to
		Type 1	Type 2	
(1)	(2)	(3)	(4)	(5)
i)	Moisture, percent by mass, <i>Max</i>	8.0	8.0	<a href="#">Annex A</a>
ii)	Water insoluble organic nitrogen, percent by mass (on moisture-free basis), <i>Min</i>	4.5	3.5	<a href="#">Annex B</a>
iii)	Total ash, percent by mass, <i>Max</i>	9.5	10.0	<a href="#">Annex C</a>
iv)	Acid insoluble ash, percent by mass (on moisture-free basis), <i>Max</i>	2.4	2.5	<a href="#">Annex D</a>

## ANNEX A

[Table 1, Sl No. (i)]

## DETERMINATION OF MOISTURE

## A-1 PREPARATION OF THE SAMPLE

Grind about 100 g of the sample so that it passes through 1.00 mm IS sieve [see IS 460 (Part 1)]. Transfer this prepared sample to a well-stoppered glass bottle.

## A-2 PROCEDURE

Weigh accurately about 5 g of the prepared sample (see A-1) in a tared aluminium dish with a cover, having a diameter of at least 50 mm and a depth of about 40 mm. Shake the dish until the contents are evenly distributed. With cover removed, place the dish and cover in an air-oven maintained at  $(102 \pm 0.5)^\circ\text{C}$  and dry for at least 2 h. Place cover on dish, cool in a desiccator and weigh. Repeat the process of heating, cooling and weighing until the

difference in mass between two successive weighings is less than one milligram.

## A-3 CALCULATION

$$\text{Moisture, percent by weight} = \frac{(M_1 - M_2)}{(M_1 - M)} \times 100$$

where

$M_1$  = mass, in g, of the dish with the material before drying;

$M_2$  = mass, in g, of the dish with the material after drying; and

$M$  = mass, in g, of the empty dish.

## ANNEX B

[Table 1, Sl No. (ii)]

## DETERMINATION OF WATER INSOLUBLE ORGANIC NITROGEN

## B-1 APPARATUS

**B-1.1 Kjeldahl Flask** — 500 ml capacity

## B-1.2 Distillation Assembly

The assembly consists of a round-bottom flask of a 1 000 ml capacity fitted with a rubber stopper through which passes one end of the connecting bulb tube. The other end of the bulb tube is connected to the condenser which is attached by means of a rubber tube to a dip tube which dips into a known quantity of standard sulphuric acid or boric acid solution contained in a conical flask of 500 ml capacity to which 3 to 4 drops of methyl red indicator solution have been added.

## B-2 REAGENTS

**B-2.1 Potassium Sulphate or Anhydrous Sodium Sulphate**

**B-2.2 Copper Sulphate**

**B-2.3 Concentrated Sulphuric Acid** — relative density 1.84 (see IS 266).

## B-2.4 Sodium Hydroxide Solution

Dissolve about 450 g of sodium hydroxide in 1 000 ml of water.

**B-2.5 Standard Sulphuric Acid** — 0.5 N

**B-2.6 Standard Sodium Hydroxide Solution** — 0.25 N

## B-2.7 Methyl Red Indicator Solution

Dissolve 1 g of methyl red in 200 ml of rectified spirit (see IS 323), 95 percent by volume.

**B-2.8 Boric Acid Solution** — saturated

Dissolve 60 g of boric acid in 1 litre of hot water, cool and allow to mature for 3 days before decanting the clear liquid.

**B-2.9 Magnesium Oxide** — carbonate free, freshly ignited

**B-3 PROCEDURE**

Transfer carefully about 2 g of the prepared sample (see [A-1](#)), accurately weighed, to the Kjeldahl flask. Add about 10 g of potassium sulphate or anhydrous sodium sulphate, about 0.5 g of copper sulphate and 25 ml or more, if necessary, of concentrated sulphuric acid. Place the flask in an inclined position, and heat below the boiling point of the acid until frothing ceases. Increase heat until the acid boils vigorously and digest for a time after the mixture is clear or until oxidation is complete (about 2 h). Cool the contents of the flask. Transfer quantitatively to the round-bottom flask with water, the total quantity of water used being about 200 ml. Add a few pieces of pumice stone to prevent bumping. Add carefully the sodium hydroxide solution in quantity which is sufficient to make the solution alkaline by the side of the flask so that it does not mix at once with the acid solution but forms a layer below the acid layer. Assemble the apparatus taking care that the tip of the dip tube extends below the surface of the standard sulphuric acid solution in the receiver. Mix the contents of the flask by shaking and distil until all ammonia has passed over into the standard sulphuric acid solution. Titrate with standard sodium hydroxide solution.

Carry out a blank determination using all reagents in the same quantities but without the material to be tested.

**B-4 CALCULATION**

Water insoluble organic nitrogen, percent by mass (on moisture free-basis)

$$= \frac{140 (B-A) N}{m (100-M)}$$

where

- $B$  = volume, in ml, of the standard sodium hydroxide solution used to neutralize the acid in blank determination;
- $A$  = volume, in ml, of the standard sodium hydroxide solution used to neutralize the excess acid in the test with the material;
- $N$  = normality of the standard sodium hydroxide solution;
- $m$  = mass, in g, of the material taken for the test; and
- $M$  = percentage moisture in the sample (see [A-3](#)).

**ANNEX C**

[Table 1, Sl No. (iii)]

**DETERMINATION OF TOTAL ASH****C-1 PROCEDURE**

Weigh accurately about 2 g of the dried material (see [A-2](#)) in a tared porcelain, silica or platinum dish. Complete the ignition by keeping in a muffle furnace at  $(550 \pm 10)$  °C until grey ash results, Cool in a desiccator and weigh. Ignite the dish again in the muffle furnace for 30 min, cool and weigh. Repeat this process until the difference in mass between two successive weighings is less than 1 mg. Note the lowest mass.

NOTE — Preserve the dish containing this ash for the determination of acid insoluble ash (see Annex D).

**C-2 CALCULATION**

Total ash (on moisture free basis), percent by mass

$$= \frac{(M_2 - M)}{(M_1 - M)} \times 100$$

where

- $M_2$  = the lowest mass, in g, of the dish with the ash;
- $M$  = mass, in g, of the empty dish; and
- $M_1$  = mass, in g, of the dish with the dried material taken for the test.

## ANNEX D

[Table 1, Sl No. (iv)]

## DETERMINATION OF ACID INSOLUBLE ASH

## D-1 REAGENTS

**D-1.1 Dilute Hydrochloric Acid** — approximately 5 N, prepared from concentrated hydrochloric acid (see IS 265).

## D-1.2 Procedure

Weigh accurately 2 g of the dried material (see A-2) in a tared porcelain, silica or platinum dish. Ignite with a Meker burner for about 1 h. Complete the ignition by keeping in a muffle furnace at  $(550 \pm 20)$  °C until grey ash results. Moisten with concentrated hydrochloric acid and evaporate to dryness. Keep in an electric air-oven maintained at  $(135 \pm 2)$  °C for about 3 h. Cool and add 25 ml of dilute hydrochloric acid, cover with a watch-glass and heat on a water-bath for 10 min. Cool and filter through Whatman filter paper No. 42 or its equivalent. Wash the residue with hot water until tile washings are free from chlorides as tested with silver nitrate solution and return the

filter paper and residue to the dish. Ignite it in a muffle furnace at  $(550 \pm 20)$  °C for 1 h. Cool in a desiccator and weigh. Ignite the dish again for 30 min, cool and weigh. Repeat this process till the difference between two successive weighings is less than one milligram. Note the lowest mass.

## D-2 CALCULATION

Acid insoluble ash (on moisture free basis), percent by mass

$$= \frac{(M_2 - M)}{(M_1 - M)} \times 100$$

where

$M_2$  = lowest mass, in g, of the dish with the acid insoluble ash;

$M$  = mass, in g, of the dish with dried material (see  $M_1$  in C-2); and

$M_1$  = mass, in g, of the empty dish.

## ANNEX E

(Clause 8)

## SAMPLING OF CASTORSEED CAKE FOR MANURING

## E-1 GENERAL REQUIREMENTS

In drawing, preparing, storing and handling samples, the following precautions and directions shall be observed.

**E-1.1** Samples shall be taken in a protected place not exposed to damp air, dust or soot.

**E-1.2** The sampling device shall be clean and dry when used.

**E-1.3** Precautions shall be taken to protect the samples, the material being sampled, the sampling device and the containers for samples from adventitious contamination.

**E-1.4** The samples shall be placed in clean and dry

containers. The sample containers shall be of such a size that they are almost completely filled by the sample.

**E-1.5** Each container shall be sealed airtight after filling and marked with full details of sampling, date of sampling, batch or code number, name of the manufacturer and other important particulars of the consignment.

**E-1.6** All the samples shall be stored in such a manner that there is no deterioration of the material.

**E-1.7** Sampling shall be done by a person agreed to between the purchaser and the vendor and in the presence of the purchaser (or his representative) and the vendor (or his representative).

## E-2 SCALE OF SAMPLING

### E-2.1 Lot

All the bags in a single consignment of the material, drawn from a single batch of manufacture shall constitute a lot. If a consignment is declared to consist of different batches of manufacture, the batches shall be grouped separately and the batches in each group shall constitute a separate lot.

**E-2.2** For ascertaining the conformity of the material in the lot to the requirements of the specification, samples shall be tested from each lot separately.

**E-2.3** The number of bags to be selected from the lot shall depend on the size of the lot and shall be in accordance with [Table 2](#).

**Table 2 Scale of Sampling**

(Clauses [E-2.3](#) and [E-3.1](#))

Sl No.	No. of Bags in the Lot	Sample Size
(1)	(2)	(3)
i)	Upto 50	3
ii)	51 to 100	4
iii)	101 to 200	5
iv)	201 to 300	7
v)	301 to 800	8
vi)	801 to 1 300	9
vii)	1 301 and above	10

The bags shall be chosen at random from the lot and for this purpose a random number table shall be used. For guidance and use of random number tables, IS 4905 may be referred. In the absence of a random number table, the following procedure may be adopted:

Starting from any bag in the lot count them as 1, 2, 3, up to  $r$  and so on where  $r$  is the integral part of  $N/n$ .  $N$  being the number of bags in the lot and  $n$  is the number of bags to be chosen. Every  $r^{\text{th}}$  bag so counted shall be withdrawn to constitute the required sample size.

### E-3 TEST SAMPLE AND REFEREE SAMPLE

**E-3.1** Draw by an appropriate sampling device equal quantities of material from the top, bottom and the sides of each bag select according to [Table 2](#). The total quantity of material drawn from each bag shall be sufficient to make triplicate determinations for all the characteristics given in the specification. Mix all

the portions of material drawn from the same bag thoroughly.

**E-3.1.1** From the mixed material from each selected bag a small but approximately equal quantity of material shall be taken from each selected bag so as to form a composite sample. The quantity of material in the composite sample shall be sufficient to make triplicate determinations for all the characteristics tested on the composite sample. The composite sample shall be divided into 3 equal parts and transferred to clean and dry containers and labelled with the particulars of sampling given in [E-1.5](#) and sealed airtight. One of these samples shall be for the purchaser, another for the supplier and the third for the referee.

**E-3.1.2** The portions of material from each selected bag (after the material for composite sample has been taken) shall constitute a test sample representing that particular bag. These shall be transferred immediately to clean and dry sample containers sealed air-tight. These shall be levelled with the particulars of sampling given in [E-1.5](#). The individual samples obtained as above shall be formed into 3 sets in such a way that each set has a test sample representing each bag selected. One of the sets shall be for the purchaser, another for the supplier and the third for the referee.

#### E-3.1.3 Referee Sample

Referee sample shall consist of a set of test samples (see [E-3.1.2](#)) and one composite sample (see [E-3.1.1](#)) and shall bear the seals of purchaser and the supplier. It shall be kept at a place agreed to between the two and used in case of a dispute.

## E-4 NUMBER OF TESTS

**E-4.1** Tests for water insoluble organic nitrogen shall be conducted on each of the individual samples.

**E-4.2** Tests for remaining characteristics given in Table 1 shall be conducted on the composite sample.

## E-5 CRITERIA FOR CONFORMITY

The lot shall be declared as conforming to the requirements of the specification if each of the test results on the individual sample satisfies the specified requirements and all test results on the composite sample meet the relevant requirements given in the specification.



## ANNEX F

*(Foreword)*

## COMMITTEE COMPOSITION

Soil Quality and Fertilizers Sectional Committee, FAD 07

<i>Organization</i>	<i>Representative(s)</i>
Natural Resource Management, New Delhi	DR SURESH KUMAR CHAUDHARI ( <i>Chairperson</i> )
Bidhan Chandra Krishi Vishwavidyalaya, Mohanpur	PROF B. MANDAL
Central Fertilizers Quality Control and Training Institute, Faridabad	SHRI SHYAM BABU
Consumer Guidance Society of India, Mumbai	DR SITARAM DIXIT
CSIR - National Environmental Engineering Research Institute, Nagpur	DR HEMANT J. PUROHIT DR B. K. SARANGI ( <i>Alternate</i> )
ICAR - Central Soil Salinity Research Institute, Karnal	DR A. K. RAI DR ASHIM DATTA ( <i>Alternate</i> )
ICAR - National Bureau of Agriculturally Important Microorganisms, Kushmaur	DR ALOK KUMAR SRIVASTAVA DR HILLOL CHAKDAR ( <i>Alternate</i> )
ICAR - National Bureau of Soil Survey and Land Use Planning, Nagpur	SHRI HRITICK BISWAS
Indian Agricultural Research Institute Library, New Delhi	HEAD (SOIL SCIENCE)
Indian Farmers Fertiliser Cooperative, New Delhi	DR TARUNENDU SINGH
Indian Institute of Soil Science, Bhopal	DR S. P. DATTA DR S. K. BEHERA
Indian Micro Fertilizers Manufacturers Association, Pune	DR RAHUL MIRCHANDANI DR R. K. TEWATIA ( <i>Alternate</i> )
Insecticides (India) Limited, Delhi	DR LOKESH CHANDER ROHELA DR RITIKA PATHAK ( <i>Alternate</i> )
Institute of Agricultural Sciences, Banaras Hindu University, Varanasi	SHRI SATISH KUMAR SINGH DR. AMITAV RAKSHIT ( <i>Alternate</i> )
International Zinc Association, New Delhi	DR SOUMITRA DAS SHRI RAHUL SHARMA ( <i>Alternate</i> )
Mahatma Phule Krishi Vidyapeeth, Rahuri	DR B. M. KAMBLE DR A. G. DURGUDE ( <i>Alternate</i> )
Ministry of Chemicals and Fertilizers, New Delhi	SHRI BALVINDER KUMAR
Multiplex Bio-Tech Private Limited, Bengaluru	SHRI MAHESH G. SHETTY
National Centre for Organic and Natural Farming, Ghaziabad	DR GAGNESH SHARMA SHRI RAVINDRA KUMAR ( <i>Alternate</i> )

**IS 3029 : 2024**

<i>Organization</i>	<i>Representative(s)</i>
National Fertilizers Limited, Noida	DR JYOTI GOEL MS MANISHA ( <i>Alternate</i> )
Tamil Nadu Agricultural University, Coimbatore	DR P. BALASUBRAMANIAM DR K. M. SELLAMUTHU
The Fertilizers Association of India, New Delhi	DR KABITA DEBNATH DAS DR SHITAL BHENDE ( <i>Alternate</i> )
BIS Directorate General	SHRIMATI SUNEETI TOTEJA, SCIENTIST 'F'/SENIOR DIRECTOR AND HEAD (FOOD AND AGRICULTURE) [REPRESENTING DIRECTOR GENERAL ( <i>Ex-officio</i> )]

*Member Secretary*  
SHRI KULDEEP MITTAL  
SCIENTIST 'B'/ASSISTANT DIRECTOR  
(FOOD AND AGRICULTURE), BIS



## Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 2016* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

### Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Head (Publication & Sales), BIS.

### Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the website-[www.bis.gov.in](http://www.bis.gov.in) or [www.standardsbis.in](http://www.standardsbis.in).

This Indian Standard has been developed from Doc No.: FAD 07 (25329).

### Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

## BUREAU OF INDIAN STANDARDS

### Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002

Telephones: 2323 0131, 2323 3375, 2323 9402

Website: [www.bis.gov.in](http://www.bis.gov.in)

### Regional Offices:

	Telephones
Central : 601/A, Konnectus Tower -1, 6 <sup>th</sup> Floor, DMRC Building, Bhavbhuti Marg, New Delhi 110002	{ 2323 7617
Eastern : 8 <sup>th</sup> Floor, Plot No 7/7 & 7/8, CP Block, Sector V, Salt Lake, Kolkata, West Bengal 700091	{ 2367 0012 2320 9474
Northern : Plot No. 4-A, Sector 27-B, Madhya Marg, Chandigarh 160019	{ 265 9930
Southern : C.I.T. Campus, IV Cross Road, Taramani, Chennai 600113	{ 2254 1442 2254 1216
Western : 5 <sup>th</sup> Floor/MTNL CETTM Technology Street, Hiranandani Gardens, Powai, Mumbai - 400076	{ 25700030 25702715

**Branches :** AHMEDABAD, BENGALURU, BHOPAL, BHUBANESHWAR, CHANDIGARH, CHENNAI, COIMBATORE, DEHRADUN, DELHI, FARIDABAD, GHAZIABAD, GUWAHATI, HARYANA (CHANDIGARH), HUBLI, HYDERABAD, JAIPUR, JAMMU, JAMSHEDPUR, KOCHI, KOLKATA, LUCKNOW, MADURAI, MUMBAI, NAGPUR, NOIDA, PARWANOO, PATNA, PUNE, RAIPUR, RAJKOT, SURAT, VIJAYAWADA.