
मशीनरी की सुरक्षा — सहायक प्रणाली
की सुरक्षा

**Safety of Machinery — Safeguarding
Supportive System**

ICS 13.110

© BIS 2024
© ISO 2021



भारतीय मानक ब्यूरो
BUREAU OF INDIAN STANDARDS
मानक भवन, 9 बहादुर शाह ज़फर मार्ग, नई दिल्ली - 110002
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI - 110002

www.bis.gov.in www.standardsbis.in

NATIONAL FOREWORD

This Indian Standard which is identical to ISO/TR 22053 : 2021 'Safety of machinery — Safeguarding supportive system' issued by the International Organization for Standardization (ISO) was adopted by the Bureau of Indian Standards on recommendation of the Safety of Machinery Sectional Committee and approval of the Mechanical Engineering Divisional Council.

The text of ISO standard has been approved as suitable for publication as an Indian Standard without deviations. Certain conventions are, however, not identical to those used in Indian Standards. Attention is particularly drawn to the following:

- a) Wherever the words 'International Standard' appears referring to this standard, they should be read as 'Indian Standard'; and
- b) Comma (,) has been used as a decimal marker while in Indian Standards, the current practice is to use a point (.) as the decimal marker.

In this adopted standard, reference appears to certain International Standards for which Indian Standards also exist. The corresponding Indian Standards, which are to be substituted in their respective places, are listed below along with their degree of equivalence for the editions indicated:

<i>International Standard</i>	<i>Corresponding Indian Standard</i>	<i>Degree of Equivalence</i>
ISO 12100 : 2010 Safety of machinery — General principles for design — Risk assessment and risk reduction	IS 16819 : 2018/ISO 12100 : 2010 Safety of machinery — General principles for design — Risk assessment and risk reduction	Identical

The Committee has reviewed the provision of the following International Standard referred in this adopted standard and has decided that it is acceptable for use in conjunction with this standard:

<i>International Standard</i>	<i>Title</i>
ISO 11161 : 2007	Safety of machinery — Integrated manufacturing systems — Basic requirements

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 2022 'Rules for rounding off numerical values (*second revision*)'. The number of significant places retained in the rounded-off value should be the same as that of the specified value in this standard.

Contents

Page

Introduction	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	2
5 Safeguarding supportive system	2
5.1 General.....	2
5.2 Description of safeguarding supportive system.....	3
5.3 Interface between SSS and SRP/CS.....	3
6 Design of safeguarding supportive system	4
6.1 General.....	4
6.2 System components.....	4
6.2.1 General.....	4
6.2.2 Identification elements.....	4
6.2.3 Human-SSS interface.....	5
6.2.4 Logic unit.....	5
6.3 Output from the credential database.....	5
6.4 Verification and validation.....	5
7 Information for use	6
Annex A (informative) Visualization of integration of SSS within IMS	7
Bibliography	8

Introduction

This document was developed to provide information about systems incorporating measures that can be introduced into machinery, especially in IMS for reducing risks based on human factors.

Due to lack of human attentiveness during any task performed in a hazard zone (for example, inspections, maintenance or set-up), safeguarding supportive systems can be used as a technical measure to minimize the probability of dangerous human errors occurring.

Indian Standard

SAFETY OF MACHINERY — SAFEGUARDING SUPPORTIVE SYSTEM

1 Scope

This document provides guidance for the design and integration of a safeguarding supportive system (SSS) which is intended to include a mode selection as part of an SRP/CS or to add a layer of personnel authentication and authorization to an IMS designed according to ISO 11161.

This document is meant to be used in conjunction with ISO 11161.

This document is applicable to the SSS but does not address personnel qualification and competency.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 11161:2007, *Safety of machinery — Integrated manufacturing systems — Basic requirements*

ISO 12100:2010, *Safety of machinery — General principles for design — Risk assessment and risk reduction*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 11161, ISO 12100 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

safeguarding supportive system

SSS

complementary risk reduction/protective measure to enable mode selection by the use of *authentication* (3.5) means

3.2

identification element

device used in the *safeguarding supportive system* (3.1), referring to all logic units and their peripheral equipment, but excluding the credential database

Note 1 to entry: Examples include readers, key switches, cameras, HMI's, industrial PLCs.

3.3

control zone

identified portion of an IMS coordinated by the control system

[SOURCE: ANSI B11.20-2017, 3.39.1]

**3.4
qualified personnel**

individual(s) who, as a result of training and experience, understands and demonstrates competence with the design, construction, operation or maintenance of the machine and the associated hazards

[SOURCE: ANSI B11.0-2020, 3.68]

**3.5
authentication**

verification of the identity of a user, process, or device, often as a prerequisite to allowing access to resources in an information system

[SOURCE: ISO/TR 22100-4:2018, 3.3, modified — In the definition, "verifying" has been changed to "verification of".]

**3.6
authorization**

right or permission that is granted to a system entity to access a system resource

[SOURCE: ISO/TR 22100-4:2018, 3.4]

**3.7
authorized personnel**

qualified personnel identified by the user (employer) or supplier to perform a specific task

[SOURCE: ANSI B11.0-2020, 3.7]

4 Symbols and abbreviated terms

HMI	human-machine interface
ID	identification
IMS	integrated manufacturing system
PLC	programmable logic controller
RF	radio frequency
RFID	radio frequency identification
SPE	sensitive protective equipment
SRP/CS	safety-related parts of a control system

5 Safeguarding supportive system

5.1 General

A safeguarding supportive system is used in conjunction with, and not in place of, guards and protective devices.

A safeguarding supportive system enables a requested mode when the authorization matches the requirements for the task to be performed.

The safeguarding supportive system affects all modes of operation requiring tasks in hazard zones including, for example, adjusting, set-up, teaching and troubleshooting. Accordingly, the safeguarding supportive system functions are based on modes of operation of the IMS described in ISO 11161:2007, 5.1.3, 8.2.2, and 8.4, and ISO 12100:2010, 6.2.11.9.

[Figure 1](#) shows a concept of the implementation of an SSS.

NOTE Details on SRP/CS are dealt with in ISO 13849-1. Details on IMS are given in ISO 11161.




Figure 1 — Concept of the implementation of a SSS

5.2 Description of safeguarding supportive system

Safeguarding supportive systems (SSS) provide the following functions:

- identification of authorized personnel;
- check that the authorization for the selected task matches with the personnel identified;
- information of the user about the task(s) authorized;
- enabling of the operating mode corresponding to the selected task(s);
- indication of the zones to be accessed by the authorized personnel.

The SSS is an additional layer which provides input(s) to the logic unit of the SRP/CS in order to enable the appropriate operating mode for the required task based on authentication. The mode selection itself is a safety function that requires SRP/CS with a performance level according to ISO 13849-1.

See also [Figure A.1](#).

5.3 Interface between SSS and SRP/CS

The interface allows information exchange between SSS and the logic unit(s) of the SRP/CS. The safety functions enabled/disabled by the SSS can include but are not limited to:

- restart;
- reset;
- release of guard locking device which locks the guard in the closed position (see ISO 14119).

6 Design of safeguarding supportive system

6.1 General

The integrator reviews the risk assessment of machinery/IMS considering the task zoning and the relevant spans-of-control. As shown in [Figure 2](#), the system components of the SSS are identification elements (see [6.2.2](#)), human–SSS interface (see [6.2.3](#)) and logic unit (see [6.2.4](#)). The SSS can be part of the SRP/CS or separated.




Figure 2 — Overview of safeguarding supportive system

The SSS design should consider as a minimum:

- a) identification elements suitable for the application;
- b) location of the identification device in relation to access zones/paths;
- c) interface to credential database;
- d) task(s) which require local operations;
- e) relevant protective devices for local operations (for example, enabling device, SPE);
- f) information to be displayed (for example, applied task, access/exit path).

6.2 System components

6.2.1 General

The system components consist of identification elements (see [6.2.2](#)), human–SSS interface (see [6.2.3](#)) and logic unit (see [6.2.4](#)).

6.2.2 Identification elements

6.2.2.1 General

The identification elements comprise any technology by which authentication can be achieved. The authentication can be related to personnel skills and/or authorization and can be used to register entry and exit to a control zone, or subsequent control zones.

The identification elements comprise of an identification device (see [6.2.2.2](#)) and an authorized personnel identification (see [6.2.2.3](#)).

6.2.2.2 Identification device

The identification device reads the authorized personnel identification and transmits the information to the logic unit of the system components (see [Annex A](#)).

The identification device should be located to easily perform the required tasks.

NOTE Examples of identification devices include biometric devices (e.g. camera), RF tag readers, barcode readers, mechanical/electromechanical key cylinders, key pads for password(s).

6.2.2.3 Authorized personnel identification

Authorized personnel identification can include biometric properties (e.g. retina scan, fingerprints) and/or identifiers assigned to the user (e.g. RF tag, authorized personnel identification card, key).

6.2.3 Human-SSS interface

The human-SSS interface is where the request is made. The human-SSS interface exchanges information with the logic unit. The human-SSS interface indicates visibly and/or audibly the IMS status information including the results of the request.

NOTE The human-SSS interface can be a keyboard, a switch, a touch panel, etc.

The following information can be considered for display:

- a) task zones that the authorized personnel can access, access paths to those zones and exit routes when necessary;
- b) selected task;
- c) tasks for which the authorized personnel is permitted;
- d) authorization results in response to a request to perform a safety-related operation.
- e) significant information of accessible adjacent task zones, for example, operating modes, if automatic/unexpected restart can occur (see ISO 12100:2010, 6.3.3.2.5).

6.2.4 Logic unit

The logic unit authenticates the authorized personnel identification and the request to the human-SSS interface with the credential database. Upon authentication, the logic unit presents authorized actions and enables the selection of the authorized personnel, e.g. selection of a mode.

6.3 Output from the credential database

The following information can be used as output from the credential database as defined by the user (see [Figure 1](#)):

- a) tasks based on the authorized personnel permissions;
- b) modes based on the authorized personnel permissions;
- c) combination of authorized personnel and tasks associated with each mode of operation.

The credential database can be part of the SSS or a remote network resource or some combination thereof.

6.4 Verification and validation

The SSS integrator should verify and validate the design and structure of the SSS according to ISO 12100:2010, 6.2.11.7.

The SSS integrator should verify and validate the mode selection meets or exceeds the requirements for the safety function according to ISO 13849-1 and ISO 13849-2.

7 Information for use

The information for use should include guidance necessary for the authorization to be granted.

Advice should be given in the information for use of the machine or IMS concerning the risks associated with the handling of authorized personnel identification (ID cards, RFID tags, keys, etc.) and also about the availability of spare authorized personnel identifications.

See also ISO 11161:2007, Clause 9, and ISO 20607.

Annex A (informative)

Visualization of integration of SSS within IMS

See [Figure A.1](#).




Figure A.1 — Elements relating to an SSS with all details regarding the SRP/CS and the IMS

Bibliography

- [1] ISO 13849-1:2015, *Safety of machinery — Safety-related parts of control systems — Part 1: General principles for design*
- [2] ISO 13850, *Safety of machinery — Emergency stop function — Principles for design*
- [3] ISO 14119:2013, *Safety of machinery — Interlocking devices associated with guards — Principles for design and selection*
- [4] ISO 20607, *Safety of machinery — Instruction handbook — General drafting principles*
- [5] ISO/TR 22100-4:2018, *Safety of machinery — Relationship with ISO 12100 — Part 4: Guidance to machinery manufacturers for consideration of related IT-security (cyber security) aspects*
- [6] ANSI B11.0-2020, *Safety of Machinery*
- [7] ANSI B11.20-2017, *Safety Requirements for Integrated Manufacturing Systems*

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 2016* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Head (Publication & Sales), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the website-www.bis.gov.in or www.standardsbis.in.

This Indian Standard has been developed from Doc No.: MED 40 (24382).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002

Telephones: 2323 0131, 2323 3375, 2323 9402

Website: www.bis.gov.in

Regional Offices:

Central : 601/A, Konnectus Tower -1, 6th Floor,
DMRC Building, Bhavbhuti Marg, New
Delhi 110002

Telephones

{ 2323 7617

Eastern : 8th Floor, Plot No 7/7 & 7/8, CP Block, Sector V,
Salt Lake, Kolkata, West Bengal 700091

{ 2367 0012
2320 9474

Northern : Plot No. 4-A, Sector 27-B, Madhya Marg,
Chandigarh 160019

{ 265 9930

Southern : C.I.T. Campus, IV Cross Road, Taramani, Chennai 600113

{ 2254 1442
2254 1216

Western : 5th Floor/MTNL CETTM, Technology Street, Hiranandani Gardens, Powai
Mumbai 400076

{ 25700030
25702715

Branches : AHMEDABAD, BENGALURU, BHOPAL, BHUBANESHWAR, CHANDIGARH, CHENNAI, COIMBATORE, DEHRADUN, DELHI, FARIDABAD, GHAZIABAD, GUWAHATI, HARYANA (CHANDIGARH), HUBLI, HYDERABAD, JAIPUR, JAMMU, JAMSHEDPUR, KOCHI, KOLKATA, LUCKNOW, MADURAI, MUMBAI, NAGPUR, NOIDA, PARWANOO, PATNA, PUNE, RAIPUR, RAJKOT, SURAT, VIJAYAWADA.