

सड़क वाहन — संपीड़ित प्राकृतिक गैस
(सीएनजी)/जैव-संपीड़ित प्राकृतिक गैस
(जैव-सीएनजी)/द्रवित पेट्रोलियम गैस
(एलपीजी) — ईंधन प्रणाली के घटक —
सीएनजी/जैव-सीएनजी/एलपीजी —
कोष्ठ/उप-कोष्ठ
(पहला पुनरीक्षण)



Road Vehicles — Compressed
Natural Gas (CNG)/Bio-Compressed
Natural Gas (Bio-CNG)/Liquefied
Petroleum Gas (LPG) — Fuel
System Components — CNG/
Bio-CNG/LPG — Compartment/
Sub-compartment
(First Revision)

ICS 43.060.40

© BIS 2024



भारतीय मानक ब्यूरो
BUREAU OF INDIAN STANDARDS
मानक भवन, 9 बहादुर शाह ज़फर मार्ग, नई दिल्ली - 110002
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI - 110002

www.bis.gov.in www.standardsbis.in

FOREWORD

This Indian Standard (First Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Automotive Vehicles Running on Non-Conventional Energy Sources Sectional Committee had been approved by the Transport Engineering Division Council.

This standard was first published in 2008 to specify definitions, test methods and requirements of compartments/sub-compartments of CNG on-board fuel system components, intended for use on motor vehicles defined in IS 14272. Later on through an amendment published in 2012, the scope of this standard was extended to LPG on board fuel system components along with some other changes. This version of the standard incorporates the content of the amendment issued to the standard in 2012. In this revision, bio-CNG is also added to the scope of this standard keeping in view the technological advancements that have taken place since its last publication.

In the formulation of this standard considerable assistance has been derived from the following AIS standards issued by the Automotive Research Association of India:

AIS 024 (Rev. 1) (Part A) — Safety and procedural requirements for type approval of gaseous fuelled vehicles — Part A (Automotive application)

AIS 024 (Rev. 1) (Part B) — Safety and procedural requirements for type approval of gaseous fuel agricultural tractors — Part B (Agricultural tractors application)

AIS 024 (Rev. 1) (Part C) — Safety and procedural requirements for type approval of gaseous fuel vehicles — Part C (CEV's application)

AIS-025 (Version 3) — Safety and procedural requirements for type approval of LPG operated vehicles

AIS 026 (Version 3) — Code of Practice for use of LPG Fuel in internal combustion engine to power 4 wheeled vehicles and heavy motor vehicles

AIS 027 (Version 3) — Code of practice for use of LPG fuel in internal combustion engine to power 2 & 3 wheeled vehicles

AIS 028 (Rev.1) (Part A) — Code of practice for use of gaseous fuels in internal combustion engine vehicles — Part A (Automotive application)

AIS 028 (Rev. 1) (Part B) — Code of practice for use of gaseous fuels in internal combustion engine agricultural tractors — Part B (Agricultural tractors application)

AIS 028 (Rev. 1) (Part C) — Code of practice for use of gaseous fuels in internal combustion engine construction equipment vehicles (CEV's) — Part C (CEV's application)

This standard is one of the series of Indian Standards published on CNG/Bio-CNG/LPG onboard fuel system components. Other standards in the series are:

<i>IS No.</i>	<i>Title</i>
IS 15710 : 2024	Road vehicles — Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components — General requirements and definitions
IS 15711 : 2024	Road vehicles — Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components — Performance and general test methods (<i>first revision</i>)
IS 15712 : 2024	Road vehicles — Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components — Automatic valve (solenoid valve) (<i>first revision</i>)

[\(Continued on third cover\)](#)

Indian Standard

ROAD VEHICLES — COMPRESSED NATURAL GAS (CNG)/ BIO-COMPRESSED NATURAL GAS (BIO-CNG)/LIQUEFIED PETROLEUM GAS (LPG) — FUEL SYSTEM COMPONENTS — CNG/BIO-CNG/LPG COMPARTMENT/SUB-COMPARTMENT

(*First Revision*)**1 SCOPE**

1.1 This standard specifies definitions, test methods and requirements of compartments/sub-compartments of CNG/bio-CNG/LPG on-board fuel system components, intended for use on motor vehicles defined in IS 14272.

1.1.1 This standard is applicable to CNG/bio-CNG/LPG fuel system components intended to be used on vehicles using compressed natural gas/bio-compressed natural gas/liquefied petroleum gas in accordance with IS 15320-1 (mono-fuel or bi-fuel applications or dual fuel applications).

1.1.2 This standard is not applicable to the following:

- a) Liquefied natural gas (LNG) fuel system components located upstream of, and including, the vaporizer;
- b) Fuel containers;
- c) Stationary gas engines;
- d) CNG/bio-CNG/LPG fuel systems components for the propulsion of marine craft; and
- e) Hydrogen natural gas blend (HCNG) fuel system components.

1.1.3 This standard is based upon a service pressure for compressed natural gas/bio-compressed natural gas as a fuel at 20 MPa (200 bar) and liquefied petroleum gas as a fuel at 1 MPa (10 bar) settled at 15 °C.

2 REFERENCES

The standards given below contain provisions which, through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most

recent edition of these standards:

<i>IS No.</i>	<i>Title</i>
IS 14272 : 2011	Automotive vehicles — Types — Terminology
IS 15061 : 2002	Automotive vehicles — Flammability requirements
IS 15710 : 2024	Road vehicles — Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components — General requirements and definitions

3 DEFINITIONS

For the purpose of this standard following definition in addition to those given in IS 15710 shall apply.

3.1 Self-extinguishing/No Bum Rate (SE/NBR) — The material stops burning before it has burnt for 60 s from the start of timing and has not burnt more than 50.8 mm (2 inch) from the point where the timing was started.

4 TESTS**4.1 Construction**

4.1.1 Hatches, covers or construction joints, which may need to be opened or dismantled during maintenance or inspection, shall be capable of being opened at least 10 times without adverse effects on durability.

4.1.2 Hinges and locking devices of hatches and covers shall be designed to prevent the dislodgment of the hatch or cover when in the closed and locked position.

4.1.3 The construction of compartments/sub-compartments shall be such that when subjected to a pushing force of 60 kgf applied at any point on any external face of the sub-compartment, any resultant damage shall not be of a nature to permit

To access Indian Standards click on the link below:

https://www.services.bis.gov.in/php/BIS_2.0/bisconnect/knowyourstandards/Indian_standards/isdetails/

gas leakage in the event of pressure testing as per [4.3](#). The pushing force shall be applied by a measuring instrument having a flat circular face of 20 mm diameter.

4.2 Material

The pliable material (non-metallic material) of compartments/sub-compartments shall be sufficiently strong to resist mechanical damage, preserve venting integrity, shall not support combustion and shall meet the following minimum criteria.

4.2.1 Resistance to Cold Cracking

The material shall withstand a bend of 180° applied within 0.5 s around a 6 mm diameter former at temperature - 35 °C without cracking.

4.2.2 Flammability Test

When tested for horizontal burning rate as per Annex A of IS 15061, the material shall be self-extinguishing/no burn rate (SE/NBR).

NOTE — If the size of component is insufficient for drawal of sample as per standard, then the sample size shall be selected as per mutual agreement between the test agency and the manufacturer.

4.2.3 Resistance 10 Ultraviolet Degradation

When tested as per [Annex A](#) of this standard, presence of stabilizer for ultraviolet degradation shall be confirmed.

4.3 Hydrostatic Test

When a compartment/sub-compartment has been subjected to hydrostatic internal pressure of 30 kPa (0.3 bar) applied for 5 min, sealing materials or gaskets shall not be displaced or otherwise lose integrity during the test.

5 MARKING

5.1 Each compartment/sub-compartment shall be legibly and indelibly marked with the following:

- a) Manufacturer 's name or trade-mark or symbol;

- b) Part No. or unique identification mark; and
- c) Date of manufacture or batch No.

NOTE — Marking for compartment/sub-compartment shall be applicable if it is a separate component.

5.2 BIS Certification Marking

The product(s) conforming to the requirements of this standard may be certified as per the conformity assessment schemes under the provisions of the *Bureau of Indian Standards Act, 2016* and the Rules and Regulations framed thereunder, and the products may be marked with the Standard Mark.

6 TECHNICAL INFORMATION TO BE SUBMITTED BY THE COMPONENT MANUFACTURER

Technical information to be submitted by the component manufacturer for component type approval/type test shall contain at least following information:

- a) Manufacturer's name, trade-mark or symbol;
- b) Part No. or unique identification mark;
- c) Model/type No.; and
- d) Drawings with relevant dimensions and materials.

7 NUMBER OF SAMPLES FOR TESTING

Minimum two numbers of compartments/sub-compartments shall be provided with suitable adaptors/plugs for its opening to the test agency for testing.

8 CHANGES IN TECHNICAL SPECIFICATIONS OF A TYPE APPROVED COMPONENT AND EXTENSION OF APPROVAL

Any modification in technical specification of already type approved component shall require re-type test/extension of approval at the discretion of certification authority, based on the justification provided by the component manufacturer and reviewed by the certification authority, which has granted type approval.

ANNEX A

(Clause 4.2.3)

TEST METHOD TO DETERMINE THE PRESENCE OF ULTRAVIOLET DEGRADATION AGENT (UV STABILIZER)**A-1 SCOPE**

This test method is intended to provide a general technique to determine the presence of ultraviolet degradation agent (UV stabilizer) present in the samples. This method is useful in performing a qualitative analysis.

A-2 SUMMARY OF THE TEST PROCEDURE

This test method consists of a method in which the acetone extract of the sample under test is prepared in the form of thin film or capillary film and its spectrum is collected over IR range of 4 000 cm^{-1} to 400 cm^{-1} . The spectrum is then compared with any internationally available library, such as atlas of hummel polymer library spectra or with the enhanced polymer additives library such as saddler, FDM, nicole, RAPRA or any other library spectra.

A-3 APPARATUS

Fourier transform infrared spectrometer with wave number range of 7 800 cm^{-1} to 350 cm^{-1} .

A-4 REAGENTS**A-4.1 Acetone****A-5 PROCEDURE**

The representative test quantity of sample is extracted with acetone solvent for 16 h. The extract is dried and then subjected to FTIR spectrometer test.

The sample prepared from the above techniques is mounted to a suitable sample holder and kept inside sample compartment of optical bench of IR

spectrometer and its infrared spectrum is collected keeping the following instrumental parameters according to the nature of the sample:

- a) The environmental conditions for equipment are maintained. They are as follows:
 - 1) Room temperature: 0 °C to 35 °C; and
 - 2) Relative humidity: 20 percent to 80 percent.
- b) The optical bench is switched on and is allowed to initialize;
- c) The resolution is set to 4.0 cm^{-1} , No. of scans to 40, apodization to Happ-Ganzel and wave number range from 4 000 cm^{-1} to 400 cm^{-1} ;
- d) Background spectrum is collected without the sample in the compartment.
- e) The sample spectrum is collected with the prepared sample in the compartment after collecting background spectrum.
- f) The sample spectrum collected is baseline corrected and normalized to compare with the standard spectrum from the library using search commands.

A-6 REPORT

The obtained FTIR spectrum is searched in any internationally available library, such as atlas of hummel polymer library spectra or with the enhanced polymer additives library such as saddler, FDM, nicole, RAPRA or any other library spectra for best matching spectrum of ultraviolet stabilizer.

ANNEX B

(Foreword)

COMMITTEE COMPOSITION

Automotive Vehicles Running on Non-Conventional Energy Sources Sectional Committee, TED 26

<i>Organization</i>	<i>Representative(s)</i>
Automotive Research Association of India (ARAI), Pune	DR S. S. THIPSE (Chairperson) SHRI A. D. DEKATE
A B Process Technologies, Pune	SHRI KUNAL CHOPDE
Ashok Leyland Ltd, Chennai	SHRIMATI SUCHISMITA C. SHRI MUTHUKUMAR N. (<i>Alternate</i>)
Automotive Component Manufactures Association of India, New Delhi	SHRI SANJAY TANK MISS SEEMA BABAL (<i>Alternate</i>)
Bajaj Auto Ltd, Pune	SHRI MILIND J. PAGARE SHRI ARVIND V. KUMBHAR (<i>Alternate</i>)
Bosch Limited, Bengaluru	SHRI BHARADWAJ M. KRISHNAMURTHY SHRI VIKRAM K. (<i>Alternate</i>)
Central Institute of Road Transport, Pune	SHRI SAMIR SATTIGERI SHRI V. V. JOSHI (<i>Alternate</i>)
Central Pollution Control Board, New Delhi	SHRI A. SUDHAKAR SHRI SUNEEL DAVE (<i>Alternate I</i>) SHRI KEDARNATH DAS (<i>Alternate II</i>)
CLH Gaseous Fuel Applications Ltd, Gurugram	SHRI SHISHIR AGRAWAL SHRI GAGAN AGRAWAL (<i>Alternate</i>)
Delhi Transport Corporation, New Delhi	SHRI VIKAS BATRA
GAIL (India) Limited, New Delhi	SHRI ASHISH KUMAR MITTAL SHRI LOKESH MEHTA (<i>Alternate</i>)
Indian Auto LPG Coalition, Faridabad	SHRI SHISHIR AGRAWAL SHRI SUYASH GUPTA (<i>Alternate</i>)
Indian Institute of Petroleum, Dehradun	SHRI WITTISON KAMEI SHRI ROBINDRO LAIRENLAKPAM (<i>Alternate</i>)
Indian Institute of Science, Bengaluru	PROF R.V. RAVIKRISHNA
Indian Institute of Technology Ropar, Rupnagar	SHRI DHIRAJ KUMAR MAHAJAN DR DEBAPRASAD MANDAL (<i>Alternate</i>)
Indian Oil Corporation Ltd, (R & D Centre), Faridabad	DR M. SITHANANTHAN
Indian Rubber Manufacturers Research Association, Thane, Mumbai	DR K. RAJ KUMAR DR BHARAT KAPGATE (<i>Alternate</i>)
International Centre for Automotive Technology (ICAT), Manesar	SHRI VAIBHAV PRASHANT YADAV SHRI VIJAYANTA AHUJA (<i>Alternate</i>)
Mahindra & Mahindra Ltd, Mumbai	SHRI RAJAMANI PARTHIBAN SHRI SHAILESH KULKARNI (<i>Alternate</i>)

<i>Organization</i>	<i>Representative(s)</i>
Mahindra & Mahindra Ltd (Truck and Bus Division), Pune	SHRI V. G. KULKARNI
Maruti Suzuki India Limited, Gurugram	SHRI GURURAJ RAVI SHRI ARUN KUMAR (<i>Alternate</i>)
Minda Emer Technologies Limited, Gurugram	SHRI VIVEK JAIN SHRI BIBHUTI KUMAR (<i>Alternate</i>)
Ministry of New and Renewable Energy, New Delhi	SHRI DIPESH PHERWANI
Petroleum and Explosive Safety Organization, Nagpur	SHRI D. K. GUPTA SHRI VIVEK KUMAR (<i>Alternate</i>)
Petronet LNG Ltd, New Delhi	SHRI PANKAJ WADHWA (<i>Alternate</i>)
Prodair Air Products India Private Ltd, Pune	SHRI RAVI SUBRAMANIAN SHRI ARUN KURUVANGATTIL (<i>Alternate</i>)
Renault India Private Limited, Mumbai	SHRI RAJENDRA KHILE SHRI VIJAY DINAKARAN (<i>Alternate</i>)
Rohan BRC Gas Equipment Pvt Ltd, Ahmedabad	SHRI STEFANO DE CAROLIS SHRI PARTHIV SHUKLA (<i>Alternate</i>)
Society of Indian Automobile Manufacturers, New Delhi	SHRI P. K. BANERJEE DR SANDEEP GARG (<i>Alternate</i>)
Swagelok – Bombay Fluid System components Pvt Ltd, Mumbai	SHRI SACHIN KOULGI SHRI HARISH TAKKE (<i>Alternate</i>)
Tata Motors Ltd, Pune	SHRI P. S. GOWRISHANKAR SHRI SHAILENDRA DEWANGAN (<i>Alternate</i>)
TVS Motor Company Ltd, Hosur	SHRI V. PATTABIRAMAN SHRI K. M. SRIKANTH (<i>Alternate</i>)
Vanaz Engineers Ltd, Pune	SHRI S. J. VISPUTE SHRI J. S. DHUMAL (<i>Alternate</i>)
Volkswagen India Pvt Ltd, Mumbai	SHRI JOREG BOUZEK SHRI PANKAJ GUPTA (<i>Alternate</i>)
BIS Directorate General	SHRI DEEPAK AGARWAL, SCIENTIST ‘F’/ SENIOR DIRECTOR AND HEAD (TRANSPORT ENGINEERING) [REPRESENTING DIRECTOR GENERAL (<i>Ex-officio</i>)]

Member Secretary
SHRI GAURAV JAYASWAL
SCIENTIST ‘C’/DEPUTY DIRECTOR
(TRANSPORT ENGINEERING), BIS

[\(Continued from second cover\)](#)

- IS 15713 : 2024 Road vehicles — Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components — Pressure regulator (*first revision*)
- IS 15714 : 2024 Road vehicles — Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components — Gas air mixer (*first revision*)
- IS 15715 : 2024 Road vehicles — Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG)/Liquefied petroleum gas (LPG) fuel system components — CNG/bio-CNG/LPG conduit (ventilation hose/pipe) (*first revision*)
- IS 15716 : 2024 Road vehicles — Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components — CNG/bio-CNG high pressure fuel line (rigid) with end connections [having pressure exceeding 2.15 MPa (21.5 bar)]
- IS 15717 : 2024 Road vehicles — Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG)/Liquefied petroleum gas (LPG) fuel system components — Petrol valve (automatic/manual)
- IS 15718 : 2024 Road vehicles — Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components — CNG/bio-CNG high pressure fuel line (flexible hose) with end connections (having pressure exceeding 2.15 MPa)
- IS 15719 : 2024 Road vehicles — Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG)/liquefied petroleum gas (LPG) fuel system components — Electrical wiring kit
- IS 15721 : 2024 Road vehicles — Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG)/Liquefied petroleum gas (LPG) fuel system components — Fire retardant material for seat, upholstery, roof and side lining
- IS 15722 : 2024 Road vehicles — Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG) fuel system components — CNG/bio-CNG flexible fuel line with or without end connections (having pressure not exceeding 2.15 MPa)
- IS 15723 : 2024 Road vehicles — Compressed natural gas (CNG)/bio-compressed natural gas (bio-CNG)/Liquefied petroleum gas (LPG) fuel system components — Current limiting devices (*first revision*)

The composition of the Committee responsible for the formulation of this standard is given in [Annex B](#).

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of test or analysis, shall be rounded off in accordance with IS 2 : 2022 'Rules for rounding off numerical values (*second revision*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 2016* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Head (Publication & Sales), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the website-www.bis.gov.in or www.standardsbis.in.

This Indian Standard has been developed from Doc No.: TED 26 (18378).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002

Telephones: 2323 0131, 2323 3375, 2323 9402

Website: www.bis.gov.in

Regional Offices:

	Telephones
Central : 601/A, Konnectus Tower -1, 6 th Floor, DMRC Building, Bhavbhuti Marg, New Delhi 110002	{ 2323 7617
Eastern : 8 th Floor, Plot No 7/7 & 7/8, CP Block, Sector V, Salt Lake, Kolkata, West Bengal 700091	{ 2367 0012 2320 9474
Northern : Plot No. 4-A, Sector 27-B, Madhya Marg, Chandigarh 160019	{ 265 9930
Southern : C.I.T. Campus, IV Cross Road, Taramani, Chennai 600113	{ 2254 1442 2254 1216
Western : 5 th Floor/MTNL CETTM, Technology Street, Hiranandani Gardens, Powai Mumbai 400076	{ 25700030 25702715

Branches : AHMEDABAD, BENGALURU, BHOPAL, BHUBANESHWAR, CHANDIGARH, CHENNAI, COIMBATORE, DEHRADUN, DELHI, FARIDABAD, GHAZIABAD, GUWAHATI, HARYANA (CHANDIGARH), HUBLI, HYDERABAD, JAIPUR, JAMMU, JAMSHEDPUR, KOCHI, KOLKATA, LUCKNOW, MADURAI, MUMBAI, NAGPUR, NOIDA, PARWANOO, PATNA, PUNE, RAIPUR, RAJKOT, SURAT, VIJAYAWADA.