भारतीय मानक Indian Standard

भूवैज्ञानिक मानचित्र, खंड और उपसतही अन्वेषी लॉग में प्रयुक्त चिह्न और संक्षिप्त रूप भाग 5 रचना, सम्पर्क तथा संरचनात्मक आकृतियों के लिए रैखिक चिह्न (पहला पुनरीक्षण)

Symbols and Abbreviations for Use in Geological Maps, Sections and Subsurface Exploratory Logs

Part 5 Line Symbols for Formation Contacts and Structural Features

(First Revision)

ICS 07.060; 01.080.30

© BIS 2024



भारतीय मानक ब्यूरो BUREAU OF INDIAN STANDARDS मानक भवन, 9 बहादुर शाह ज़फर मार्ग, नई दिल्ली - 110002 MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI - 110002 www.bis.gov.in www.standardsbis.in

October 2024

Price Group 9

Geological Investigations and Subsurface Exploration Sectional Committee, WRD 05

FOREWORD

This Indian Standard (Part 5) (First Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Geological Investigation and Subsurface Exploration Sectional Committee had been approved by the Water Resources Division Council.

In all spheres of engineering construction, data on the nature of geological formation, constituting the foundations is indispensable. Often, the data are given on maps or in geological sections using symbols and abbreviations. Geological maps and sections are also required for other activities such as mining and mineral prospecting. Such maps and sections are being prepared by various agencies in the country. In the absence of any standard for the guidance of the engineering geologist or engineer different symbols and abbreviations are being used by different agencies, resulting in entirely different representations of the same geological data. The data collected and presented by one agency for a particular purpose is often useful for other agencies investigating for a different job. It, therefore, becomes essential for all agencies to follow the same practice. This standard has been prepared to fulfil this need.

This standard (Part 5) deals with line symbols for formation contacts and structural features while other parts deal with the following:

Part 1 Abbreviations Part 2 Igneous rocks Part 3 Sedimentary rocks Part 4 Metamorphic rocks

The standard was first published in 1992. This revision has been brought out to bring the standard in latest style and update with respect to the latest field practices. In this revision, due weightage has been given to international co-ordination among the standards and practices prevailing in different countries in addition to relating it to the practices in the field in this country. In this revision, assistance have been derived from ISO 710 'Graphical symbol for use on detailed maps, plans and geological cross section'.

The composition of the Committee responsible for the formulation of this standard is given in Annex A.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test, shall be rounded off in accordance with IS 2 : 2022 'Rounding off numerical values (*second revision*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Indian Standard

SYMBOLS AND ABBREVIATIONS FOR USE IN GEOLOGICAL MAPS, SECTIONS AND SUBSURFACE EXPLORATORY LOGS

PART 5 LINE SYMBOLS FOR FORMATION CONTACTS AND STRUCTURAL, FEATURES

(First Revision)

1 SCOPE

The symbols covered in this standard (Part 5) are:

- a) Line symbols for formation contacts and other structural features;
- b) Symbols for surface openings and exploration;
- c) Symbols for underground working and exploration, and
- d) Other miscellaneous symbols.

2 BASIC PRINCIPLES OF REPRESENTATION

2.1 The symbols used are intended to characterize the existing state as found in nature and shall not be used to represent genetic processes and their connections.

2.2 The tectonic elements can be regarded as surfaces or lineations characterized by their situations in space.

2.2.1 Planes

Tectonic planes are represented by their traces in the reference plane. The basic symbols for traces is a continuous line to which additional symbols characterizing the nature of the surface are added.

2.2.2 Lineation

Lineations are represented by their projection on the reference plane. The basic symbols for the projection of lineations is a compound line of alternate dots and dashes to which additional symbols characterizing the nature of the lineations in question are added.

2.2.3 Indication of Position

The position of the planes and lineations are given by the oriented representation of their traces and projections on the map or plan.

3 LINE SYMBOLS FOR FORMATION, CONTACTS AND STRUCTURAL FEATURES

3.1 The line symbols representing formation contacts and various structural features are given in tabular form as listed below:

Contacts	Table 1
Faults	Table 2
Folds	Table 3
Planar features	Table 4
Line features	Table 5
Slip plane and minor shear	Table 6
seams	
Contours and isopleths	Table 7

NOTE — For representing the fault, letter 'F' may be indicate at both the ends of the symbol. Similarly, for lineament, letter 'L' may be used at both the ends of the symbol.

4 SYMBOLS FOR SURFACE OPENINGS AND EXPLORATION

The symbols representing surface openings and exploration are given in tabular form as listed below:

Symbols for use in large scale maps	Table 8
Symbols for use in small scale maps	Table 9

5 SYMBOLS FOR UNDERGROUND WORKING AND EXPLORATION

The symbols representing underground workings and such exploration are given in Table 10.

6 OTHER MISCELLANEOUS SYMBOLS

Symbols for sections, water wells and springs and other miscellaneous items are given in Table 11.

Table 1 Line Symbols for Contacts

(<u>Clauses 3.1</u>)

Sl No. (1)	Description (2)	Symbol (3)
i)	Contact	
ii)	Contact showing dip, vertical contact with topside known	45 90
iii)	Overturned contact, showing dip	65
iv)	Approximate contact	
v)	Possible contact	Q
vi)	Concealed contact	

Table 2 Line Symbol for Faults

Sl No. (1)	Description (2)	Symbol (3)
i)	Fault	
ii)	Fault, showing dip	60 90
iii)	Fault, approximately located	
iv)	Fault, inferred or doubtful	
v)	Concealed fault	· · ·
vi)	Lineament	
vii)	Fault (showing bearing and plunge of grooves, striation or slickensides)	65

Table 2 (Concluded)		ıded)
 Sl No. (1)	Description (2)	Symbol (3)
 viii)	Fault, showing dip (U-upthrown side, D-downthrown side)	U D 65
ix)	Fault (bar and ball on downthrown side)	
x)	Fault showing relative horizontal movement	
xi)	Fault (showing bearing and plunge of apparently downthrown block)	D 65 D 43 NORMAL REVERSE
xii)	Normal fault (hachures on downthrown side)	
xiii)	Reverse fault (R, upthrown side)	<u>۲</u>
xiv)	Thrust fault (T, upper plate)	⊢ 50
xv)	Thrust fault (sawteeth on upper plate, major thrust fault)	
xvi)	Overturned thrust fault, sawteeth in dip direction, bar on side of tectonically	
xvii)	higher plate Fault (shear or mylonite) zone showing dip	
xviii)	Fault breccia	$ \begin{array}{c} \Delta \bigtriangledown \land \Delta \land \Delta \\ \Delta \bigtriangledown \Box \land \bigtriangledown \frown \frown \frown \end{array} \end{array} $
xix)	Fault, intruded by dyke	- × × × × × × × ×
xx)	Termination of fault	———————————————————————————————————————

 Table 2 (Concluded)

Table 3 Line Symbols for Folds

Sl No.	Description	Symbol
(1) i)	(2) Anticline, showing crestline	(3)
1)	Antienne, snowing crestine	
ii)	Anticline showing crestline and direction of plunge	
iii)	Anticline showing crestline and plunge	20
iv)	Asymmetric anticline showing crestline and plunge, shorter arrow indicates steeper limb	15
v)	Asymmetric anticline showing dip of limbs and plunge	$\frac{20}{20}$ $\frac{50}{20}$
vi)	Overturned anticline showing direction of dip of limbs and plunge	<u>10</u>
vii)	Inverted anticline, arrows show direction of dip of limbs	- \
viii)	Dome	
ix)	Antiform	+
x)	Syncline showing troughline	+

Sl No.	Description	Symbol
(1)	(2)	(3)
xi)	Syncline showing troughline and direction of plunge	
xii)	Syncline showing troughline and plunge	15
xiii)	Asymmetric syncline showing trough line and plunge. Short arrow indicates steeper limb	
xiv)	Asymmetric syncline showing dip of limbs and plunge	<u>15</u>
xv)	Overturned syncline showing direction of dip of limbs and plunge	
xvi)	Basin	
xvii)	Inverted syncline, arrows show direction of dip of limbs	-
xviii)	Synform, drawn on foilation, cleavage or bedding	ŧ
xix)	Monocline showing trace and plunge of axes, dashed where approximately located	
xx)	Anticlinal bend showing trace and plunge of axis. Dashed where approximately located	
xxi)	Synclinal bend showing trace and plunge of axis. Dashed where approximately located	S
xxii)	Minor anticline, showing plunge	⁶⁶ -
xxiii)	Minor syncline, showing plunge	

 Table 3 (Continued)

Sl No. (1)	Description (2)	•	mbol (3)
xxiv)	Minor fold axis, showing plunge	FA	15
xxv)	Minor fold axis, horizontal	FA	-
xxvi)	Minor folds showing plunge of axes	ñ	20

Table 3 (Concluded)

Table 4 Planar Features

(*Clause* 3.1)

SI No. (1)	Description (2)	Symbol (3)
i)	Strike and dip of beds	50
ii)	Strike and dip of beds (top beds known from sedimentary features, used only in areas of complex structure where overturning is also recognized)	50
iii)	Strike and dip of overturned beds	65
iv)	Strike and dip of overturned beds (top of beds known)	
v)	Strike of vertical beds (top of beds known)	†
vi)	Strike of vertical beds	
vii)	Component of dip (dot marks point of observation)	•
viii)	Horizontal beds	\oplus
ix)	Strike and dip of beds and plunge of slicken-sides	25

Sl No.	Description	Symbol
(1)	(2)	(3)
x)	Strike and dip of foliation	^20
xi)	Strike of vertical foliation (relation- ship of foliation or shistosity, to bedding not shown in outcrop)	
xii)	Horizontal foliation	_ +
xiii)	Crumpled, plicated, crenulated, or undulatory beds and average dip	
xiv)	Strike and dip of foliation and parallel bedding	10
xv)	Strike of vertical foliation and parallel bedding	×
xvi)	Strike and dip of foliation and parallel bedding	22
xvii)	Horizontal foliation and bedding	
xviii)	Strike and dip of cleavage	16
xix)	Strike of vertical cleavage	⊢−−−−1
xx)	Horizontal cleavage	ιŢι




Table 4 (Concluded)

Contrasting symbols can be used to distinguish between different kinds of planar structures : Type of planar structure should be specified in explanation.

Table 5 Line Symbols for Liner Features

Sl No. (1)	Description (2)	Symbol (3)
i)	Bearing and plunge of lineation	-
ii)	Vertical lineation (use open symbol in combination with line symbols)	
iii)	Vertical beds, showing horizontal lineation	
iv)	Horizontal beds showing trend of horizontal lineation	
v)	Vertical beds showing plunge of lineation	
vi)	Horizontal lineation	
vii)	Strike and dip of foliation and plunge of lineation	38 75

Table 5 (Continued)			
Sl No. (1)	Description (2)	Symbol (3)	
viii)	Vertical foliation showing horizontal lineation	-	
ix)	Strike and dip of foliation showing horizontal lineation	50 	
x)	Strike and dip of beds and plunge of lineation	14 25	
xi)	Vertical foliation and vertical lineation	\rightarrow	
xii)	Strike of vertical foliation showing plunge of lineation	⁸²	
xiii)	Approximate strike of folded beds showing plunge of fold axes	80	
xiv)	Attitude of overturned beds and parallel foliation	15	
xv)	Attitude of foliation and overturned beds, strikes parallel but dips differ	50 30	
xvi)	Double lineation	38 35	
xvii)	Strike and dip of beds and intersecting slip cleavage (symbols joined at points of observation)	40	
xviii)	Strike and dip of beds and intersecting slip cleavage	70 20	
xix)	Strike and dip of joints	10	
xx)	Strike of vertical joints		

 Table 5 (Continued)




Table 5 (Concluded)

Table 6 Line Symbols for Slip Planes and Minor Shkar Seams

(<u>C</u>	lause	3.	1)
$(\underline{\smile},$	citibe	2.	-

Sl No. (1)	Description (2)	Symbol (3)
(1) i)	Joint plane	JP
ii)	Slip plane	SP
iii)	Shear zone – 1 cm to 5 cm (thick crushed rock)	<u> </u>
iv)	Shear zone – 5 cm to 15 cm (thick crushed rock)	
v)	Shear zone – thickness of zone defined by border lines	
vi)	Glide crack	GL

Table 7 Lines Symbols for Contours and Isopleths

Sl No.	Description	Symbol
(1)	(2)	(3)
i)	Structure contours drawn on top (or base) of given geological horizon, long-dashed where control less accurate, short dashed where datum is above land surface, contour interval 5 m, arrow indicates direction of dip (structure contours generally not shown as concealed; may be omitted in areas of no information. Arrows used only where	
	index contours fail to show dip).	125
ii)	Outcrop point used for structural control	
iii)	Isopachs	
iv)	Isograds (add key mineral names to map and describe in explanation)	SILLIMANITE
		STAUROLITE

	(<u>Cla</u>	<u>ause 4</u>)
Sl No.	Description	Symbol
(1)	(2)	(3)
i)	Vertical shaft	S-1 S-1
ii)	Inclined shaft	IS-1 IS-1
iii)	Portal or slit	P-1 P-1
iv)	Portal or open cut	P0-1 >
v)	Trench	T-1 T-2
vi)	Prospect pit or open cut	0C-1 0C-1
vii)	Drill hole (up to and including 150 mm)	DH-1 DH-1
viii)	Drill hole, large diameter (more than 150 mm)	DH-1 DH-1
ix)	Drill hole (no geological data available)	HD

Table 8 Symbols for Surface Openings and Exploration for Use in Large Scale Maps


⁽Clause 4)

Sl No. (1)	Description (2)	Symbol (3)
x)	Auger hole (up to and including 150 mm)	AH-1 AH-1
xi)	Auger hole, large diameter (above 150 mm)	AH-1 AH-1
xii)	Drill hole, inclined (showing bearing and inclination for surface)	50°/S 30° W
xiii)	Mine dump	

 Table 8 (Concluded)

NOTE — Wherever two symbol. are given, the left hand figure denotes the proposed and the right hand figure, the completed working.

Table 9 Symbols for Surface Openings and Exploration for Use in Small Scale Maps



SI No.	Description	Symbol
(1) iv)	(2)	(3)
iv)	Inaccessible tunnel, adit or slope	$) - + - \rangle - + -$
v)	Trench	
vi)	Prospect pit	\times
vii)	Sand, gravel, clay or placer pit	$\times \times$
viii)	Mine, quarry, glory hole or open pit	$\propto \propto$

 Table 9 (Concluded)

NOTE — The left hand figure denotes the proposed, and the right hand figure, the completed working.

Table 10 Symbols for Under Ground W	Vorking and Exploration
-------------------------------------	-------------------------

	(<u>Clause 5</u>)		
Sl No.	Description	Symbol	
(1)	(2)	(3)	
i)	Shaft at surface		
ii)	Shaft, above and below level		

Table 10 (Concluded)			
SI No.	Description	Symbol	
(1)	(2)	(3)	
iii)	Bottom of shaft (show bottom of pump by note on map of lower level)		
iv)	Winze or head or raise		
v)	Raise or winze extending through level		
vi)	Raise or foot of winze		
vii)	Stopes (can also be explained by note stoped above or stoped below)		
viii)	Oil well	\bigcirc	
ix)	Shaft or dig	\bigcirc	
x)	Dry hole (Showing formation and altitude at surface, formation at bottom of hole and total depth)		
		Km 350 Kd 450	

 Table 10 (Concluded)

Sl No.	Description	Symbol
(1)	(2)	(3)
i)	Thrust (arrow shows relative direction of movement)	
ii)	Fault (arrow shows relative direction of movement)	
iii)	Fault, showing lateral movement (T towards observer; A away from observer, may be combined with arrows to show strike slip and dip slip movement)	-320
iv)	Drill hole or well on section (showing surface altitude and depth in m) (angle of deviation from vertical plotted)	ТА
v)	Drill hole or wall projected to section (showing surface altitude and total depth in m)	350
vi)	Nonflowing well	\bigcirc
vii)	Flowing well	

Table 11 Symbols for Sections, Water Wells and Springs and Other Miscellaneous Items

(<u>Clause 6</u>)

	I able 8 (Continued)	
Sl No.	Description	Symbol
(1)	(2)	(3)
viii)	Test hole, abandoned or not in use	\bigcirc
ix)	Nonflowing well with pumping plant [generally shown on blue (drainage) base plate in ground-water and surface-water reports]	\bigcirc
x)	Flowing well with pumping plant	
xi)	Spring	
xii)	Thermal spring	T T
xiii)	Mineral spring	M
xiv)	Glacial striae	
		*

 Table 8 (Continued)

Sl No.	Description	Symbol	
(1)	(2)	(3)	
xv)	Line of stratigraphic section	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	
xvi)	Line of section (generally omitted from explanation, used only to avoid confusion with other line)	Α	A

 Table 8 (Concluded)

ANNEX A

(*Foreword*)

COMMITTEE COMPOSITION

Geological Investigations and Subsurface Exploration Sectional Committee, WRD 05

Organization	Representative(s)
In Personal Capacity Gurugram (G-202, JMD Garden Sohna Road, Sector 33 Gurugram - 122018)	DR P. C. NAWANI (<i>Chairperson</i>)
Aecs Engineering and Geotechnical Services Pvt Limited, Noida	DR TANU RAGHUVANSHI Shri Sanjeev Trehan (<i>Alternate</i>)
Afcons Infrastructure Limited, Mumbai	DR SUNIL BASARKAR DR LAKSHMANA RAO MANTRI (<i>Alternate</i>)
Aimil Limited, New Delhi	SHRI LAXMIDHAR MOHAPATRA SHRI HEMAN MANCHANDA (Alternate)
Central Soil and Material Research Station, New Delhi	SHRI N. P. HONKANDAVAR Shri Hari Dev (<i>Alternate</i>)
Central Water and Power Research Station, Pune	DR G. DHANUNJAYA Shri V. Chandra Shekar (<i>Alternate</i> I) Shri B. Suresh Kumar (<i>Alternate</i> II)
Central Water Commission, New Delhi	SHRI SAMIR KUMAR SHUKLA SHRI K. REKHA RANI (Alternate)
CSIR - Central Building Research Institute, Roorkee	SHRI KOUSHIK PANDIT DR P. K. S. CHAUHAN (<i>Alternate</i>)
CSIR - Central Institute for Mining and Fuel Research, Dhanbad	DR J. K. MOHNOT DR ASHOK KUMAR SINGH (<i>Alternate</i>)
Ferro Concrete Construction Pvt Ltd, Indore	Dr Mahavir Bidasaria
Geological Survey of India, New Delhi	SHRI P. K. GAJBHIYE SHRI IMTIKUMZUK (Alternate)
Gujarat Engineering Research Institute, Vadodara	SHRI N. R. MAKWANA SHRI R. K. CHAUHAN (Alternate)
Himachal Pradesh Power Corporation Limited, Shimla	SHRI ER R. K. KAUNDAL SHRI SANJAY RANA (Alternate)
Indian Institute of Remote Sensing, Dehradun	DR R. S. CHATTERJEE
Indian Institute of Technology, Dhanbad	SHRI LOHIT KUMAR NAINEGALI Dr Avinash Kumar Singh (<i>Alternate</i>)
Indian Institute of Technology, Indore	SHRI MANISH KUMAR GOYAL
J&K State Power Development Corporation Limited	Shri Ravi Pandita
M/S Parsons Overseas Ltd, New Delhi	SHRI SANJAY RANA SHRI ASHUTOSH KAUSHIK (<i>Alternate</i>)

Organization	Representative(s)		
Narmada Control Authority, Indore	SHRI M. K. CHAUHAN		
National Institute of Rock Mechanics, Bengaluru	DR AJAY KUMAR NAITHANI DR SANDEEP NELLIAT (<i>Alternate</i>)		
National Hydroelectric Power Corporation Ltd, Faridabad	SHRI AJAY SINGH SHRI MOHINDER PAL SINGH (<i>Alternate</i>)		
National Thermal Power Corporation Limited, Noida	SHRI NAVEEN KUMAR JAIN Shri Bhuvnesh Kumar <i>(Alternate)</i>		
North Eastern Electric Power Corporation Ltd, Shillong	Shri Girish Kalita		
Satluj Jal Vidyut Nigam Limited, Shimla	SHRI AJAY KUMAR Shri Brijesh Badoni (<i>Alternate</i>)		
Tehri Hydro Development Corporation India Limited, Rishikesh	Shri Ajay Kumar		
Uttarakhand Jal Vidyut Nigam Ltd, Dehradun	DR HARISH BAHUGUNA		
In Personal Capacity (House No. 120, Jalshakti Vihar (NHPC Society) Sector PHI 1, Pocket 4 Greater Noida, Gautam Budhha Nagar - 201310)	SHRI GOPAL DHAWAN		
In Personal Capacity (Falt no. 4123, Ace Golfshire, Tower 4, Sector 150, Noida - 201310)	SHRI R. K. GOEL		
In Personal Capacity (68 Sadhbhawna Apartment, Plot no. 13 IP Extesnsion, Patparganj Delhi - 110092)	SHRI SHYAM LAL KAPIL		
In Personal Capacity (D 31, Jal Vidyut Apts. Sector 21 C. Part III, Faridabad - 121001)	SHRI IMRAAN SYEED		
BIS Directorate General	Shri R. Bhanu Prakash Scientist 'E'/ Director and Head (Water Resources) [Representing Director		

Member Secretary Shri Ajay Meena Scientist 'B'/Assistant Director (Water Resources), BIS

GENERAL (*Ex-officio*)]

this Page has been intertionally left blank

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 2016 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

Headquarters:

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Head (Publication & Sales), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the website-www.bis.gov.in or www.standardsbis.in.

This Indian Standard has been developed from Doc No.: WRD 05 (21370).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Manak Bhavan, 9 Bahadur Shah Zafar <i>Telephones</i> : 2323 0131, 2323 3375, 23	0	Website: www.bis.gov.in	
Regional Offices:			Telephones
Central : 601/A, Konnectus Tower DMRC Building, Bhavbhu Delhi 110002			2323 7617
Eastern : 8 th Floor, Plot No 7/7 & 7/ Salt Lake, Kolkata, West I			<pre>{ 2367 0012 2320 9474 { 265 9930</pre>
Northern : Plot No. 4-A, Sector 27-B, Chandigarh 160019	Madhya Marg,		265 9930
Southern : C.I.T. Campus, IV Cross Road, Taramani, Chennai 600113		<pre>{ 2254 1442 2254 1216</pre>	
Western : 5 th Floor/MTNL CETTM, Technology Street, Hiranandani Gardens, Powai Mumbai 400076		{ 25700030 25702715	

Branches : AHMEDABAD, BENGALURU, BHOPAL, BHUBANESHWAR, CHANDIGARH, CHENNAI, COIMBATORE, DEHRADUN, DELHI, FARIDABAD, GHAZIABAD, GUWAHATI, HARYANA (CHANDIGARH), HUBLI, HYDERABAD, JAIPUR, JAMMU, JAMSHEDPUR, KOCHI, KOLKATA, LUCKNOW, MADURAI, MUMBAI, NAGPUR, NOIDA, PARWANOO, PATNA, PUNE, RAIPUR, RAJKOT, SURAT, VIJAYAWADA.