

(PREVIEW)

IS 4468 (Part1) : 1997
(Reaffirmed 2001)

Indian Standard
**AGRICULTURAL WHEELED TRACTORS -
REAR-MOUNTED THREE-POINT LINKAGE
PART 1 CATEGORIES 1,2,3 AND 4**
(*Fourth Revision*)

1 SCOPE

1.1 This standard specifies the dimensions and requirements of the three-point linkage for the attachment of implements of equipment to the rear of agricultural wheeled tractors.

1.2 It specifies four categories to be used on different ranges of agricultural tractors as shown in Table 1.

Table 1 Categories

Category	PTO Power at Rated Rotational Frequency of Engine ¹) kW
(1)	(2)
1	Up to 48
S2	Up to 92
3	80 to 185
4	150 to 350

1) Determined in accordance with IS 12036 : 1995.

Category 4 has been divided into two parts, 4 L and 4 H, depending on the location of the power takeoff (PTO). Category 4L and 4H dimensions apply to tractors with the PTO, respectively, below and above the rear axle centreline.

2 REFERENCES

The following standards contain provisions which, through reference in this text constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below:

IS No,	Title
6483 : 1981	Linch pin assembly (first <i>revision</i>)
12036 : 1995	Agricultural tractors – Test procedures - Power tests for power take off (first <i>revision</i>)