Draft AMENDMENT NO. 4

TO IS 17427: 2020

WOODEN (TIMBER) PALLETS FOR PACKAGING, STORAGE AND TRANSPORTATION — SPECIFICATION

(*Page* 8, Table under *clause* 10) — Substitute following table for existing Table:

Sl No	Dimensions (mm) $L \times W \times H$
i)	$1\ 000 \times 1\ 200 \times 145$
ii)	$1\ 100 \times 1\ 100 \times 145$
iii)	800 × 1 200 × 145
iv)	1 300 × 1 100 × 150
v)	1 200 × 1 200 × 150
vi)	$1\ 000 \times 1\ 000 \times 140$
vii)	$800 \times 800 \times 140$
viii)	$1\ 200 \times 1\ 800 \times 200$
ix)	$1500 \times 600 \times 130$ (For storage other than food grain only)
x)	$1500 \times 900 \times 130$ (For storage other than food grain only)
xi)	1 200 × 1 200 × 140
xii)	$1500 \times 600 \times 180$ (For Food Grain storage only)
xiii)	$1500 \times 900 \times 180$ (For Food Grain storage only)

(*Page* 8 and 9, *clause* **10.2**, sixth sentence) — Delete the following:

'In case of storage pallets for food grain height of pallet shall be minimum 145 mm. for stringers plus 35 mm for planks.'

[Page 12, Compression Test, Test Method (see also amendment 1)] — Replace-

'8.3 of IS 6219: 2024'

[Page 12, Fork Lifting Test, Test Method (see also amendment 1)] — Replace-

'8.2 of IS 6219: 2024'

(*Page* 13, *clause* 16) — Substitute the following for the existing:

16 GUIDELINES FOR MARKING OF PALLETS

16.1 The Rating Code shall be calculated using following formula:

Rating Code = Integer Value of $\left[\frac{Rated\ Load\ Value}{250}\right]$ discarding any decimal value.

- **16.2** Pallets shall be marked with their Rating Code according to their rating.
- **16.3** No pallet shall be marked with safe working load in kg, however, assembled unit loads may be marked with gross and tare weight as required for safe handling.
- **16.4** Safe working load (SWL) shall vary according to load severity and the allocation of safe working Load values is the responsibility of the unit load supervisor assembler. Example:

A 1 000 kg rated pallet (validated by tests) shall be marked BIS/4. It may, at various stages of its life when being used for differing unit loads, be carrying more or less than 1 000 kg.

[*Page* 14, **ANNEX A**] — Delete the Annexure.

[*Page* 15, **ANNEX B**] — Delete the Annexure.

(TED 24)