#### CENTRAL MARKS DEPARTMENT-III

Ref: CMD-III/16: IS 269

03 July 2020

Subject: Use of marble slurry as performance improver in Ordinary Portland Cement as per IS 269: 2015.

- 1. This has reference to the above subject and email dated 02/07/2020 is received from M/s Shree Cement Ltd which is self-explanatory.
- 2. CaCO<sub>3</sub> content in marble slurry is more than requirement specified in IS 269: 2015 but same is not included in list of performance improver permitted as per Table 1 of IS 269: 2015.
- 3. In view of the above, CED is requested to examine the matter and confirm whether marble slurry can be used as per performance improver in OPC as per IS 269 : 2015.

Head (CED)

43/178/mg/2020

(S D Rane

Sc-F

CIN No. : L26943RJ1979PLC001935

Phone : 01462 228101-6
Toll Free : 1800 180 6003 / 6004
Fax : 01462 228117 / 228119

E-Mail : shreebwr@shreecementItd.com

Website : www.shreecement.in



## SHREE CEMENT LTD.

Read. Office:

BANGUR NAGAR, POST BOX NO.33, BEAWAR 305 901, RAJASTHAN, INDIA SCL/BIS/RAS/2019-20/

Date: 30.06.2020

To, The Director& Head Bureau of Indian Standards, Manak Bhawan,Bahadur Shah Zafar Marg New Delhi

Sub: Utilization of Marble Slurry as Performance Improver in OPC as per IS 269: 2015

Sir,

This has refer to above subject, we wish to submit that Marble Slurry from Makrana / Kishangarh contains % CaCO3 and MgCO3 around 80% and 9 % respectively. Marble slurry waste, consisting in fine-grained residues resulting from operations of cutting and polishing of different types of limestone, and it can be re-used as raw materials suitable for applications in cement sectors as a replacement of limestone for clinker manufacturing as well as performance improver in OPC manufacturing.

Marble slurry chemically, physically, mineralogically and morphologically demonstrate high content of calcium oxide and comparable with cement grade limestone (CaCO3), which shows that marble slurry can be re-used as a Limestone raw material with no treatments. Besides the economic benefits, transforming a waste into an important economic resource involves environmental advantages. Since it implies a reduction in the need for landfill storages and in the consequent associated detriments. Marble slurry can be an important economic resource capable of promoting the sustainability.

We have send samples of Marble Slurry and OPC-43 (with use of 5% Marble Slurry prepared in Lab Ball Mill) to National Test House Jaipur for testing (Reports are attached herewith).

We wish to submit that BIS has already approved use of marble / dolomite as performance improver up to 8% in revised specification of White Portland Cement as per IS 8042 : 2015

In view of above, kindly accord your permission to utilize Marble Slurry as performance improver in limestone category for manufacturing of OPC as per specification IS 269: 2015.

Your's faithfully

For: Shree Cement Ltd.

Shailesh Hawa 6

A.V.P-(Q.C)
Shree Cement Ltd

Bangur City, Village & Post-Ras

Tehsil-Jaitaran, Distt:-Pali (Raj.)-306107

JAIPUR OFFICE : SB-187, Bapu Nagar, Opp. Rajasthan University, JLN Marg, Jaipur-302 015
Phone : 0141 4241200, 4241204, Fax : 0141 4241219

NEW DELHI OFFICE: 122-123, Hans Bhawan, 1, Bahadurshah Zafar Marg, New Delhi 110 002

Phone : 011 23370828, 23379218, 23370776, Fax : 011 23370499



#### भारत सरकार राष्ट्रीय परीक्षण शाला, ( उ.प. क्षे ) ई-763, रोड नं. 9 एफ 1, वी.को.आई. एरिया, जयपुर - 302013

#### Government of India National Test House (NWR)

E-763, Road No. 9 F 1, VKIA, Jaipur- 302 013



Number of Copies issued Single

परीक्षण प्रमाण पत्र TEST CERTIFICATE

INTERIM/FINAL REPORT

परीशण प्रमाण पत्र सं. Test Certificate No.

जारी होने की तिथि

कोड नं

पुष्ट

पृथ्ठों की संख्वा

NTH(NWR)/CH(G)/2020/00152

Date of Issue

Code No

Page

No of Pages

26/02/2020

1581400286331

जिसे वारी करना है

Issued To

पता

Address

SHREE CEMENT LTD, BEAWAR

BANGUR NAGAR, POST BOX NO. 33, BEAWAR-305901

ग्राहक का सन्दर्भ सं एवं दिनांक

Customer's Ref. No.

SCL/BWR/NTH/2019-20/

Date: 10/02/2020

पंजिका सं एवं दिनांक

Register No & Date

00152/NTH(NWR)/CH(G)/11/02/2020

परीक्षण सामग्री का विवरण Description of Test Item

परीक्षण सामग्री का पहचान Identification of Test Item One sample described as "Marble Slurry"

नमुना का विशिष्टि (यदि हीं) Product Specification (Fany)

नगुना प्राप्ति की तिथि Date of Receipt of the Test Item

कार्य सम्पादन की तिथि Date(s) of Performance of Tests

व्यावद्वत प्रणाली का पहचान Method(s) used for Test

नम्ना प्रकिया वहाँ प्रासंगिक हों Sampling Procedure where relevant 11/02/2020

From: 11/02/2020

26/02/2020

IS 1760 & ASTM C25

**Tested By** 

Approved By



### भारत सरकार राष्ट्रीय परीक्षण शाला, ( उ.प. क्षे ) ई-763, रोड नं. 9 एफ 1, वी.के.आई. एरिया, जयपुर - 302013





Number of Copies issued Single

परीक्षण प्रमाण पत्र TEST CERTIFICATE

INTERIM/FINAL REPORT

परीक्षाण प्रमाण पन्न सं.

NTH(NWR)/CH(G)/2020/00152

जारी होने की तिथि

कोड नं

पृष्ठों की संख्वा पुष्ठ

Test Certificate No

Date of Issue 26/02/2020

Code No 1581400286331 Page No of Pages

SI. No.

**Test Name** 

**Test Result** 

Limit

1

Test result

As per Annexure

टिपाणी

Note

केफियत Remarks

**Tested By** 


checked By

Approved By

सूचनार्थ / Note : इस्टिम्साइक्वेसिट्टिंगि Please See Ovesterfutist- D (Mechanical) SO (Chemical)



भारत सरकार राष्ट्रीय परीक्षण शाला, (उ.प. क्षे) ई-763, रोड नं. 9 एफ 1, वी.को.आई. एरिया, जयपुर - 302013





#### परीक्षण प्रमाण पत्र

# TEST CERTIFICATE Date of Issue Code No

Test certificate no NTH(NWR)/CH(G)/2020/00152 26/02/2020

1581400286331

No. of page 1 of 1

#### **ANNEXURE**

Sr. No.	Test Parameters	IS: Clause	Observed Value	Specified Value	Test Protocol
1	Chemical Composition (% by mass)				
1.1	Loss on ignition	Tulki saragi	40.6		IS 1760 (part 1)
1.1	Silica as (SiO <sub>2</sub> )	-	5.47	-	ASTM C25 Cl.10
1.2	Iron oxide as (Fe <sub>2</sub> O <sub>3</sub> )	-	1.58	- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	ASTM C25 Cl.13
1.3	Alumina as (Al <sub>2</sub> O <sub>3</sub> )	-	1.02	-	ASTM C25 Cl.15
1.4	Lime as (CaO)	-	44.6	-	ASTM C25 C1.16
1.5	Magnesia as (MgO)		5.74		ASTM C25 C1.18
1.6	Chloride as (Cl)	-	0.02		IS 1760 (part 5)

---- END OF TEST REPORT----

Tested By

SO (Chemical)

Akbar H 26 2

Checked By

Approved By

Sumath Kumar laha Rakesh Saint । एक प्राचनार्थ / NScientist Buckenhicathन दें / Please See Overlea Scientist D (Mechanical)

111 P TC53012 A 00000 0 1 0 2 E



भारत सरकार राष्ट्रीय परीक्षण शाला, ( उ.प. क्षे ) ई-763, रोड नं. 9 एफ 1, वी.को.आई. एरिया, जयपुर - 302013

Government of India National Test House (NWR) E-763, Road No. 9 F 1, VKIA, Jaipur- 302 013



परीक्षण प्रमाण पत्र

TEST CERTIFICATE

\_INTERIM/FINAL REPORT

Number of Copies issued Single परीशण प्रमाण पत्र सं Test Certificate No

जारी होने की तिथि

कोड नं

पुष्ठ Page पृष्ठों की संख्वा No of Pages

NTH(NWR)/CIV(G)/2020/00272

Code No Date of Issue 1581398597868 13/03/2020

SHREE CEMENT LTD, BEAWAR

जिसे जारी करना है

Issued To

पता

Address

BANGUR NAGAR, POST BOX NO. 33, BEAWAR-305901

गाहक का सन्दर्भ सं एवं दिनांक

Customer's Ref. No.

पंजिका सं एवं दिनांक Register No & Date

परीक्षण सामगी का विवरण Description of Test Item

परीक्षण सामगी का पहचान Identification of Test Item SCL/BWR/NTH/2019-20/

Date: 10/02/2020

00272/NTH(NWR)/CIV(G)/11/02/2020

One sample of OPC 43 grade cement received in a polythene

bag.

OPC 43 with 5% MARBLE SLURRY

नमुना का विशिष्टि (यदि हीं) Product Specification (F any)

नम्ना प्राप्ति की तिथि

Date of Receipt of the Test Item

कार्य सम्पादन की तिथि Date(s) of Performance of Tests

व्यावद्वत प्रणाली का पहचान Method(s) used for Test

नमुना प्रकिवा वही प्रासंगिक हों Sampling Procedure where relevant IS 269:2015

11/02/2020

From: 11/02/2020

13/03/2020

IS 4031:1988 & IS 4032:1985

Vivek Sharma

Approved By

Rakesh Saint

SO Civil

सूचनार्थ / Note : कृप्या**Scientiste Capital)** Please See Overlear



#### भारत सरकार राष्ट्रीय परीक्षण शाला, ( उ.प. क्षे ) ई-763, रोड नं. 9 एफ 1, वी.को.आई. एरिया, जयपुर - 302013





परीक्षण प्रमाण पत्र

TEST CERTIFICATE

INTERIM/FINAL REPORT

Number of Copies issued परीशण प्रमाण पत्र सं. Test Certificate No

जारी होने की तिथि

कोड नं

पृष्ठों की संख्या पृष्ठ No of Pages

NTH(NWR)/CIV(G)/2020/00272

Date of Issue 13/03/2020

Code No 1581398597868 Page

2

2

SI. No.

**Test Name** 

Single

**Test Result** 

Limit

**Full Tests** 

As per Annexure attached.

As per Annexure

**टिप्पणी** 

Note

The sample complies with the requirements of IS 269:2015 for 43 Grade Ordinary

केफियत Remarks Portland Cement in respect of the physical tests & chemical analysis carried out.

SO Civil

Vivek Sharma

Approved By

Rakesh Sain

सूचनार्थ / Note : कृप्या **Şcientistə C (Cixil)**Please See Overleaf 6 3

5301200000000 2 E



भारत सरकार राष्ट्रीय परीक्षण शाला, ( उ.प. क्षे ) ई-763, रोड नं. 9 एफ 1, वी.के.आई. एरिया, जयपुर - 302013

Government of India
National Test House (NWR)
E-763, Road No. 9 F 1, VKIA,
Jaipur- 302 013



### परीक्षण प्रमाण पत्र TEST CERTIFICATE

Test certificate no NTH(NWR)/CIV(G)/2020/00272

Date of Issue 13/03/2020 Code No 1581398597868 No. of page 1 of 1

#### **ANNEXURE**

Sr. No.	Tests	IS:Clause	Observed Value	Specified Requirement	Test Protocol
1.	Chemical Composition	6.1		Marks Market	
1.1	Ratio of percentage of Lime to percentages of Silica, Alumina and Iron Oxide		0.86	0.66 to 1.02	IS: 4032 - 1985
1.2	Ratio of percentage of Alumina to that of Iron Oxide		1.83	0.66 Min	IS: 4032-1985
1.3	Insoluble residue, (% by mass)		2.36	5.0 Max	IS: 4032-1985
1.4	Magnesia, (% by mass)		2.83	6.0 Max	IS: 4032-1985
1.5	Total Sulphur Content, calculated as Sulphuric anhydride (SO <sub>3</sub> ), (% by mass)		3.03	3.5 Max	IS: 4032-1985
1.6	Total loss on ignition, (% by mass)		2.91	5.0 Max	IS: 4032-1985
1.7	Total Chloride Content, (% by mass)		0.01	0.1 Max	IS: 4032-1985
2.	Physical Tests	7			
2.1	Fineness Specific Surface( m²/kg)		335	225 Min	IS: 4031(Pt -2)- 1999
2.2	Compressive Strength (MPa) (Cement and standard sand mortar 1:3)				
2.2.1	3 days		30.5	23 Min	IS: 4031(Pt -6)-
2.2.2	7 days		37.5	33 Min	1988
2.2.3	28days		57.5	43 Min 58 Max.	
2.3	Setting Time (minutes)				
2.3.1	Initial		135	30 Min	IS: 4031(Pt -5)-
2.3.2	Final		220	600 Max	1988
2.4	Soundness				
2.4.1	Expansion after Le chatelier test (mm)		0.50	10 Max	IS: 4031(Pt -3) -
2.4.2	Expansion after Autoclave Test (%)		(-)0.02	0.8 Max	1988

Water required for paste of Standard Consistency (%) : 27.5Temperature during period of testing (°C) :  $27\pm2$ 

..... END OF TEST REPORT .....

Tested By

epak Srivastava

Checked By

Vivek Sharma

Approved By

學學

Rakesh Saini 3 03 2

सूचनार्थ / Not**Scientist ©(किं शी**के ध्यान दें / Please See Overlied

ULR-TC539120000000267 F

0137363



### राष्ट्रीय सीमेन्ट एवं भवन सामग्री परिषद्

(भारत सरकार के वाणिज्य एवं उद्योग मंत्रालय के शासनाधीन)

#### NATIONAL COUNCIL FOR CEMENT AND BUILDING MATERIALS

(Under the Administrative Control of Ministry of Commerce & Industry, Government of India)

#### **TESTING LABORATORIES**

(NCB/TL/QM/TKRF2961)

#### INDEPENDENT TESTING LABORATORIES

**TEST REPORT** 

ULR - TC529620100000557F

No. : ITL/005380 Date : 07/08/2020

**Customer Address** 

SHREE CEMENT LTD. (BEAWAR)

BANGUR NAGAR, POST BOX NO. 33, BEAWAR-305901,

RAJASTHAN, INDIA

Reference

SCL/NCCBM/RAS, DTD.30/06/2020

Sample

Said to be Lime Stone

Identification

MARBLE SLURRY

**Condition of Sample** 

UnSealed with ID Tag

Date of Receipt

02/07/2020

Laboratory Mark -

ITLL3437/3/1

Period of Testing

07/07/2020 - 21/07/2020

**Tested for Conformity to** 

Discipline

Chemical Testing

Group

**Building Materials** 

SI No	Test Name		Test Method	Test Result	:s
1	Loss on Ignition	***************************************	IS:1760(Pt-1):1991	39.79	% by mass
2	Silica		IS:1760(Pt-2):1991	5.06	% by mass
3	Iron Oxide		IS:1760(Pt-3):1992	0.50	% by mass
4	Alumina		IS:1760(Pt-3):1992	0.96	% by mass
5	Calcium Oxide		IS:1760(Pt-3):1992	46.47	% by mass
6	Magnesium Oxide		IS:1760(Pt-3):1992	4.86	% by mass
7	Sulphuric Anhydride		ASTM C-25: 2017	1.18	% by mass
8	Alkalies	Sodium Oxide	NCB STD(MS-13-2010)	0.24	% by mass
		Potassium Oxide	NCB STD(MS-13-2010)	0.19	% by mass
		Eq. as Na2O	NCB STD(MS-13-2010)	0.37	% by mass
9	Chloride		IS:1760(Pt-5):1991	0.018	% by mass
	*******	**** ******** END OF TH	HE TEST REPORT ********	*****	

Conditions

1. Results given above refer only to the sample supplied.

The Report is being issued on the specific understanding that NCB will not in any way be involved in any action following the interpretation of the above results.

3. This report shall not be reproduced except in full without written approval from NCB.

4. Sample shall be retained for 90 days after reporting the results.

5. This report does not imply that the sample/material is approved or endorsed by NCB or NABL

Scientist/s Tinhy landy
Page 1 of 1

Dr D Yadav

**Authorised Signatory** 

Centre for Cement Research and Independent Testing



## राष्ट्रीय सीमेन्ट एवं भवन सामग्री परिषद्

(भारत सरकार के वाणिज्य एवं उद्योग मंत्रालय के शासनाधीन)

### NATIONAL COUNCIL FOR CEMENT AND BUILDING MATERIALS

(Under the Administrative Control of Ministry of Commerce & Industry, Government of India)

#### **TESTING LABORATORIES**

(NCB/TL/QM/TRF5498)

# INDEPENDENT TESTING LABORATORIES TEST REPORT

**Customer Address** 

SHREE CEMENT LTD. (BEAWAR)

ULR - TC529620100000554F

BANGUR NAGAR, POST BOX NO. 33, BEAWAR-305901,

No. : ITL/005377 Date : 07/08/2020

RAJASTHAN, INDIA

Reference SCL/NCCBM/RAS, DTD.30/06/2020
Sample Said to be Ordinary Portland

Ordinary Portland Cement-43 Grade

Identification

OPC-43 (WITH 5% MARBLE SLURRY)

**Condition of Sample** 

UnSealed with ID Tag

**Date of Receipt** 

02/07/2020

Laboratory Mark -

ITLL3437/1/1

Period of Testing

07/07/2020 - 07/08/2020

**Tested for Conformity to** 

IS:269-2015

Discipline

Mechanical Testing

Group Building Materials

SI T	Test Name		Test Method	Test Results		Lower Limit As Per	Upper Limit IS:269-2015
1 4	Fineness (Blaine)		IS:4031(Pt-2):1999	319	m2/Kg	225	
2 :	Setting Time	Initial	IS:4031(Pt-5):1988	80	Minutes	30	
		Final	IS:4031(Pt-5):1988	125	Minutes		600
3	Soundness	Lechatelier Exp.	IS:4031(Pt-3):1988	2.0	mm		10
		Autoclave Exp.	IS:4031(Pt-3):1988	Before aeration bar collapsed& After aeration 0.04	%		0.8
4	Comp.Strength at 72±1h		IS:4031(Pt-6):1988	39.5	МРа	23	
5	Comp.Strength at 168±2h		IS:4031(Pt-6):1988	49.5	MPa	33	-
6	Comp.Strength at 672±4h		IS:4031(Pt-6):1988	57.5	МРа	43	58
	********	********	END OF THE TEST RE	PORT ****	******	*******	

#### Conditions

1. Results given above refer only to the sample supplied.

The Report is being issued on the specific understanding that NCB will not in any way be involved in any action following the interpretation of the above results.

3. This report shall not be reproduced except in full without written approval from NCB.

4. Sample shall be retained for 90 days after reporting the results.

5. This report does not imply that the sample/material is appoved or endorsed by NCB or NABL

Scientist's

Dr D Yadav Authorised Signatory



## राष्ट्रीय सीमेन्ट एवं भवन सामग्री परिषद्

(भारत सरकार के वाणिज्य एवं उद्योग मंत्रालय के शासनाधीन)

## NATIONAL COUNCIL FOR CEMENT AND BUILDING MATERIALS

(Under the Administrative Control of Ministry of Commerce & Industry, Government of India)

#### **TESTING LABORATORIES**

(NCB/TL/QM/TRF3198)

ULR - TC529620100000555F

No. : ITL/005378

Date: 07/08/2020

# INDEPENDENT TESTING LABORATORIES TEST REPORT

**Customer Address** 

SHREE CEMENT LTD. (BEAWAR)

BANGUR NAGAR, POST BOX NO. 33, BEAWAR-305901,

RAJASTHAN, INDIA

Reference

SCL/NCCBM/RAS, DTD.30/06/2020

Sample

Said to be

Ordinary Portland Cement-43 Grade

Identification

OPC-43 (WITH 5% MARBLE SLURRY)

**Condition of Sample** 

UnSealed with ID Tag

**Date of Receipt** 

02/07/2020

Laboratory Mark -

ITLL3437/2/1

Period of Testing

07/07/2020 - 21/07/2020

**Tested for Conformity to** 

IS:269-2015

Discipline

Chemical Testing

Group Building Materials

SI No	Test Name		Test Method	Test Results		Lower Limit As Per	Upper Limit IS:269-2015
1	Loss on Ignition		IS 4032:1985	1.55	% by mass		5
2	Silica		IS 4032:1985	19.91	% by mass		
3	Iron Oxide		IS 4032:1985	5.26	% by mass		
4	Alumina		IS 4032:1985	5.21	% by mass		
5	Calcium Oxide		IS 4032:1985	63.23	% by mass		
6	Magnesium Oxide		IS 4032:1985	0.70	% by mass		6
7	Sulphuric Anhydride		IS 4032:1985	2.89	% by mass		3.5
8	Insoluble Residue		IS 4032:1985	1.13	% by mass		5
9	Alkalies.	Sodium Oxide	NCB STD(MS-13- 2010)	0.20	% by mass		
		Potassium Oxide	NCB STD(MS-13- 2010)	0.30	% by mass	-	-
		Eq. as Na2O	NCB STD(MS-13- 2010)	0.40	% by mass		*
10	Chloride		IS 4032:1985	0.026	% by mass		0.1/0.05**
11	LSF		Calculated	0.94		0.66	1.02
12	Ratio of % of Alumina to Iron Oxide		Calculated	0.99		0.66	-
	*********	******	END OF THE TEST R	EPORT ****	******	******	

\*Reference: See NOTE-1 of Table-2 in IS: 269:2015

\*\*For Prestressed Structures

#### Conditions

Page 1 of 1

1. Results given above refer only to the sample supplied.

The Report is being issued on the specific understanding that NCB will not in any way be involved in any action following the interpretation of the above results.

3. This report shall not be reproduced except in full without written approval from NCB.

4. Sample shall be retained for 90 days after reporting the results.

5. This report does not imply that the sample/material is appoved or endorsed by NCB or NABL

Scientist/s

Dr D Yadav Authorised Signatory

Centre for Cement Research and Independent Testing